

**25:1 Gear Reducer**

ITEM BMQ1100-25-3-42  
**\$59.95**



• New, GROVE FLEXALINE Model BMQ-1100-25-3-42CZ. Worm gear reducer with cast iron housing. Mount is for C flange electric motors. Output shaft extends to the right viewed from flange end.

- SPECIFICATIONS**
- Gear ratio 25:1
  - RPM 1750 in, 70 out
  - Input HP 0.19 max
  - Torque 119 in.-lbs. output
  - Input shaft 1/2" dia. hollow
  - Output shaft 1/2" d. x 1 1/8"
  - Motor mount 42CZ
  - Size 5 1/4" x 3" x 3 5/8"
  - Shpg. 12 lbs.

**29:1 Gear Reducer**

ITEM 13-1176-A  
**\$59.95**



• Used Reliance Electric cast iron worm gear reducer. 4-bolt face mount on 6" bolt diameter pattern. Output shaft extends to the right when viewing the input side.

- SPECIFICATIONS**
- Gear ratio 29:1
  - Input 1750 RPM max.
  - HP 1/3 input max.
  - Torque 430 in/lbs output
  - Input shaft 0.645" d. x 1/2" 12 T spline
  - RPM 29 output
  - Output shaft 7/8" dia. x 2" keyed
  - 4-bolt base mount on 4 1/2" x 6" ctrs.
  - Size 7 1/16" x 6 5/8" x 7 13/16"
  - Shpg. 26 lbs.

**30:1 Gear Reducer**



ITEM 13-1418  
**\$189.95**

• New, LEESON. Cast iron right-angle worm gear-reducer. Left hand output shaft when viewed from input shaft. Tapped mounting holes on top and bottom of case. Shaft input can be direct coupled, belt or chain driven. CW input rotation gives CW output rotation.

- SPECIFICATIONS**
- Model B624-30-L
  - Gear ratio 30:1
  - HP 1.33 input
  - RPM 1750 input, 58 output
  - Output torque 1113 in-lbs
  - Input shaft 3/4" diam. x 2 1/4" keyed
  - Output shaft 1 1/8" diam. x 2 3/4" keyed
  - Size 6 7/8" x 5 1/4" x 6 7/8"
  - Shpg. 33 lbs.

**35:1 Gear Reducer**



ITEM 13-990  
**\$79.99**

• New, ALLING LANDER. Foot mount gear reducer. Cast iron construction.

- SPECIFICATIONS**
- 35:1 gear ratio
  - 1/4 HP capacity
  - 840 RPM input max.
  - Input shaft 5/8" x 2" w/keyway
  - Output torque 500 in. lbs.
  - Output shaft 1" x 2" w/keyway
  - Size 7 1/2" x 7 1/2" x 8"
  - Shpg. 35 lbs.

**49:1 Winsmith Gear Reducer**

ITEM 13-1215  
**\$169.99**



• New, WINSMITH Model 3CT. Gear reducer. Output shaft extends to the right when viewed from the input side. Threaded output shaft.

- SPECIFICATIONS**
- Ratio 49:1
  - HP 0.533
  - RPM 1800 input
  - RPM 36.7 output
  - Torque 4801 in. lbs.
  - Mount 4 bolt 5" x 3 3/4"
  - Input shaft 5/8" diam. x 1 3/8" w/keyway
  - Output shaft threaded 3/4"-16 x 1 3/8"
  - Right hand output
  - Size 6" x 4 3/4" x 6 7/8"
  - Shpg. 23 lbs.

**49:1 Right Angle Gearbox**

ITEM 13-1441  
**\$49.95**



• New take-offs, STM Model RMI 50P gearbox. Aluminum housing. Motor mount has four 7 mm holes on 85 mm B.C. Four mounting holes on either side of output bore, tapped M8-1.25 on 85 mm B.C.

- SPECIFICATIONS**
- Ratio 49:1
  - Power 0.34 kW max.
  - Input 1400 RPM max.
  - Output 29 RPM max.
  - Torque 637 in.-lbs. max.
  - Motor mount IEC 71
  - Input shaft 14 mm keyed
  - Output bore accepts 1" dia. keyed shaft x 3 7/8" bore thru-length
  - Mount four tapped holes on each side of output bore
  - Size 6" x 4" x 6 3/8"
  - Shpg. 10 lbs.

**60:1 Gear Reducer**

ITEM 13-1444  
**\$59.95**



• New, Morse Model 17LT right angle gear reducer. Very compact size. Aluminum alloy case, bronze gears and tapered roller bearings.

- SPECIFICATIONS**
- Ratio 60:1
  - Power 1/8 HP max.
  - Input 1750 RPM max.
  - Output 29.2 RPM max.
  - Torque 181 in. lbs. max.
  - Input shaft 1/2" dia. x 2" with flat
  - Input centerline height 4"
  - Output shaft 1/2" dia. x 2" with flat
  - Output centerline ht. 2 1/4"
  - Mount 4 5/8" x 2 3/8"
  - Size 5 1/2" x 3 1/4" x 5 5/16"
  - Shpg. 7 lbs.

**106:1 Gear Reducer**


ITEM 13-1445  
**\$219.95**



• New, SEW-Eurodrive Model K66LP56 cast iron right angle gear reducer. Foot mounted. Input adapter for 56C electric motor.

- SPECIFICATIONS**
- Ratio 106:1
  - Power 1.4 HP max.
  - Input 1750 RPM max.
  - Output 16 RPM max.
  - Torque 3980 max.
  - Output centerline height 5 1/2"
  - Motor mount 56C
  - Input shaft coupling for 5/8" motor shaft
  - Output shaft 1 3/8" x 2 3/4" w/keyway
  - Mount 6 1/2" x 4 3/4"
  - Size 14 1/4" x 7" x 8 3/4"
  - Shpg. 90 lbs.

**50:1 Right Angle Gear Reducers**



• New, ELECTRA-GEAR Model 2400 right angle gear reducer. Platinum finish aluminum gear case with zinc plated output shaft for corrosion resistance.

- SPECIFICATIONS**
- Gear ratio 50:1
  - 1750 RPM input max.
  - 0.91 HP input max.
  - 35 output RPM
  - Input shaft 3/4" diam. x 2" w/1/4" cross hole
  - 900 in.-lbs. output torque
  - Output shaft 1 1/8" diam. x 5" full length keyed
  - 4 bolt base mount on 6 3/8" x 3 3/8" bolt centers
  - Size 7 1/2" x 6" x 7 1/4"
  - Shpg. 23 lbs.

ITEM 13-1399-L **\$99.95**

• Output shaft extends to the left when viewed from the input side.

ITEM 13-1399-R **\$99.95**

• Output shaft extends to the right when viewed from the input side.

**60:1 Gear Reducer**



ITEM 13-1308  
**\$139.95**

• New, POWER TORQ. Worm gear reducer with cast iron housing. Mount is for 56C flange electric motors. Dual hollow output shafts. The left hand output has a 4 bolt mount on 4 1/8" x 4 1/8" centers.

- SPECIFICATIONS**
- Gear ratio 60:1
  - RPM 1750 input max. 29.2 output
  - HP 0.27 input max.
  - Torque 320 in/lbs output
  - Mount 56C
  - Input shaft 5/8" diam. hollow w/keyway
  - Dual output shafts 1" diam. hollow w/keyway
  - Size 7 1/8" x 6 3/16" x 8 9/4"
  - Shpg. 28 lbs.

**60:1 Gear Reducer**



ITEM 13-1408  
**\$129.99**

• New, Ironman by Ohio Gear. Cast iron right-angle worm gear-reducer. Left hand output shaft when viewed from motor flange. Can be easily swapped to give right hand output. Tapped mounting holes on top and bottom of case.

- SPECIFICATIONS**
- 60:1 gear ratio
  - 0.18 HP input
  - 1750 RPM input
  - 29 RPM output
  - 220 in.-lbs output torque
  - 1.72" output centerline ht.
  - Motor mount 56C
  - Input 5/8" dia. keyed hollow
  - Output shaft 5/8" dia. x 2" keyed
  - Mtg. 2" x 3 1/4" bolt pattern
  - Size 6" x 6 1/2" x 6 1/4"
  - Shpg. 17 lbs.

**New Arrivals Daily**  
[www.surpluscenter.com](http://www.surpluscenter.com)

ENGINES

HYDRAULICS

PNEUMATICS

POWER TRANSMISSION  
GEAR REDUCERS

ELECTRICAL

WATER PUMPS

MISCELLANEOUS