

**1.6 RPM, 12 VDC
Inline
Gearmotor**



ITEM 5-1741
\$18.99

• New, RP2020 inline gearmotor. Ideal replacement corn pellet stove, auger motor. Aluminum gear housing. Six 10-32 bolt hole face mount on 1¹⁵/₁₆" - 4³/₈" x 2³/₈" centers.

SPECIFICATIONS

- Speed 1.6 RPM
- Voltage 12 DC
- Amperage 350 mA
- Torque 78 in - lbs.
- Rotation reversible
- Duty continuous
- Enclosure open
- Mount face
- Shaft 3/8" diam. x 1" w/flat
- Size 3³/₄" x 2³/₄" x 4³/₄"
- Shpg. 3 lbs.

**4 RPM, 12 VDC
Gearmotor**



ITEM 5-1587
\$2.99

• New, TRW 58024E right-angle miniature gearmotor. Originally made for use in automotive air-conditioning vents. Plastic housing, shaft and gears. Permanent magnet motor. Hollow shaft accepts 3/16" square shaft.

SPECIFICATIONS

- RPM 4
- Voltage 12 VDC
- 10 mA at no load
- Rotation reversible
- Duty intermittent
- Fully enclosed
- Shaft 17/32" diam. 8T spline 1⁹/₃₂" long
- Three bolt mount
- Size 4¹/₂" x 1¹/₈" x 3¹/₄"
- Shpg. 1 lb.

**10 RPM,
12 VDC**



ITEM 5-1746
\$128.95

• New, LEESON Electric inline permanent magnet gearmotor. Ball bearings.

SPECIFICATIONS

- Speed 10 RPM
- Voltage 12 DC
- Amperage 2.7 Amps
- Power 1/20 HP
- Torque 100 in - lbs.
- Gear ratio 180:1
- Rotation reversible
- Duty continuous
- Enclosure TENV
- Mount four 10/32 tapped holes on face, 2.65" x 2.65"
- Shaft 1/2" dia. x 1" w/key
- Size 7³/₄" x 3⁵/₈" x 3⁵/₈"
- Shpg. 10 lbs.

**Cargo Hoist
Motor**



ITEM 5-1167

\$349.50

• Military surplus. Very high torque - low speed. Heavy duty construction. Reconditioned.

SPECIFICATIONS

- 24 VDC
- 130 amps
- 12 RPM
- Torque 15,000 in lbs.
- Reversible
- 75% duty cycle
- Shaft 1³/₈" diam. 27 tooth x 2¹/₄"
- Size 6" diam. x 22"
- Shpg. 57 lbs.

**12 RPM, 12 VDC
Gearmotor**



ITEM 5-1697
\$9.95

• New, small gearmotor originally built for use in vending machines. Hollow output shaft accepts a 1/4" square shaft. SPDT microswitch mounted on back side, actuates during part of the output shaft rotation. All plastic housing.

SPECIFICATIONS

- Speed 12 RPM
- Voltage 12 DC
- Amperage 60 mA at no load
- Rotation reversible
- Duty intermittent
- Mount six thru-holes
- Shaft accepts 1/4" square
- Size 2¹/₄" x 2¹/₂" x 3⁵/₈"
- Shpg. 2 lbs.

**20 RPM, 12 VDC
Inline
Gearmotor**



ITEM 5-1726
\$49.95

• New, T & L INTERNATIONAL permanent magnet inline gearmotor.

SPECIFICATIONS

- Speed 20 RPM
- Voltage 12 DC
- Amperage 13 Amps
- Torque 16.75 in - lbs.
- Rotation reversible
- Duty intermittent
- Enclosure TENV
- Mount 4 bolt on 2⁹/₁₆" x 3³/₈" centers
- Shaft 1/2" diam. x 7/8" w/dual flats
- Size 7⁵/₈" x 3¹/₈" x 3⁷/₈"
- Shpg. 8 lbs.

**21 RPM,
12 VDC**



ITEM 5-1624
\$32.99

• New takeoffs, Buehler Model 1.61.031.111.06. right angle gearmotor. Permanent magnet motor. Shaft can be changed from right to left side output.

SPECIFICATIONS

- 21 RPM (no load)
- Voltage 12 VDC
- 0.2 amps (no load)
- Torque 48 in-lbs. stall
- Rotation reversible
- Duty intermittent
- Mount 3 hole on 1³/₄"
- Shaft 8mm x 1⁷/₈"
- Size 6¹/₂" x 3¹/₈" x 2⁵/₈"
- Shpg. 3 lbs.

**25 RPM,
12 VDC
Gearmotor**



ITEM 5-1648
\$119.95

• Brand new, STATURE ELECTRIC Model PL-AFSD-25AN-208 parallel shaft gearmotor. Ball and needle bearings, steel gears and cast aluminum gearbox. Two pole, permanent magnet motor with internal brushes. Ten mounting holes tapped 1/4"-20: four on motor side of gearbox, six in opposite face.

SPECIFICATIONS

- Speed 25 RPM
- Voltage 12 DC
- Amperage 3.0 no load, 6.0 cont., 37.6 peak
- HP 1/30 cont.
- Torque 100 in-lbs. cont.
- Gear ratio 208:1
- Rotation reversible
- Duty intermittent
- Fully enclosed
- Face mount, tapped holes
- Shaft accepts 1/2" hex
- Size 7" x 2⁵/₈" x 6¹/₁₆"
- Shpg. 8 lbs.



**40 RPM, 12 VDC
Right-Angle
Gearmotors**

• Brand new, BUYERS PRODUCTS. High torque, right-angle gearmotor built to fit common truck and trailer tarp systems. Forged drive gear, aluminum gearbox housing and motor end-cap, steel motor housing. Gearbox is sealed to prevent contamination. Includes a chromed plastic bolt-on cover and mounting hardware. Shaft has two 3/16" cross-holes spaced 3/4" apart. Five mounting holes in face of gearbox tapped 5/16"-18.

ITEM 5-1719

SPECIFICATIONS

- P/N 5543095
- Speed 40 RPM
- Voltage 12 DC
- Amperage 33-50 Amps
- Power 0.53 HP
- Torque 836 in-lbs.
- Gear ratio 90:1
- Rotation reversible
- Duty intermittent
- Totally enclosed
- Mount five tapped holes
- Shaft 3/4" x 3¹/₈" w/ two cross-holes
- Size 10" x 6" x 3³/₈"
- Shpg. 14 lbs.

\$179.95

ITEM 5-1720

SPECIFICATIONS

- P/N 5543895
- Speed 40 RPM
- Voltage 12 DC
- Amperage 33-75 Amps
- Power 1.2 HP
- Torque 1890 in-lbs.
- Gear ratio 90:1
- Rotation reversible
- Duty intermittent
- Totally enclosed
- Mount five tapped holes
- Shaft 3/4" x 3¹/₈" w/ two cross-holes
- Size 11¹/₈" x 6" x 3³/₈"
- Shpg. 16 lbs.

\$199.95

**42 RPM,
12 VDC**



ITEM 5-1745
\$159.95

• New, LEESON Electric inline permanent magnet gearmotor. Ball bearings.

SPECIFICATIONS

- Speed 42 RPM
- Voltage 12 DC
- Amperage 21 Amps
- Power 1/4 HP
- Torque 325 in - lbs.
- Gear ratio 58:1
- Rotation reversible
- Duty continuous
- Enclosure TENV
- Mount four 1/4-28 tapped holes on face, 5¹/₈" B.C.
- Shaft 3/4" dia. x 1¹/₈" w/key
- Size 11¹/₂" x 5" x 5"
- Shpg. 18 lbs.

**42 RPM, 12 VDC
Gearmotor**



ITEM 5-1683
\$13.95

• New, Molon Model CHM-1245-1. Slotted output from gearbox. Includes 1" dia. x 8⁵/₈" long 5 section rubber drive roller for output.

SPECIFICATIONS

- Speed 42 RPM
- Voltage 12 DC
- Amperage 0.85 Amps
- Torque 8 in - lbs.
- Rotation reversible
- Duty continuous
- Mount 4 holes 2¹/₂" x 2³/₈"
- Shaft 3/16" female w/3/16" slot
- Size 2³/₄" x 2³/₄" x 3"
- Shpg. 2 lbs.

**Ordering Information
& UPS Rates
on pages 146 - 147**