

5 RPM, 24 VDC Inline Gearmotor



ITEM 5-1840 \$129.95

• New take-off, SolFocus P/N 350-000062-000 permanent magnet inline gearmotor. Rated for 24 volts but will operate on 12 volts at reduced speed and output.

SPECIFICATIONS

- Speed 5 RPM
- Voltage 24 VDC
- Amperage 4.2 Amps
- Power 1/10 HP
- Torque 109 Nm (964.8 in.lbs.)
- Gear ratio 266.3:1
- Rotation reversible
- Duty continuous
- Enclosure TENV
- Face mount 2 bolt, 106mm (4.173") bolt circle
- Mount pilot 68mm (2.677")
- Shaft 25mm (0.984") dia. x 1 1/2" long 18T spline
- Size 18 5/8" x 5 1/16" x 6 1/4"
- Shpg. 40 lbs.

171 RPM, 24 VDC Inline Gearmotor



ITEM 5-1839 \$119.95

• New take-off, SolFocus P/N 350-000058-000 permanent magnet inline gearmotor. Rated for 24 volts but will operate on 12 volts at reduced speed and output.

SPECIFICATIONS

- Speed 171 RPM
- Voltage 24 VDC
- Amperage 12 Amps
- Power 1/3 HP
- Torque 9.1 Nm (80.5 in.lbs.)
- Gear ratio 18.7:1
- Rotation reversible
- Duty continuous
- Enclosure TENV
- Face mount 4 bolt, 80mm (3.150") bolt circle
- Mount pilot 60mm (2.362")
- Shaft 14mm (0.551") dia. x 1 5/16" long with 5mm keyway
- Size 12 1/8" x 4 9/16" x 5 1/2"
- Shpg. 19 lbs.

15 RPM, 24 VDC



ITEM 5-1451 \$4.95

• New CKD Model J209-056. DC synchronous motor attached to removable mtg. bracket.

SPECIFICATIONS

- RPM 15
- Voltage 24 DC
- Amps 0.2 no load
- Rotation CW
- Duty intermittent
- Shaft 3/16" diam. x 1/2" long w/flat
- Mount 2 bolt on 3 13/32" BC
- Size 4" x 1 3/4" x 2"
- Shpg. 1 lb.

30 RPM, 24 VDC



ITEM 5-1358 \$24.95

• New MULTI-PRODUCTS CO. INC. #2738. Offset gearbox.

SPECIFICATIONS

- RPM 30
- Voltage 24 DC
- Amps 0.68 no load
- HP 1/4s
- Torque 47 in. lbs.
- Rotation reversible
- Duty continuous
- Shaft 11 mm dia. x 12 mm w/dual flats
- Mint. 4 bolt 2 1/2" x 2" pattern
- Size 4 1/2" x 3" x 4 3/4"
- Shpg. 5 lbs.

35 RPM, 24 VDC



ITEM 5-1257 \$9.95

• New take-offs MOLON. Inline parallel shaft gear motor. Rated 24 volt DC, will run on 12 volt DC at lower speed and torque.

SPECIFICATIONS

- RPM 35
- Voltage 24 DC
- Torque 38 in. lbs. full load 7.5 in. lbs. cont.
- Rotation reversible
- Duty continuous
- Shaft 5/16" x 3/4" long w/flat
- Mount face 2 3/8" x 2 1/2" drilled/tapped
- Size 2 3/4" x 3" x 2 3/16"
- Shpg. 2 lbs.

45 RPM, 24 VDC Inline Gearmotor



ITEM 5-1660 \$9.95

• New, Molon Model CHM-2435-1. High torque output. 4 7/8" wheel with o-ring on edge to friction drive equipment. Use for drive wheel on robots. Operates at 1/2 speed on 12 VDC. Permanent magnet motor.

SPECIFICATIONS

- Speed 45 RPM
- Voltage 24 DC
- Amperage 0.28
- Torque 7.5 in.lbs.
- Rotation reversible
- Duty continuous
- Mount 4 tapped holes 2 3/8" x 2 1/2"
- Shaft 5/16" dia.
- Size 2 3/4" x 2 1/4" x 3"
- Shpg. 1 1/2 lbs.

68 RPM, 24 VDC



ITEM 5-1447 \$18.99

• New BUEHLER.

SPECIFICATIONS

- RPM 68
- Voltage 24 DC
- Amps 50 mA
- Watts 1.2
- Torque 14 in. oz.
- Rotation reversible
- Duty intermittent
- Shaft 0.2" dia. x 3/8" w/flat
- Mount face
- Size 1 3/8" diam. x 2 5/8"
- Shpg. 3/4 lb.

109 RPM, 24 VDC Gearmotor



ITEM 5-1693 \$14.95

• New, MABUCHI inline parallel shaft gearmotor. Die-cast gear housing. Mtg.holes are drilled and tapped with 10-32 thread.

SPECIFICATIONS

- Speed 109 RPM
- Voltage 24 DC
- Amperage 78 mA (no load)
- Torque 2.5 in. - lbs.
- Duty intermittent
- Enclosure open
- Mount 4 bolt face on 2 3/8" x 2 1/2" centers
- Shaft 5/16" dia. x 3/8" w/ flat
- Size 2 1/8" x 2 3/4" x 3 1/16"
- Shpg. 2 lbs.

180 RPM, 24 VDC



ITEM 5-1812 \$8.95

• New, inline gearmotor. Die cast zinc gear housing. Will operate on 12 volts at reduced output speed.

SPECIFICATIONS

- Speed 180 RPM
- Voltage 24 DC
- Amperage 0.6 Amps
- Torque 2.5 in. - lbs.
- Rotation reversible
- Duty continuous
- Shaft 1/4" dia. x 5/8" w/dual flats and crosshole
- Shaft crosshole 1/8"
- Mount 4 bolt 1.25" x 1.56" centers
- Size 2 3/4" x 2 1/2" x 2 3/4"
- Shpg. 1 lb.

120 RPM, 22 VDC Inline Gearmotors



• New, IGARASHI permanent magnet inline gearmotors. Spur geartrain.

SPECIFICATIONS

- Speed 120 RPM-no load
- Voltage 22 DC
- Amperage 90 mA no-load
- Performance 70 RPM w/50 oz.in. torque, 500 mA
- Gear ratio 50
- Rotation reversible
- Duty continuous
- Mount 3 holes on face, M3 thread
- Shaft 5mm dia. x 7mm w/flat
- Size 1.3" dia. x 2.5"
- Shpg. 1 lb.

ITEM 5-1810

• Includes rubber boot over brushholders.

ITEM 5-1811

• Brushholders are exposed.

152 RPM, 36 VDC Gearmotor



ITEM 5-1801 \$7.99

• New, MAXON A-max, very compact permanent magnet precision gearmotor. Will operate on 12-36 VDC.

SPECIFICATIONS

- Speed 152 RPM
- Voltage 36 DC
- Gear ratio 64.4:1
- Power consumption 5 watts
- Rotation reversible
- Duty continuous
- Mount three M2x1.5 holes, 17mm B.C.
- Shaft 2.7mm dia. x 4mm w/flat
- Size 1 5/16" dia. x 2"
- Shpg. 1/2 lb.

128 RPM, 36 VDC



5-1423-R Pictured

• MAGNETEK. Series wound gearmotor. built for subway door openers. Operates on 36 volts DC. Available with either left or right output shaft. Aluminum gearbox housing.

SPECIFICATIONS

- RPM 128
- Voltage 36 DC
- Amps 0.8 at 36 VDC no load
- Ratio 14:1
- Rotation reversible
- Duty continuous
- Shaft 1 1/4" dia. x 1 3/8" long stepped to 5/8" dia. x 7/8" long w/keyway
- Mount base
- Size 15" x 4 1/2" x 7 1/2"
- Shpg. 20 lbs.

ITEM 5-1423-R

ITEM 5-1423-L

\$59.99 \$59.99

30 RPM, 50 VDC Gearmotor



ITEM 5-1687 \$89.95

• Used PARVALUX permanent magnet right angle gearmotor. Heavy duty construction.

SPECIFICATIONS

- Speed 30 RPM
- Voltage 50 DC
- Amperage 1.3 Amps
- Torque 62 in. - lbs.
- Gear ratio 96:1
- Rotation reversible
- Duty continuous
- Mount base
- Shaft 15 mm x 2" w/keyway
- Size 9" x 5" x 5 1/2"
- Shpg. 16 lbs.