



Hydraulic Solenoid Valves



• Brand new EATON VICKERS DG4V-3 Series. Dual solenoid directional valves for operating hydraulic cylinders, motors and other actuators. Spring centering spool action. Manual over-ride on solenoids. Valves ship with four cap-screws for mounting. Requires D03 subplate sold separately on this page. Use with two Hirschmann connectors (not incl.) for wiring.

SPECIFICATIONS



- GPM 10 1/2
- PSI 3000
- Ports D03 subplate mtg.
- Shpg. 6 lbs.



	ITEM	Price	Valve Type	Spool Details
12 VDC Amperage 3.5 Size 8 3/4" x 1 7/8" x 2 1/8"	9-6136	\$151.00	Open center	Work ports blocked in neutral
	9-6138	\$130.40	Closed center	All ports blocked in neutral
	9-6137	\$141.40	Open center	All ports open to tank in neutral
120 VAC Amperage 0.35 Size 7 3/4" x 1 7/8" x 2 1/8"	9-7235	\$189.15	Open center	Work ports blocked in neutral
	9-7237	\$204.55	Closed center	All ports blocked in neutral
	9-7236	\$192.10	Open center	All ports open to tank in neutral

Solenoid Coil Wire Connector

ITEM 11-2457



\$5.00

• Brand new HIRSCHMAN style connector for installation of wires to solenoid coil. Two connectors required for each solenoid valve. Shpg. 1/40 lb.



D03 Subplates

- Brand new D03 aluminum subplates for solenoid operated valves.
- Parallel circuit for closed center valves.
- Series circuit for open center valves.



Parallel



Series

Valves	Parallel		Series		Ports	Shpg.
	ITEM	Price	ITEM	Price		
1	9-4070-1	\$ 36.75	9-5883-1	\$ 35.95	SAE 6	2 lbs.
2	9-4070-2	\$ 89.95	9-5883-2	\$ 95.10	IN SAE 10, OUT SAE 12, Work SAE 8	6 lbs.
3	9-4070-3	\$114.95	9-5883-3	\$131.90	IN SAE 10, OUT SAE 12, Work SAE 8	7 lbs.
4	9-4070-4	\$145.85	9-5883-4	\$157.00	IN SAE 10, OUT SAE 12, Work SAE 8	9 lbs.


Directional Control Valves

• Brand new HYDRAFORCE dual solenoid directional control valves.



SPECIFICATIONS

- Pressure 3500 PSI
- Mount 2 hole side 2" c/c
- Spools one
- In/Out ports SAE 6
- Size 2 1/2" x 1 1/4" x 7 3/4"
- Flow 5 GPM
- Work ports SAE 6
- Shpg. 5 lbs.



Voltage	ITEM	Price	Valve Type	Spool Details
12 VDC Amperage 1.67	9-7987	\$122.92	Open center	Work ports blocked in neutral
	9-7989	\$120.95	Closed center	All ports blocked in neutral
	9-7988	\$122.95	Open center	All ports open to tank in neutral
115 VAC Amperage 0.18	9-7990	\$149.95	Open center	Work ports blocked in neutral
	9-7992	\$147.95	Closed center	All ports blocked in neutral
	9-7991	\$149.95	Open center	All ports open to tank in neutral

1" NPT Hydraulic Relief Valve



ITEM 9-7901

\$82.50

• Brand new, BUYERS PRODUCTS model HRV10025 inline (3 port) relief valve. Ball and spring direct acting style. Cast iron body. Three mounting holes for 3/8" bolts.

SPECIFICATIONS

- Flow Rating 50 GPM max
- Relief Range 1501-3000 PSI
- Factory Setting 2000 PSI
- Ports 1" NPT
- Gauge Port 1/4" NPT
- Size 9 5/8" x 3 1/2" x 3 1/4"
- Shpg. 10 lbs.

12 Volt DC Double Acting Directional Control Valve



ITEM 9-8878

\$119.95

• New, ARGO HYTOS RPE3-06C11/01200E8/M dual solenoid directional control valve for operating double acting cylinders. Manual override on solenoids. Spring centering spool. Subplate mounting requires D03 subplate (sold separately) for port connections. Includes subplate valve to manifold bolts.

SPECIFICATIONS

- Open Center
- Spools One
- Flow 21 GPM
- Pressure at Ports P, A & B 5100 PSI Max.
- Pressure at Port T 3050 PSI Max.
- Voltage 12 VDC
- Amperage 2.72
- Ports D03 Subplate manifold
- Mount D03 Subplate manifold
- Size 8 1/4" x 1 1/4" x 2 1/4"
- Shpg. 6 lbs.

Electric Flow Control



• Brand new BRAND HYDRAULICS. Variable flow control valve with 12 volt DC controller for remote operation. Gives convenient hydraulic motor speed control from tractor cabs.



SPECIFICATIONS

- 12 volt DC control
- 3000 PSI max.
- Ports SAE 12
- Size 9 1/2" x 5" x 1 7/8"
- Shpg. 12 lbs.

ITEM 9-5178-15 \$619.90

- Flow range 0 - 15 GPM.

ITEM 9-5178-30 \$628.65

- Flow range 0 - 30 GPM.

12 VDC & 115 VAC Solenoid Operated Poppet Valves



• Brand new HYDRAFORCE. Solenoid operated 2 way poppet type valves. Use for starting, stopping, or dumping of hydraulic circuits to 3000 PSI (not a directional control valve). Available in N.O. or N.C. configurations with 12 volt DC or 115 volt AC coils. Continuous rated solenoids with hardened seats for long life and low leakage. Rated 12-15 GPM, ports SAE 8. Shpg. 2 lbs.

Voltage	ITEM	Valve Type	Price
12 VDC Amps 1.67	9-5112-NO	Normally Open	\$74.95
	9-5112-NC	Normally Closed	\$65.95
115 VAC Amps 0.18	9-5111-NO	Normally Open	\$84.95
	9-5111-NC	Normally Closed	\$79.95

SAE 12 30 GPM Hydraulic Motor Relief Bypass Valve



ITEM 9-8745 \$172.75

• Brand new, FLUIDTECH four port inline crossover relief and bypass check valve. Provides overload and shut off protection for motor wind down when used with hydraulic control valves that have blocked work ports in neutral. For non reversible applications only. Ideal for use with skid steer loader or tractor valve outlets for operating remote hydraulic motor for overload and shut off protection. Two mounting holes for 3/8" bolts.

SPECIFICATIONS

- Flow Rating 30 GPM max
- Pressure Rating 3000 PSI max
- Relief Range 450-3000 PSI
- Factory Setting 2500 PSI
- Ports SAE 12
- Size 2 1/2" x 3 7/8" x 8 1/8"
- Shpg. 7 lbs.