


MTE Hydraulic Pumps

- Brand new, MTE hydraulic pumps. Cast iron body. Made for direct drive, no shaft side-loading. Made in USA.



SPECIFICATIONS

- CW Rotation
- Shaft 1/2" diam. x 1 1/2" w/1/8" keyway
- 4F17 mount (1.78" dia. Pilot)
- 3600 RPM

ITEM	Displ.	GPM at		PSI		Ports		Size	Shpg.	Price
		3600 RPM		Cont.	Int.	Inlet	Outlet			
9-8401-67	0.067	1.04		3000	4000	SAE 6	SAE 6	3.82" x 2.8" x 3.66"	5 lbs.	\$107.70
9-8401-97	0.097	1.51		3000	4000	SAE 6	SAE 6	3.89" x 2.8" x 3.66"	5 lbs.	\$110.20
9-8401-129	0.129	2.00		3000	4000	SAE 8	SAE 6	3.95" x 2.8" x 3.66"	5 lbs.	\$111.85
9-8401-192	0.192	2.98		3000	4000	SAE 8	SAE 6	4.08" x 2.8" x 3.66"	5 lbs.	\$113.00
9-8401-251	0.251	3.92		2300	4000	SAE 8	SAE 8	4.2" x 2.8" x 3.66"	5 lbs.	\$114.35
9-8401-277	0.277	4.32		2100	3500	SAE 8	SAE 8	4.26" x 2.8" x 3.66"	5 lbs.	\$116.05
9-8401-323	0.323	5.04		1900	3000	SAE 10	SAE 8	4.35" x 2.8" x 3.66"	6 lbs.	\$117.70
9-8401-434	0.434	6.76		1600	2500	SAE 10	SAE 10	4.58" x 2.8" x 3.66"	6 lbs.	\$120.20
9-8401-479	0.479	7.46		1300	2250	SAE 10	SAE 10	4.68" x 2.8" x 3.66"	6 lbs.	\$121.90

1.22 cu in Hydrecu Gear Pump



ITEM 9-4849-C
\$112.99

New. Aluminum housing. Teflon lined bushings.

SPECIFICATIONS

- 1.22 cu in dia
- 2900 PSI cont
- 3625 PSI int
- 3000 RPM max
- 7.1 GPM @ 1500 RPM
- 15 GPM @ 3000 RPM
- CCW Rotation
- Mount 2 bolt SAE A
- Shaft 5/8" 9 tooth spline
- Port IN SAE 16
- Port OUT SAE 10
- Size 5 1/8" x 7 1/2" x 5 1/4"
- Shpg. 17 lbs.

28 GPM 2 Stage Hydraulic Pump



ITEM 9-250028
\$229.95

New, CONCENTRIC two stage HI/LO pressure hydraulic gear pump. Ideal for applications such as log splitters, presses and other equipment.

SPECIFICATIONS

- Displacement: 0.465/1.395 cu. in. / rev.
- Rotation CW
- Power Requirement 16HP
- Pressure: 3000 PSI max.
- Speed: 3600 RPM max.
- Flow: 7.25 GPM HI press. stage 28 GPM LO press. stage
- Unloading Pressure 650 PSI
- Mount 2 bolt SAE A
- Shaft 5/8" dia. x 1 1/2", 3/16" keyway
- Inlet Port 1" NPT
- Outlet Port 3/4" NPT
- Size 6 1/4" x 6 1/4" x 4 5/8"
- Shpg. 21 lbs.

1.86/1.24 cu in Commercial Hydraulic Double Gear Pump



ITEM 9-12234


\$369.95

• New, PARKER/COMMERCIAL model# 329-9120-138 gear pump with independent inlet and outlet ports for each section. Cast iron construction. 3 extended studs out rear of pump. Original application Thomas Bus power steering pump part TBB159878.

SPECIFICATIONS

- Product Code PG-P315L*293**AB15**OK*AB10-1
- Disp. Front 1.86 cu. in. / rev. Rear 1.254cu. in. / rev.
- Pump Type Gear
- Rotation CCW
- Pressure 2500 PSI max.
- Speed 2400 RPM max.
- Flow at 2000 RPM Front 16.1GPM
- Rear 10.7 GPM
- Mount SAE A 2 Bolt
- Shaft 3/4" 11 tooth splined shaft.
- Front Section Ports
- Inlet SAE 20 side
- Outlet SAE 16 side
- Rear Section Ports
- Inlet SAE 16 side
- Outlet SAE 12 rear
- Size 9 7/8" x 5" x 5"
- Shpg. 45 lbs.

1.526 cu in Hydraulic Pump



ITEM 9-8981
\$79.95

• New, CONCENTRIC hydraulic pump. Rear plate has one HYDRAFORCE CV10-23-05 check valve and one HYDRAFORCE TS10-27A proportional pressure relief valve with 12 VDC coil.

SPECIFICATIONS

- Model WPO9A1B250
- Disp. 1.526 cu. in. / rev.
- Pump Type Gear
- Rotation Clockwise
- Pressure: 3000 PSI Cont.
- Speed: 3000 RPM max.
- Flow: Unknown
- Mount Two-bolt SAE A
- Shaft 3/4" dia. x 1 1/4" tapered shaft w/ threaded end and castle nut
- Inlet Port SAE 16
- Outlet Port SAE 12
- Size 6 3/4" x 5 1/16" x 5"
- Shpg. 15 lbs.

0.89 CU in. Gear Pump




ITEM 9-8302
\$79.95

New, CASAPPA model# KP20.14D5-N9R2-LMB-GC/GD/B-N-R gear pump with installed priority valve. Removeable, 39T helical gear attached to pump shaft.

SPECIFICATIONS

- Disp. 0.89 cu. in. / rev.
- Pump Type Gear
- Rotation CW
- Pressure 3850 PSI cont.
- Speed 3500 RPM max.
- Mount Four M8 x 1.25 tapped holes on 90mm B.C.
- Shaft 5/8" dia. x 1 3/8" long 9T spline, tapped M12
- x 1.25
- Inlet Port 19mm I.D. manifold w/ four M10 x 1.5 tapped holes on 48mm x 22.5mm centers
- Work Port 1/2" BSPP
- Drain Port 3/8" BSPP
- Size 6 7/8" x 5 1/2" x 4 3/4"
- Shpg. 21 lbs.

7.1 cu in Dowty Gear Pump



New, DOWTY P4000 series gear pump. Aluminum housing. Pressure balanced bushings.

SPECIFICATIONS

- Model 3P4380-ASCSB
- Disp. 7.1 Cu. In.
- Speed 2,000 RPM Max
- Pressure 2,500 PSI Max
- 55 GPM @ 1,800 RPM
- 61 GPM @ 2,000 RPM Max
- Rotation CCW
- Mount SAE C 4 bolt
- Shaft 1 1/4" x 14 tooth
- IN Port 1 1/2" flange
- OUT Port 1 1/4" flange
- Shpg. 34 lbs.

ITEM 9-2069-R Rotation CW **\$329.00**

ITEM 9-2070-R Rotation CCW **\$329.00**

1.61/0.4 Cu.In. Double Gear Pump



ITEM 9-12165
\$199.95

New, CASAPPA double gear pump. Common inlet port. Aluminum body.

SPECIFICATIONS

- Disp. Front 1.46 cu.in. Rear 0.4 cu. in.
- Pump Type Gear
- Rotation CW
- Pressure Front 2465 PSI, Rear 3600 PSI cont.
- Speed 2500 RPM max.
- Flow Front 17.4 GPM cont., Rear 4.6 GPM cont.
- Mount SAE A 2 bolt
- Shaft 3/4-11 Spline
- Inlet Port SAE 16
- Outlet Ports SAE 10
- Size 7 1/2" x 5" x 4 1/2"
- Shpg. 12 lbs.

0.66 cu. in. Gear Pump



ITEM 9-4886
\$79.95

• New CESSNA 25301 LAG.

SPECIFICATIONS

- Disp. 0.66 cu. in.
- 3600 RPM max.
- 3000 PSI max.
- 5.5 GPM at 2000 RPM
- 2 bolt SAE A mount
- Rotation CCW
- IN SAE 16, OUT SAE 10
- Shaft 5/8" x 1 1/2" tapered w/keyway & threaded end
- Size 4" x 5" x 5"
- Shpg. 6 lbs.

0.48 cu. in. Casappa Hydraulic Pump



ITEM 9-8724
\$89.95

• New, CASAPPA Model PLP10-8 D0-02S0-L-OC/OB-N-EL hydraulic gear pump.

SPECIFICATIONS

- Disp. 0.48 cu. in. / rev.
- Pump Type Gear
- Rotation CW
- PSI 2610 max. cont.
- RPM 1800 rated, 3500 max.
- GPM 3.69 rated, 7.3 max.
- Mount 2 bolt SAE AA
- Shaft 1/2" dia. x 3/4" long 9T splined
- Inlet port SAE 10
- Outlet port SAE 8
- Size 3 5/8" x 4" x 3 1/8"
- Shpg. 5 lbs.