

5" x 23" x 2 1/2"



ITEM 9-9080
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 5" x 23"
- Rod End Tang
- Max Thickness 1 1/16"
- Pin Hole 3 3/16" (81mm)
- Base End Solid No Pin
- Base End Diameter 3 7/16"
- Base End Length 6"
- Pressure 3000 PSI max.
- Rod Dia. 2 1/2"
- Ports 1/4" NPT
- Retracted Length 45"
- Shpg. 220 lbs.

Truck freight only.

\$329.95

5" x 24" x 2"



ITEM 9-8996
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 5" x 24"
- Pressure 2500 PSI max.
- Rod Dia. 2"
- Extend Port ORFS 10
- Retract Port SAE 8
- Retracted Length 32"
- Rod End Thru-Hole
- Rod End Width 1.5"
- Rod End Pin Hole 9/16"
- Base End Clevis
- Base End Inside Width 1.15"
- Base End Outside Width 1.90"
- Base End Pin Hole 1.25"
- Shpg. 80 lbs.

\$199.95

5" x 24" x 2"



ITEM 9-12217
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 5" x 24"
- Rod Dia. 2"
- Ports SAE 8
- Pressure 3000 PSI max.
- Rod End Thru-Hole
- Rod End Width 1.75"
- Rod End Pin Hole 1 1/2"
- Retracted Length 33.25"
- Base Clevis
- Base End Outside Width 2.61"
- Base End Inside Width 1.12"
- Base End Pin Hole 1 1/4"
- Shpg. 87 lbs.

\$299.95

5" x 24" x 2"
Log Splitter Cylinder



ITEM 9-7850


- Brand new, FISHER HYDRAULICS hydraulic cylinder used on many popular brands of log splitters. Rated 3500 PSI to provide up to 34 tons of force. Ideal cylinder for replacement use or for building heavy duty log splitters.

SPECIFICATIONS

- Double acting
- Bore x Stroke 5" x 24"
- Pressure 3500 PSI max.
- Rod dia. 2"
- Push port JIC 8 M
- Retract port 1/2" NPTM
- Retracted lgth. 31 7/8"
- Rod thru-hole 1 1/2" w.
- Pin hole 9/16"
- Base clevis 1 7/8" wide
- Pin hole 1 1/4"
- Shpg. 74 lbs.

\$345.10

Retracted Length



Is Measured Pin Center to Pin Center

5" x 24" x 2"



ITEM 9-8996
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 5" x 24"
- Pressure 2500 PSI max.
- Rod Dia. 2"
- Extend Port ORFS 10
- Retract Port SAE 8
- Retracted Length 32"
- Rod End Thru-Hole
- Rod End Width 1.5"
- Rod End Pin Hole 9/16"
- Base End Clevis
- Base End Inside Width 1.15"
- Base End Outside Width 1.90"
- Base End Pin Hole 1.25"
- Shpg. 80 lbs.

\$199.95

5" x 51.75" x 2.5"



ITEM 9-9082
SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 5" x 51 3/4"
- Tang Ends
- Max Thickness 1 3/8"
- Pin Hole 2 3/4"
- Pressure 3000 PSI max.
- Rod Dia. 2 1/2"
- Ports SAE 8
- Retracted Length 67 1/2"
- Shpg. 270 lbs.

\$594.95

Truck freight only.

5" x 54" x 2 3/4"



ITEM 9-8755
SPECIFICATIONS

- New, Double acting
- Bore x Stroke 5" x 54"
- PSI max.
- 2342 push, 4000 pull
- Rod dia. 2 3/4"
- Ports SAE 12
- Retracted lgth. 73"
- Rod tang with swivel eye 3" thick
- Base tang 2" thick
- Pin holes 2 1/4"
- Shpg. 360 lbs.

\$899.99

Truck freight only.

5 1/2" x 37 1/8" x 2 1/2"



ITEM 9-9689
SPECIFICATIONS

- New, Double acting
- Bore x Stroke 5 1/2" x 37 1/8"
- Pressure 3000 PSI max
- Rod dia. 2 1/2"
- Retracted lgth. 51 3/8"
- Extend port
- 1" four bolt flange, code 61
- Retract port JIC 16M
- Crosstube ends rod 3 1/4" w., base 6 3/4" w.
- Pin holes 2"
- Shpg. 290 lbs.

\$569.95

Truck freight only.

5 1/2" x 37 1/8" x 2 1/2"



ITEM 9-9690
SPECIFICATIONS

- New, Double acting
- Bore x Stroke 5 1/2" x 37 1/8"
- Pressure 3000 PSI max.
- Rod dia. 2 1/2"
- Retracted lgth. 51 3/8"
- Extend port
- 1" four bolt flange, code 61
- Retract port JIC 16M
- Crosstube ends rod 3 1/4" w., base 6 3/4" w.
- Pin holes 2"
- Shpg. 290 lbs.

\$569.95

Truck freight only.

5 1/2" x 37 1/4" x 3.177"



ITEM 9-9113
SPECIFICATIONS

- New, Double acting
- Bore x Stroke 5 1/2" x 37 1/4"
- Pressure 3000 PSI max.
- Rod dia. 80mm (3.177")
- Retracted lgth. 51 3/8"
- Ports 1" four bolt flange, code 61
- Rod tang 3 1/4" thick
- Base crosstube 6 3/4" w.
- Pin holes 2"
- Shpg. 350 lbs.

\$579.95

Truck freight only.

5 1/2" x 46 1/2" x 2 1/2"



ITEM 9-10171

Cushion valves at end of extend and retract strokes.

SPECIFICATIONS

- New, Double Acting
- Rod End Clevis
- Outside Width 5 1/4"
- Inside Width 3 1/16"
- Pin Hole 1 1/2"
- Rod End Crosstube Assembly Width 4"
- Double Acting
- Bore x Stroke 5 1/2" x 46 1/2"
- Pressure 3000 PSI max
- Rod Dia. 2 1/2"
- Ports 1" Four Bolt Flange, Code 61
- Retracted Length 34 1/4"
- O.D. 2 5/16"
- Trunnion Female
- Pin Outside Width 10 1/4"
- Pin Inside Width 6"
- Pin Center to Rod Pin Center 3 1/4"
- Pin Center to Base End 38"
- Pin Diameter 2 1/2"
- Shpg. 375 lbs.

\$569.95

Truck freight only.

5 1/2" x 58" x 3 1/2"



ITEM 9-9062

Counter-balance valve with 3:1 pilot ratio.

SPECIFICATIONS

- New double acting
- Bore x Stroke 5 1/2" x 58"
- Pressure 3000 PSI max.
- Rod dia. 3 1/2"
- Ports SAE 12
- Retracted lgth. 767/8"
- Rod tang 5 1/2" wide
- Pin hole 3 3/16"
- Base clevis 4" wide
- Pin hole 2"
- Shpg. 445 lbs.

\$799.95

Truck freight only.

5 1/2" x 63" x 4"



ITEM 9-8169

Cap, rod wiper seals are cracked.

SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore x Stroke 5 1/2" x 63"
- Pressure 3000 PSI max.
- Rod dia. 4", hollow
- Ports SAE 16
- Rod thru-hole 3 15/16" wide
- Base crosstube 6 1/2" w.
- Pin holes 2" v
- Shpg. 340 lbs.

\$749.99

Truck freight only.

6" x 22.25" x 3"



ITEM 9-9054
SPECIFICATIONS

- Double Acting
- Bore x Stroke 6" x 22 1/4"
- Tang Ends
- Max Thickness 2"
- Pin Hole 1 7/8"
- Pressure 3000 PSI max.
- Rod Dia. 3"
- Ports 3/8" NPT
- Retracted Length 64"
- Shpg. 350 lbs.

\$449.95

Truck freight only.