

BAR Dry Gauges

1/4" NPT Back Connection



ITEM	BAR	Dia.	Case	Shpg.	Price
21-1582-BB	2.5	2"	Plastic	1/2 lb.	\$4.95
21-1653-R	6	2"	Plastic	1/2 lb.	\$3.95
21-1653-S	10	2"	Plastic	1/2 lb.	\$3.95
21-1582-BG	10	2"	Plastic	1/2 lb.	\$4.95

1/4" NPT Lower Connection



ITEM	BAR	Dia.	Case	Shpg.	Price
21-1657-N	6	2 1/2"	Plastic	1 lb.	\$5.95
21-1657-O	10	2 1/2"	Plastic	1 lb.	\$5.95
21-1583-AW	22	2 1/2"	Steel	1 lb.	\$5.95

1/2" NPT Lower Connection



ITEM	BAR	Dia.	Case	Shpg.	Price
21-1608-BI	0-10	4"	Plastic	2 lbs.	\$15.95
21-1634-AM	25	6"	Stainless	3 lbs.	\$19.95
21-1634-AL	40	4"	Stainless	3 lbs.	\$12.95
21-1634-AO	100	6"	Stainless	3 lbs.	\$19.95

60 PSI Gauge



ITEM 21-1716 \$1.99

• New, SUPER PRO pressure gauge. White face with black numbers.

SPECIFICATIONS

- Range 0-60
- Graduations 1 PSI
- Face dia. 2"
- Bezel dia. 2"
- Dry
- Connection 1/4" NPT back
- Plastic case
- Shpg. 1/2 lb.

30 PSI PM Gauge



ITEM 21-1634-BA \$3.99

• New top quality TEL-TRU 2050BC4B1-C6FV dry pressure gauge. "U" shaped bracket, 2 studs 1 3/8" C-C.

SPECIFICATIONS

- Measures 0-30 PSI / 0-2 Bar
- Graduated 0.5 PSI / 0.05 Bar
- Face diam. 2"
- Bezel diam. 2 1/4"
- Stainless steel bezel
- Dry
- Panel mount
- 1/4" NPT connection
- Steel housing
- Shpg. 1/2 lb.

200 PSI Gauge



ITEM 21-1565-H \$5.95

• New Dynamic Fluid Components CDS-1P-015E. 200 PSI gauge, 3 bolts on 3" dia. B.C.

SPECIFICATIONS

- Measures 0-200 PSI / 0-14 Bar
- Graduated 5 PSI / 0.5 Bar
- Face diam. 2 1/2"
- White face
- Chrome bezel
- Dry gauge
- Mounting: Panel Mount
- Mounting Depth: 1 1/8"
- Fitting: 1/4" NPT
- Housing Material: Metal
- Shpg. 1/2 lbs.

Special Inventory Reduction Sale

\$2.99 each!!!

30 PSI 1 1/2" Gauge



ITEM 21-1635-G \$2.99

• New top quality Winters 415230 Pressure gauge.

SPECIFICATIONS

- Range 0 to 30 PSI / 0 to 210 KPA
- Graduations: 1 PSI / 6 KPA
- 1 1/2" face diam.
- 1 5/8" bezel diam.
- Clear bezel
- Dry gauge
- Fitting 1/8" NPT
- Back mount
- Plastic housing
- Shpg. 1/4 lb.

100 PSI Panel Mount 2" Gauge



ITEM 21-1634-BB \$2.99

• New top quality TEL-TRU 2050BC4B-1D9FV dry pressure gauge. "U" shaped bracket, 2 studs 1 3/8" C-C.

SPECIFICATIONS

- Measures 0-100 PSI / 0-7 Bar
- Graduated 2 PSI / 0.1 Bar
- Face diam. 2"
- Bezel diam. 2 1/4"
- Stainless steel bezel
- Dry
- Panel mount
- 1/4" NPT connection
- Steel housing
- Shpg. 1/2 lb.

400 PSI 2" Gauge



ITEM 21-1560 \$2.99

• New Marsh Instruments part number J1460M pressure gauge. Black painted steel housing.

SPECIFICATIONS

- Measures 0-400 PSI in 10 PSI increments
- White face/black markings
- 1/4" NPT lower connection
- 2" dia. face
- Shpg. 1/4 lb.

0 to 600 PSI, 2 1/2" Gauge



ITEM 21-1637-I \$2.99

• New top quality Winters 600425 Pressure gauge. 2 Mounting studs 1 15/16" C-C with "U" shaped bracket

SPECIFICATIONS

- Range: 0 to 600 PSI
- Graduations: 20 PSI
- Gauge Type: Pressure
- Face Diameter: 2 1/2"
- Bezel Diameter: 2 7/8"
- Bezel Color: Clear
- Dry gauge
- Mounting: Panel Mount
- Mounting Depth: 1 1/8"
- Fitting: 1/4" NPT
- Housing Material: Metal
- Shpg. 1/2 lbs.

Refrigerant Gauges

• New pressure gauges calibrated to display the temperature and corresponding pressure of compressed refrigerants. All have white faces. Panel mount gauges include a mounting bracket. All are dry gauges. Shpg. 1/2 lb.

Case: M = Metal P = Plastic B = Brass S = Steel SS = Stainless Steel
Connection indicated L = Lower P = Panel



ITEM	Diam.	PSI	Vac.	Compatible Refrigerants & Their Ranges	Connect	Case	Price
21-1583-AH	2 1/2"	500		R502: -40 to 167 F, R22: -40 to 173 F, R12: -20 to 218 F	1/8" L	P	\$5.95
21-1583-AP	2 1/2"	500		R502: -40 to 167 F, R22: -40 to 173 F, R12: -20 to 218 F	1/8" L	S	\$5.95
21-1637-CF	2 1/2"	500	30"	R410A: -40 to 90 F, R12: 0 to 160 F, R134a: 0 to 150 F, R22: -30 to 120 F	1/8" P	M	\$5.95
21-1637-CG	2 1/2"	500	30"	R410A: -40 to 90 F, R12: 0 to 160 F, R134a: 0 to 150 F, R22: -30 to 120 F	1/8" L	P	\$5.95
21-1637-CH	2 1/2"	800		R410A: 20 to 150 F, R12: 70 to 200 F, R134a: 60 to 190 F, R22: 30 to 160 F	1/8" L	P	\$5.95
21-1637-CK	2 1/2"	3.4 MPa	-0.1 MPa	R410A: -40 to 30 C, R12: -5 to 70 C, R134a: 0 to 65 C, R22: -20 to 45 C	1/8" P	M	\$5.95
21-1637-CL	2 1/2"	3.4 MPa	-0.1 MPa	R410A: -40 to 30 C, R12: -5 to 70 C, R134a: 0 to 65 C, R22: -20 to 45 C	1/8" L	P	\$5.95