

### 1 HP Stainless Steel Vertical Pump



ITEM 2-1430  
**\$269.99**

• New, GOULDS vertically immersed stainless steel end suction pump. Enclosed impellor for maximum efficiency. TEFC motor.

**SPECIFICATIONS**

- Voltage 115/230 VAC
- Amperage 11.4/5.7 Amps
- Power 1 HP
- Speed 3450 RPM
- Max Head 88 ft (38 PSI)
- Flow Rates 20 GPM @ 72 ft. head
- 40 GPM @ 40 ft. head
- Impellor dia. 4 3/4"
- Inlet 1 1/4" NPT
- Discharge 1" NPT
- Max fluid temp 250F
- Size 10" x 10 1/2" x 26"
- Shpg. 77 lbs.

### 12 VDC Marine Camper Pump




ITEM 2-924  
**\$31.70**

• Brand new. For boats, camper-trailers, etc. as bilge or water system pump. Non-corrosive. Use in any position provided intake is submerged. Fits into tight, out-of-way places.

**SPECIFICATIONS**

- 12 VDC at 1.8 full load amp
- 339 GPH at 1 ft.
- 95 GPH at 10 ft.
- IN 1/2" NPT
- OUT 3/8" NPT
- Size 5 1/2" x 2" x 2"
- Shpg. 2 lbs.

### Flexible Impeller Pumps



• Brand new SCC. Flexible impeller type pumps. Bronze head. Self-priming. Not for pumping flammable fuels.

**SPECIFICATIONS**

- 6 GPM open flow
- 4 GPM at 10 PSI
- 18 PSI max.
- Ports 3/8" NPT Dual Threaded Female
- 3/4" garden hose thread male
- Size 6" x 4" x 3 1/4"
- Shpg. 8 lbs.

**Nitrile Impeller Models**

• Use for waste oil or water.

ITEM 2-1185 **\$96.85**

• 115 VAC, 2 amps.

Flow (GPH) vs. Pressure (Feet of head)

|          |     |     |     |     |     |     |          |
|----------|-----|-----|-----|-----|-----|-----|----------|
| Pressure | 1'  | 5'  | 10' | 20' | 30' | 40' | Shut-Off |
| Water    | 400 | 390 | 358 | 295 | 225 | 120 | 48 Ft.   |

ITEM 2-1186 **\$96.95**

• 12 VDC, 10 amps.

Flow (GPH) vs. Pressure (Feet of head)

|          |     |     |     |     |     |     |          |
|----------|-----|-----|-----|-----|-----|-----|----------|
| Pressure | 1'  | 5'  | 10' | 20' | 30' | 40' | Shut-Off |
| Water    | 375 | 375 | 342 | 273 | 192 | 85  | 42 Ft.   |

ITEM 2-1185-Kit **\$11.45**

• Repair kit includes impeller, seals, retainer and cover gasket. Shpg. 1/2 lb.

ITEM 2-1185-I **\$7.10**

• Impeller only. Shpg. 2 oz.

**High Strength Polyurethane Impeller**

• Use for water only.

ITEM 2-1379 **\$102.85**

• 12 VDC, 10 amps. See performance chart for ITEM 2-1186 above.

### Rotary Chemical Pump

ITEM 2-1453  
**\$49.95**

• New, Funnel King Fluid Control Products by WirthCo model 32446 rotary hand pump. Use to transfer DEF, diesel fuel, antifreeze, kerosene, ammonium chloride. Glass filled polypropylene with Ryton vanes. Stainless steel hardware. Includes 2" bung adapters in coarse and fine thread. 3 piece suction tube with strainer and check valve at bottom.

**SPECIFICATIONS**

- Flow Rate 6.5 gal. @ 100 revolutions max.
- Rotation CW
- Mount 2" Tank Bung
- Suction Pipe Length Adjustable up to 40" long
- Shpg. 6 lbs.

### Polypropylene Chemical Pump

ITEM 2-1451  
**\$36.95**

• New, Funnel King Fluid Control Products by WirthCo plunger style hand pump. Use to transfer antifreeze, detergent, windshield fluid. Polypropylene with steel rod and Viton seals. Includes 2" bung adapter and angled discharge spout.

**SPECIFICATIONS**

- Flow Rate 1 gal. @ 10 full strokes
- Rotation CW
- Mount 2" Tank Bung
- Suction Pipe Length 38"
- Shpg. 3 lbs.

### Nylon Chemical Pump

ITEM 2-1452  
**\$36.95**

• New, Funnel King Fluid Control Products by WirthCo plunger style hand pump. Use to transfer DEF, acetone, antifreeze, detergent mild acid. Nylon with stainless steel rod and PTFE seals. Includes 2" bung adapter and angled discharge spout.

**SPECIFICATIONS**

- Flow Rate 1 gal. @ 10 full strokes
- Rotation CW
- Mount 2" Tank Bung
- Suction Pipe Length 38"
- Shpg. 4 lbs.

### Windshield Washer Pump

ITEM 2-1442  
**\$8.99**

• New, windshield washer pump. Mounts thru grommet on side of reservoir (not included). Recessed two prong electrical connection.

**SPECIFICATIONS**

- Pump Voltage 12 VDC
- Mount 0.65 OD barb for grommet
- Outlet 3/16" hose barb
- Size 1 3/8" dia. x 3 3/4"
- Shpg. 1 lb.

### Barrel Drain Petcock

ITEM 20-973  
**\$1.99**

• 1" NPT male. Size 2 3/4" x 2 1/2" x 1 1/2". Shpg. 1 lb.

### Water System Automatic Pressure Switches



Brand new, LEFOO automatic pressure switch for automatic water systems. Automatically turns pump ON or OFF at set values. Adjustable differential. Sturdy plastic housing. Single port.

ITEM 4-1822  
**\$13.95**

**SPECIFICATIONS**

- Contact ratings 1 1/2 HP at 120 VAC, 2 HP at 230 VAC, 3 HP at 240 VAC 3PH
- Factory setting ON (cut-in) 40 PSI, OFF (cut-out) 60 PSI
- Min. ON (cut-in) 20 PSI
- Max. OFF (cut-out) 80 PSI
- Differential 15-35 PSI
- Port 1/4" NPT
- Size 3 3/4" x 2 5/8" x 3 3/4"
- Shpg. 1 1/2 lbs.



ITEM 4-1821  
**\$13.95**

**SPECIFICATIONS**

- Contact ratings 1 1/2 HP, 20 amps at 120 VAC, 2 HP, 12 amps at 240 VAC, 3 HP, 9.6 amps at 240 VAC 3PH
- Factory setting ON (cut-in) 30 PSI, OFF (cut-out) 50 PSI
- Min. ON (cut-in) 30 PSI
- Max. OFF (cut-out) 100 PSI
- Differential 20-35 PSI
- Port 1/4" NPT
- Size 3 1/2" x 2 1/4" x 3 1/4"
- Shpg. 1 1/2 lbs.



### Bilge or Drum Pump

ITEM 2-1454  
**\$39.95**

• New, Funnel King Fluid Control Products by WirthCo diaphragm hand pump. Use as a bilge pump or convert to drum pump. Will handle water, saltwater, diesel, kerosene, gasoline, antifreeze, light oils. Can be mounted and operated in any position. Swap hoses to reverse fluid flow. Polyacetal body, polyurethane diaphragm with stainless steel hardware. Includes suction strainer and discharge nozzle.

**SPECIFICATIONS**

- Flow Rate 4.4 gal. per minute
- Drum Adapter 2" Tank
- Bung
- Hose size 1" ID
- Shpg. 8 lbs.



### 115 VAC Coolant Recirculating Pump

ITEM 2-1436  
**\$27.95**

• New, BECKETT Model BJ5A coolant recirculating pedestal pump. Ideal replacement or use with evaporative coolers, displays, laboratories and other water transfer applications. Features include polystyrene column and cap, ABS base plate and a 1/2" OD PVC adapter. ODP motor with fan and cover.

**SPECIFICATIONS**

- Voltage 115 VAC
- Amperage 0.9 Amps
- Power 1770 HP
- Flow Rates 340 GPH at 1 ft. head, 255 GPH at 4 ft. head, 200 GPH at 6 ft. head, 130 GPH at 8 ft. head, 40 GPH at 10 ft. head
- Max. head 88 ft. (38 PSI)
- Shut-off at 10.1 ft. head
- Duty continuous
- Power cord 3 foot 18/3
- Inlet base
- Discharge 1/2" hose barb w/adaptor
- Size 4 1/2" dia. x 9" high
- Shpg. 5 lbs.

