


Double Roller Chain Couplers

• Brand new. Three piece chain coupler consist of two sprockets connected together with double roller chain. Sold as individual halves and chain. Purchase two halves and one coupler chain to make a complete coupling.



Pitch & Tooth Count	Max. RPM	Max. Torque Ft.-Lbs.	Max HP at RPM	Coupling O.D.	Coupled Length
	40 Pitch 16 Tooth	5000	80.5	73.6 at 4800 RPM	3.03"
50 Pitch 16 Tooth	4000	159.6	109.4 at 3600 RPM	3.78"	3.92"
60 Pitch 18 Tooth	3000	407.5	194.5 at 2500 RPM	5"	4.86"

Keyed Half

• Furnished with standard keyway and setscrews.

Bore Size	40 Pitch 16 Tooth ITEM	50 Pitch 16 Tooth ITEM	60 Pitch 18 Tooth ITEM
5/8"	1-4050-B	1-4051-B	—
3/4"	1-4050-C	1-4051-C	—
7/8"	1-4050-D	1-4051-D	—
1"	1-4050-E	1-4051-E	1-4053-E
1 1/8"	1-4050-F	1-4051-F	1-4053-F
1 3/16"	—	1-4051-G	1-4053-G
1 1/4"	—	1-4051-H	1-4053-H
1 3/8"	—	1-4051-I	1-4053-I
1 7/16"	—	1-4051-J	1-4053-J
1 1/2"	—	1-4051-K	1-4053-K
1 5/8"	—	1-4051-L	1-4053-L
1 3/4"	—	—	1-4053-M
1 7/8"	—	—	1-4053-N
1 15/16"	—	—	1-4053-O
2"	—	—	1-4053-P
2 1/8"	—	—	1-4053-Q
2 1/4"	—	—	1-4053-R
2 3/8"	—	—	1-4053-S
2 7/16"	—	—	1-4053-T
Shpg. Price	2 lbs. \$12.70	3 lbs. \$15.80	7 lbs. \$27.40



Smooth Bore Half

• Plain bore, no keyway or setscrews.

Machinable Bore Range	40 Pitch 16 Tooth ITEM	50 Pitch 16 Tooth ITEM	60 Pitch 18 Tooth ITEM
5/8" - 1 1/8"	1-4050-SB	—	—
5/8" - 1 5/8"	—	1-4051-SB	—
1" - 2 7/16"	—	—	1-4053-SB
Shpg. Price	2 lbs. \$11.05	3 lbs. \$13.70	7 lbs. \$27.40



Double Roller Chain with Connecting Link

	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
ITEM	1-4050-X	1-4051-X	1-4053-X
Shpg. Price	1/2 lb. \$4.80	1 1/2 lbs. \$7.15	3 lbs. \$12.70




Coupling Covers

• Brand new. Shock coupling covers recommended to obtain maximum coupling life. Aluminum covers are made as halves for easy installation.

	40 Pitch 16 Tooth	50 Pitch 16 Tooth	60 Pitch 18 Tooth
ITEM	1-4050-CC	1-4051-CC	1-4053-CC
Shpg. Price	1 lb. \$20.85	1 1/2 lbs. \$28.30	3 lbs. \$37.45



Splined PTO Adapters



• Brand new, G & G Mfg. Co. Adapts keyed shaft to 1 3/8" 6 tooth spline. **Shpg 4 lbs.**

ITEM	Female Bore	Size	Price
1-2241	1"	2" diam. x 5 3/4"	\$28.95
1-2242	1 1/4"	2" diam. x 5 7/8"	\$27.90
1-2970	1 1/2"	2 1/4" diam. 5 7/8"	\$32.95

3/4-16 Swivel Eye Rod End ITEM 1-3778 \$10.95



• New, Radial Bearing Corporation Model RF-12TH high strength precision swivel eye rod end. Chrome moly ball with Teflon fabric liner, steel housing.

- SPECIFICATIONS**
- Misalignment angle 14° max.
 - Body female right hand thread
 - Thread size 3/4-16
 - Swivel eye bore 3/4" diam.
 - End to center 2.875"
 - Length thru bore 7/8"
 - Wrench flat 1"
 - Max. statis load 28,081 lbs.
 - **Shpg. 1 lb.**

Tractor PTO Adapter ITEM 1-1655 \$46.80



• New. Use to connect hydraulic or water pumps direct to tractor PTO.

- SPECIFICATIONS**
- Splined end 1 3/8" 6 tooth spline, 2 1/2" deep
 - Keyed end 7/8" dia. x 2 1/2" deep, 3/16" keyway
 - Overall size 1 3/4" dia. x 5"
 - **Shpg. 3 lbs.**

Snap Hitch Pump Adapters



• Brand new G & G. Snap hitch adapters. Slides onto standard 1 3/8" splined PTO shaft and spring-loaded retention pin holds adapter onto PTO shaft retention groove. Painted steel construction. Size 4 1/8" x 2 1/2" x 2 1/8". **Shpg. 4 lbs.**

ITEM # 6T	ITEM # 21T	Round Bore	Keyway	Price
1-2455	1-2462	5/8"	3/16"	\$49.75
1-2456	1-2465	3/4"	3/16"	\$49.75
1-2457	1-2466	7/8"	3/16" & 1/4"	\$53.55
1-2458	1-2467	15/16"	1/4"	\$49.75
1-2459	1-2468	1"	1/4"	\$49.75