

5200 RPM, DC Voltage Motors

\$3.99 each

• New, GLOBE MOTORS. Permanent magnet design.

SPECIFICATIONS FOR ALL

- Power 0.005 HP
- Speed 5200 RPM
- Rotation reversible
- Mnt. two 6-32 holes 1" c/c
- Bronze sleeve bearings
- Duty continuous
- Enclosure closed
- Shpg. 1/2 lb.

ITEM	Model	Voltage	Amps	Shaft	Size
10-2482	405A100	6 DC	0.2	1/8" dia. x 3/8"	1.27" dia. x 1.85"
10-2490	405A6001	28 DC	0.125	1/8" dia. x 1/2"	1.25" dia. x 1.8"
10-2492	397A1073	24 DC	0.125	1/8" dia. x 1/4"	1.25" dia. x 2.25"
10-2493	405A1192	24 DC	0.125	1/8" dia. x 1/2"	1.25" dia. x 1.85"



3600 RPM Fan Motor

ITEM 10-1726
\$12.99

• New FLEETRITE Model PM259. Permanent magnet.

SPECIFICATIONS

- Voltage 12 DC
- Amps 1.6 no load
- 180 ohms resistance
- RPM 3600
- Rotation reversible
- Mount 67/8" B.C.
- Shaft 5/16" x 1 1/8" w/flat
- Motor size 3" diam. x 5"
- Size w/mnt. 7 3/4" dia. x 5"
- Shpg. 6 lbs.



450 RPM, 12 VDC Motor



ITEM 10-2680

\$39.95

• New, TRUE-TORQUE by LEESON permanent magnet motor. Built to drive ATV mounted salt spreader. Could also be used as small DC generator.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 0.2 Amps (no load)
- 1.5 Amps (full load)
- Speed 450 RPM
- Rotation reversible
- Bearings bronze bushings
- Enclosure TENV
- Duty intermittent
- Mount 2 studs at front, 2 1/2" c/c
- Shaft 5/16" dia. x 2" w/crosshole near motor end
- Size 3" dia. x 4 1/8"
- Shpg. 5 lbs.

12 VDC, 5200 RPM Replacement Tilt/Trim Pump Motor



ITEM 10-2618

\$18.95

• New, permanent magnet 12 VDC replacement tilt/trim pump motor. Constructed for marine environments SAE J1171. Gaskets at end caps. Weather pack connectors.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 5.3 amps (no load)
- Speed 5200 RPM
- Rotation reversible
- Bearings ball
- Enclosure TENV
- Duty intermittent
- Mount 2 bolt on 3 3/16" diam. B.C
- Shaft 5/16" diam. x 0.73" ending in 4mm thick tang
- Size 5 1/2" x 3 1/4" x 3 1/4"
- Shpg. 5 lbs.

12 VDC Motor



ITEM 10-2548

\$14.99

• New, MAMCO Model CP-12-132 permanent magnet motor. Designed to fit into a 4.3" dia. opening with O-ring groove in edge of front mounting flange. Shaft is partially recessed in flange, extends 5/8" from face.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 2.5 (no load)
- Speed 4400 RPM (no load)
- Torque 45 in.oz. at 3600 RPM 15 amps
- Rotation reversible
- Bearings bronze sleeve
- Enclosure TENV
- Duty continuous
- Shaft 5/16" dia. x 1" w/threaded end
- Size 4.33" dia. x 4 9/16"
- Shpg. 5 lbs.

14000 RPM 6 Volt DC PM Motor

ITEM 10-3102

\$3.99

• New, permanent magnet motor. Shaft has 0.38" dia. 12 tooth gear on it.

SPECIFICATIONS

- Voltage 6 DC
- Amperage 0.3 amps (no load)
- Speed 14000 RPM
- Rotation Reversible
- Enclosure Open
- Duty Intermittant
- Mount Two tapped holes on face
- Shaft 0.09 dia. x 0.425
- Size 1 1/8" dia. x 2"
- Shpg. 1/2 lb.



6000 RPM, 12 VDC

ITEM 10-2631

\$7.99

• New, permanent magnet motor. Built for use in battery powered weed trimmers. Could also be used as small DC generator.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 1 Amps (no load)
- Speed 6000 RPM
- Rotation reversible
- Bearings bronze bushings
- Enclosure TENV
- Duty intermittent
- Mnt. 2 studs rear 2 1/4" c/c
- Shaft 1/4" dia. x 1" w/flat
- Size 3.15" dia. x 1 3/4"
- Shpg. 3 lbs.



3200 RPM, 12 VDC Motor

ITEM 10-2606

\$2.99

• New, DAEWOO permanent magnet motor. Originally for automotive power seat drive. Accepts 3mm square flex drive cable into each end. Packard 12064750 terminal (3/16" push-on spades).

SPECIFICATIONS

- Voltage 12 DC
- Amperage 1.1 Amps
- Speed 3200
- Rotation reversible
- Enclosure TENV
- Duty intermittent
- Mount 2 screws each end
- Shaft female 3mm socket at each end
- Size 2" dia. x 4 5/8"
- Shpg. 2 lbs.



4850 RPM 12 VDC Fan Motor

ITEM 10-2033

\$8.95

• Unused, old inventory. Permanent magnet motor. Automotive fan motor.

SPECIFICATIONS

- Voltage 12 VDC
- Amperage 2.5 Amps, No Load
- Speed 4850 RPM @ 12V, No Load
- Rotation Reversible
- Enclosure Open
- Duty Continuous, Air-Over
- Mount None
- Shaft 5/16" dia. x 1 1/8" overall length w/ flat
- Size 5 1/4" W x 6 1/2" dia.
- Shpg. 6 lbs



12 VDC Permanent Magnet Motor

ITEM 10-3096

\$3.99

• New, MABUCHI permanent magnet motor. Model RS-545PH-19185. Leads have Molex connector.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 0.2 Amps
- Speed 1450 RPM
- Torque 1.4 oz.in.
- Rotation Reversible
- Duty Intermittent
- Enclosure Open
- Mount 2 M3x0.5 tapped holes 25mm c/c
- Shaft 1/8" dia x 1/2" long (knurled)
- Size 1.45" dia. x 2"
- Shpg. 1/2 lb.



ITEM 10-3099

\$3.99

• Same as 10-3096 above except 1120 RPM Rated 4085 RPM @ 24 and Shaft 1/8" dia x 1/2" long, grooved

24 VDC Permanent Magnet Motor

ITEM 10-3097

\$3.99

• New, permanent magnet motor. "133000313F" stamped into motor housing.

SPECIFICATIONS

- Voltage 24 VDC
- Speed 1120 RPM Rated 1800 RPM @ 24 VDC, No Load
- Rotation Reversible
- Duty Intermittent
- Enclosure Open
- Mount Two tapped holes in face on 1" centers
- Shaft 0.294" dia x 1/2" long 12T spline
- Size 2 1/2" x 1 1/2" dia.
- Shpg. 1 lb.



ITEM 10-3098

\$3.99

• Same as 10-3097 above except 1925 RPM @ 24 and Shaft 1/8" dia x 1/2" long, grooved

3400 RPM, 24 VDC

ITEM 10-1796

\$9.95

• New, BUEHLER MOTOR INC. Dual shaft, permanent magnet motor.

SPECIFICATIONS

- Voltage 24 DC
- Amps 0.15 no load
- RPM 3435
- Rotation reversible
- Enclosure fully enclosed
- Duty intermittent
- Mount face
- 3 bolts on 1 1/16" BC
- Shafts 5/32" diam. x 3/4" w/flat
- 5/32" diam. x 7/16"
- Size 1 9/16" diam. x 3"
- Shpg. 2 lbs.

