



12 VDC Fans


• New, axial fans. Provide airflow at very low sound levels. Low power consumption. Easy to mount with holes in each corner.



ITEM	CFM	Mfg.	Watts	RPM	# Blades	db	Bearing	Size	Shpg.	Price
16-1507	17	NMB	1	3600	5	28	Ball	60mm x 60mm x 25mm	¼ lb.	\$1.89
16-1508	22	Globe	2.04		5	34	Ball	60mm x 60mm x 25mm	¼ lb.	\$2.49
16-1522	9.5	GDT	1.2	6000	9	27	Sleeve	40mm x 40mm x 10mm	¼ lb.	\$2.99
16-1524	11.4	Delta	1.8	5500	7	35	Ball	50mm x 50mm x 10mm	¼ lb.	\$2.99
16-1525	11.9	Protechnic	2.3	5800	9	34.6	Rifle	50mm x 50mm x 10mm	¼ lb.	\$2.99
16-1527	50	Delta	10.44		7	55	Ball	60mm x 60mm x 25mm	¼ lb.	\$3.49
16-1517	52	MassCool	3	1500	7	25	Sleeve	120mm x 120mm x 25mm	½ lb.	\$4.99
16-1529	52	AVC	3.6		7	34	Sleeve	92mm x 92mm x 25mm	½ lb.	\$3.99
16-1519	98.6	CoolMa x	9.6	3000	7	43.3	Ball	120mm x 120mm x 25mm	½ lb.	\$4.99
16-1518	108	Sunon	5.4	3100	7	44.5	Vapo	120mm x 120mm x 25mm	½ lb.	\$4.99
16-1528	109	Nidec	20.7	8500	7	60	Ball	80mm x 80mm x 38mm	½ lb.	\$3.99
16-1531	110	SanAce	13.2	5000	7	50	Ball	92mm x 92mm x 38mm	½ lb.	\$3.99

25 CFM 12 VDC Blower

ITEM 16-1544



\$7.95

• New, NICEC Gamma30 model A34124 centrifugal blower. Brushless design with lubricated ball bearing. Flat mounting on back side. 2 thru holes for mounting.

SPECIFICATIONS

- Flow 25 CFM max.
- Voltage 12 DC
- Amperage 0.7 Amps
- Speed 3800 RPM

- Sound level 57.4 dBA
- Inlet 2⁵/₁₆" dia.
- Outlet 1¹/₈" x 2¹/₈"
- Size 3.83" x 3.72" x 1.3"
- Shpg. ½ lb.

ITEM 16-1545

• NICEC Gamma28 model A33475-68

SPECIFICATIONS

- Flow 10 CFM max.
- Voltage 12 DC
- Amperage 0.29 Amps

- Inlet 1⁷/₈" dia.
- Outlet 1⁵/₁₆" x 1³/₈"
- Size 3" x 3" x 1¹/₈"
- Shpg. ¼ lb.

\$6.95

112 CFM, 12 VDC Fan

ITEM 16-1515
\$19.95

• New, SPAL USA Model VA32-A100-62S fan. Plastic housing and blower wheel. Waterproof motor. Pusher design draws air over motor toward fan blades for discharge.

SPECIFICATIONS

- Air flow
112 CFM at 0" H₂O
30 CFM at 0.3" H₂O
- Voltage 12 DC
- Amperage
1.8 amps at 112 CFM
1.7 amps at 30 CFM

- Max. static press. 0.5" H₂O
- Duty continuous
- Mount 4 hole flange
82mm x 82mm
- Blade count 5"
- Blade dia. 3³/₄"
- Size 5" dia. x 2¹/₈"
- Shpg. 2 lbs.



200 CFM 48 Volt DC Fan

ITEM 16-1521

\$4.99

• New, SUNON fan model PSD-4812PMB1. Sound level 62 db. Ball bearing. Thermoplastic housing and impeller.

SPECIFICATIONS

- Flow 200 CFM max.
- Voltage 48 DC
- Power 19 Watts
- Speed 4000 RPM



- Blades 9
- Mount 110mm sq.
- Size 120mm x 120mm x 38mm
- Shpg. 1½ lbs.

Stepper Motor Driven Low Flow Blower


ITEM 16-1450

\$24.95

• Unused, blower assembly from a CPAP breathing machine. NOT FOR MEDICAL REPLACEMENT PURPOSES. Heavy aluminum housing with isolation to control sound. Performance and motor specification are unknown. Wiring diagram is NOT available.

SPECIFICATIONS

- Motor Stepper (8 leads)
- Duty Continuous
- Inlet ¾" OD tubing
- Outlet ¾" OD tubing
- Size 7¹/₂" x 8" x 3¹/₂"
- Shpg. 5 lbs.



12 or 24 VDC Heavy Duty Cab Fans

Two Speed Metal Blades



• Brand new, SERVICEMATE two speed cab fans. Metal mounting base with swivel ball joint to position air flow. Toggle switch for low/off/high. Aluminum fan blades with chromed steel shroud. Single wire installation (ground thru base).

SPECIFICATIONS FOR BOTH

- Blade dia. 6¹/₄"
- Mount four hole pattern 1³/₄" x 1"
- Number of blades 4
- Size 7¹/₄" x 5" x 8³/₄"
- Shpg. 5 lbs.

ITEM 16-1458-12

\$58.80

• Model SM3012, 12 VDC, 1.6/2.6 amps.

ITEM 16-1458-24-A

\$45.00

• Model SM3024, 24 VDC, 0.8/1.25 amps.

12 VDC Cab Fan

ITEM 16-1503
\$19.99

• Brand new, two speed cab fan. Metal mounting base with swivel ball joint to position air flow. Toggle switch for low/off/high. Aluminum fan blades with chromed steel shroud. Two wire installation.

SPECIFICATIONS

- Voltage 12 DC
- Amperage 0.6/0.9 Amps
- Blade dia. 6¹/₄"
- Number of blades 4
- Mount 3 hole pattern 2¹/₁₆" B.C.
- Size 7¹/₄" x 4¹/₄" x 8³/₄"
- Shpg. 3 lbs.



26 CFM,
48 VDC
ITEM 16-1449
\$8.95

• New, ROTRON Biscuit centrifugal blower. Operating voltage range 24-56 DC. Plastic body.

SPECIFICATIONS

- Model BD48B3
- Airflow 26 CFM
- Voltage 48 DC
- Pressure 0.87" H₂O
- Inlet 2³/₄" dia.
- Outlet 1" x 2⁹/₁₆"
- Blower wheel 3¹/₄" dia. x 5⁵/₈"
- Mount 4 holes thru body
- Size 4.8" x 4.8" x 1.6"
- Shpg. 2 lbs.



9 VDC Muffin Fan

ITEM 16-1047
\$5.99

• New ROTRON. Supplied with housing to direct airflow through fan and turn 90° through 1¹/₂" x 4¹/₂" outlet. Ideal for moving air through cabinets with restricted access. Operates on 9 VDC, 0.6 amps. Approx. 90 CFM airflow. 5 blades, 4¹/₄" diam. Size 5" x 3¹/₈" x 5". Shpg. 2 lbs.