

## 12 VDC Motor Reversing Contactor



**ITEM 11-3149**  
**\$41.95**

• Brand new TROMBETTA Model 214-1231-A11 reversing polarity contactor. Ideal for controlling permanent magnet motors. Dynamic braking in de-energized state. Sealed plastic housing.

### SPECIFICATIONS

- 12 VDC coil
- Contact ratings 12 VDC nominal, 15 VDC max 75 amps for 5 min. max 125 amps for 30 sec. 150 amps in-rush
- 5 min. max ON time
- 20% max duty cycle
- Coil terminals 1/4 spade
- Motor & battery terminals 5/16"-24 studs
- 2 bolt mount on 4 1/8" ctrs.
- Size 5" x 3 3/8" x 3"
- Shpg. 1 lb.

**ITEM 11-3149-COVER \$6.80**

• Plastic cover for ITEM 11-3149 above. 2 hole mount. Shpg. 1/10 lb.

## 12 VDC SPDT Relay



**ITEM 11-3222-RM**  
**\$3.10**

• Brand new. Ideal for auxiliary lights, motors. Plastic enclosure. Steel mounting tab.

### SPECIFICATIONS

- Coil Voltage 12 volt DC
- Contacts SPDT
- Contact Ratings 14 VDC max 30 Amps break
- 40 Amps make
- Mounting Single hole
- Terminals 1/4" spade
- Size 1" x 1" x 1 1/4"
- Shpg. 1/4 lb.

## 15 Amp SPDT Roller Lever Microswitch



**ITEM 11-3613**  
**\$2.95**

• New, Unimax model A480. Lever has 60° upward bend at actuator.

### SPECIFICATIONS

- Contact Type SPDT
- Contact Ratings: 15 Amps @ 125/250 VAC
- Actuator Type Roller
- Lever arm
- Terminals 1/4" spade
- Size 1 7/8" x 3/4" x 9/16"
- Mount 2 hole 1" c/c
- Shpg. 1/8 lb.

## 12 VDC SPDT Relay



**ITEM 11-3076**  
**\$2.39**

• New. 12 volt DC 43 ohm coil. Normally open 5 amp contacts. Grounds thru mounting bracket. Push on terminals. Size 1 1/2" x 1 1/8" x 7/8". Shpg. 1/4 lb.

## RV/Mobile Home Adapter



**ITEM 11-3225**  
**\$3.95**

• New, Eletricord (Leviton) model C-1427-009-BL. Male end plugs into 30 amp 125V outlet and converts to standard 15 amp female.

### SPECIFICATIONS

- Conductor Gauge 12
- Conductor Count 3
- Length 9"
- Jacketing Type STW
- End 1 30 Amp 125 volt male
- End 2 15 Amp 125 volt female
- Shpg. 1 lbs.

## Handheld Winch Reversing Control



**ITEM 11-3644**  
**\$19.95**

• New. Handheld remote control for 2000 lb. winches. Polarity reversing. Heavy contacts and cables eliminate need for solenoids. Black plastic housing. Four leads with ring terminals.

### SPECIFICATIONS

- Lead Lengths: 50" to winch
- 66" to battery
- Voltage 12 DC
- Shpg. 2 lbs.

## Hand Held Remote Control



**ITEM 11-3640**  
**\$9.95**

• New hand remote control switch with pistol grip.

### SPECIFICATIONS

- Switch Type Rocker
- Contacts SPDT-CO
- Contact Rating 16 amps 125/250 Volt
- Action Momentary
- Switch Positions Three (on-off-on)
- Cord 3 conductor 10 ft.
- Connector 3 pin
- Size 3 1/4" x 4" x 6"
- Shpg. 1 lb.

## 12 VDC, 70 Amp Waterproof RelayPack



**ITEM 11-3411**  
**\$19.95**

• New, STIRLING TECHNOLOGIES Part# DN13911. Original equipment for controlling a hydraulic slide-out system on motorhomes. Includes fuse on positive control lead. 3 studs for motor connections.

### SPECIFICATIONS

- Coil voltage 12 volt DC
- Contact rating 70 amps
- Mount 2 holes, 4 3/4" c/c
- Contacts 2 independent normally open
- Size 5 1/2" x 1 1/2" x 3 3/4"
- Shpg. 1 lb.

## Handlebar Mount Remote Switch



**ITEM 11-3643**  
**\$14.95**

• New, handle bar mount switch for momentary use on winches. Integral switch guard in body. Rubber cover labeled for In/Out.

### SPECIFICATIONS

- Contact SPDT-CO
- Contact Ratings 16 amps at 125 Volt
- Action Momentary
- Leads Red 3 Ft. Black & Green 8 Ft.
- Size 2" x 2" x 1"
- Shpg. 1 lb.

## 120/240 VAC Generator Panel



**ITEM 11-3306**  
**\$8.99**

• New, generator panel outlet enclosure box with hinged cover. Surface mounting to a panel. Four stud mount for use with 3/16" thread cutting speed nuts. Two push-button reset circuit breakers. For generators.

### SPECIFICATIONS

- 240/120 Outlet
- NEMA L14-30, 30 amp twist-lock
- 120 Outlets
- 3-prong 20 amp duplex
- Circuit Breaker Rating 20 amps
- Panel Opening Size 8" x 5 1/8"
- Mounting Studs c/c 6 1/2" x 5 2 1/2"
- Mounting Studs 3/16" diameter
- Face Size 8 1/2" x 6 1/8"
- Size 4 7/8" x 8 1/2" x 6 1/8"
- Shpg. 4 lbs.

## DC Motor Reversing Contactors



• Brand new, SPAL reversing polarity contactor. Ideal for controlling permanent magnet motors. Both output terminals rest at ground for dynamic braking in de-energized state. Splash resistant body with O-ring seals. Silver-plated contacts.

### SPECIFICATIONS

- Contact ratings 5-30 VDC 100 amps max duty cycle 6 min. at max. cont. output
- Two hole mount 2 3/4" ctrs.
- 20% max duty cycle
- Coil terminals 1/4" spade
- Motor & battery terminals 6mm studs
- Size 2 1/8" x 3 3/16" x 3 1/4"
- Shpg. 1 lb.

**ITEM 11-3169-12 \$53.65**

• Coil ratings 12 VDC nominal, 15 VDC max. 7 ohms

**ITEM 11-3169-24 \$56.35**

• Coil ratings 24 VDC nominal, 30 VDC max. 26.8 ohms

## 24 VDC, 3PDT

**ITEM 11-1195**  
**\$3.85**



• Used. Coil 55 ohms. 10 amp at 125 VAC, 5 amp at 240 VAC. Clear plastic dust proof case w/slotted flange mount. Tiny lamp across the coil lights up when relay energizes. Removable diode shunt across relay coil. Size 1 7/8" x 1 1/2" x 1 1/2". Shpg. 1/4 lb.

## SPDT Relay w/Base



**Prop 65** **ITEM 11-3222**  
**\$4.95**

• New. Ideal for auxiliary lights, motors. Includes base socket with 11" leads.

### SPECIFICATIONS

- Coil voltage 12 volt DC
- Contacts SPDT
- Mounting single hole
- Amp rating 30 break, 40 make
- Size 1" x 1" x 1 3/4"
- Shpg. 1/2 lb.

## Generator Panel



**ITEM 11-3646**  
**\$6.95**

• New generator panel. Electrical components are mounted on a steel panel. Use for generators, electrical panels, power center for a workbench, or remove the components to install in other applications.

### SPECIFICATIONS

- One 120 Volt AC 15 amp 3-prong outlets
- One 120/240 Volt AC, 20 Amp, 4 conductor twist lock outlet (NEMA L14-20)
- Two 125/250 Volt AC, 20
- Amp, manual reset, circuit breakers
- 4 bolt mount on 6 1/4" bolt circle
- Overall 6 1/2" x 6 1/2" x 1 1/4"
- Shpg. 1 lb.

## 115 VAC : 12 VDC 3 AMP Power Supply



**ITEM 15-1204**  
**\$4.95**

• New CHALLENGER CABLE SALES model PS-2.1-12-DC-S1 power supply. Comcast ESP-3. UL listed. 7 ft wall cord. UL listed. 6 ft. output cord with 5.5mm barrel end.

### SPECIFICATIONS

- Input 115 Volt AC, 60 Hz, 96 Watts
- Output 12 Volt DC, 3 Amps
- Overall size 4 1/2" x 2" x 1 1/4"
- Shpg. 1 lb