

2" x 24" x 1.25"**ITEM 9-12114**

Pins not included.

SPECIFICATIONS


- New, Double-Acting
- Bore x Stroke 2" x 24"
- Pressure 2500 PSI max.
- Rod Dia. 1 1/4"
- Ports SAE 6
- Retracted Length 35 1/4"
- Clevis Ends
- Rod Outside Width 2 5/16"
- Rod Inside Width 1 9/16"
- Base Outside Width 2 5/16"
- Base Inside Width 1 1/4"
- Pin Holes 1"
- Shpg. 27 lbs.

\$99.95**2" x 55" x 1"****ITEM 9-12493**

Cylinder has 3/8" feeder tube from retract port located on base end.

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2" x 55"
- Pressure 3000 PSI
- Rod Dia. 1"
- Ports SAE 6
- Retracted Length 65.25"
- Pin Holes 3/4"
- Swivel Eye Ends
- Swivel Eye Width 1"
- Shpg. 44 lbs.

\$199.95**2.25" x 9.625" x 1.25"****ITEM 9-8390****SPECIFICATIONS**

- New, double acting
- Bore x Stroke 2 1/4" x 9 5/8"
- Pressure 3000 PSI max.
- Rod dia. 1 1/4"
- Ports SAE 6
- Base to crosstube pin lgth. 17 1/8"
- Trunnion to crosstube pin lgth. 7 3/4"
- Rod crosstube 2 5/16" wide
- Pin hole 25 mm (0.984")
- Base end plain
- Trunnion outside pin width 4.96"
- Trunnion inside pin width 3.34"
- Trunnion pin size 30 mm (1.18")
- Trunnion pin lgth. 1.13"
- Shpg. 22 lbs.

\$79.99**2.25" x 19.5" x 1.375"****ITEM 9-8912****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2 1/4" x 19 1/2"
- Pressure 3000 PSI max.
- Rod Dia. 1 3/8"
- Crosstube ends
- Ports SAE 6
- Width 3"
- Retracted Length 27 1/4"
- Pin holes 1"
- Shpg. 26 lbs.

\$89.99**2.25" x 19.5625" x 1.25"****ITEM 9-8431**


• New. Ports offset 90° facing base end.

SPECIFICATIONS

- Double acting
- Bore x Stroke 2 1/4" x 19 1/2"
- Pressure 3000 PSI max.
- Rod dia. 1 1/4"
- Ports JIC 6M
- Retracted lgth. 29 7/16"
- Crosstube ends rod 4 5/16" w., base 3" w.
- Pin holes 1"
- Shpg. 29 lbs.

\$89.99**2.25" x 20.875" x 1.25"****ITEM 9-8432****SPECIFICATIONS**

- New, double acting
- Bore x Stroke 2 1/4" x 20 7/8"
- Pressure 3000 PSI max.
- Rod dia. 1 1/4"
- Ports JIC 6M
- Retracted lgth. 29 7/16"
- Crosstube ends rod 4 5/16" w., base 3" w.
- Pin holes 1"
- Shpg. 29 lbs.

\$89.99**2.5" x .25" x 1" Double Acting Cylinder****ITEM 9-9803****SPECIFICATIONS**

- New, Double acting tie rod
- Double acting tie rod
- Bore x Stroke 2 1/2" x 1/4"
- Pressure 1500 PSI
- Retracted lgth. 12 1/8"
- Rod dia. 1"
- Ports 3/8" NPT
- Rod threaded 7/8-14
- Base end blank
- Shpg. 12 lbs.

\$59.99**2.5" x 3.3125" x 1"****ITEM 9-12504****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2.5" x 3.3125"
- Pressure 2000 PSI
- Rod Dia. 1"
- Extend Port SAE 6
- Retract Port SAE 4
- Retracted Length 8.75"
- Pin Holes 3/4"
- Rod End Swivel Eye Width 1"
- Base End: Thru-Hole Width 2.75"
- Shpg. 10 lbs.

\$49.95**2.5" x 4" x 1"****ITEM 9-12492****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2.5" x 4"
- Pressure 2500 PSI
- Rod Dia. 1"
- Ports 3/8" NPT
- Retracted Length 14.25"
- Pin Holes 1"
- Clevis Ends
- Shpg. 19 lbs.

\$59.95**2.5" x 6" x 1.125"****ITEM 9-12427****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2.5" x 6"
- Pressure 2500 PSI
- Rod Dia. 1.125"
- Ports SAE 8
- Retracted Length 16.25"
- Pin Holes 1"
- Clevis Ends
- Shpg. 15 lbs.

\$59.95

See pg. 57 for new line of Wolverine by Prince swivel ball end cylinders.

**2.5" x 6" x 1.125"****ITEM 9-12490****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2.5" x 6"
- Pressure 3000 PSI
- Rod Dia. 1.25"
- Ports SAE 8
- Retracted Length 14"
- Pin Holes 1"
- Cross-Tube Ends
- Rod End: Width 2"
- Base End: Width 3.125"
- Shpg. 18 lbs.

\$69.95**2.5" x 6" x 1.125"****ITEM 9-12173****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2 1/2" x 6"
- Clevis Ends
- Pin Diam. 1"
- Pressure 2500 PSI
- Rod Diam. 1 1/8"
- Ports 3/8" NPT
- Retracted Length 16 1/4"
- Shpg. 22 lbs.

\$57.95**2.5" x 6" x 1.125"****ITEM 9-12447****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2.5" x 6"
- Pressure 3000 PSI
- Rod Dia. 1.125"
- Ports SAE 8
- Retracted Length 16.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 19 lbs.

\$89.99

2.5" x 7" x 1.125" DA Rephasing Cylinder

**ITEM 9-7478**

• Rephasing cylinder with internal ball checks to ease cylinder start-up at both ends of stroke.

SPECIFICATIONS

- New, Double acting
- Bore x stroke 2 1/2" x 7"
- Pressure 2500 PSI max.
- Rod dia. 1 1/8"
- Ports SAE 6
- Retracted lgth. 15"
- Threaded rod end 1"-16 x 1 1/2" threaded 1" across wrench flats
- Tapped base end 2 1/2" O.D.
- Tapped 1 1/8"-12 x 1 3/4" deep
- Shpg. 19 lbs.

\$49.95**2.5" x 8" x 1.125"****ITEM 9-12308****SPECIFICATIONS**

- New, Double Acting
- Bore x Stroke 2.5" x 8"
- Pressure 2500 PSI max.
- Rod Dia. 1.125"
- Ports 3/8" NPT
- Retracted Length 20.25"
- Clevis Ends
- Shpg. 23 lbs.

\$54.95