

6" x 36" x 2.5"



ITEM 9-9011

\$499.95

- Each port has adjustable load check valve.

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 6" x 36"
- Pressure 3000 PSI max.
- Rod Dia. 2 1/2"
- Ports SAE 6

- Retracted Length 53"
- Rod End Crosstube
- Width 3"
- Pin Hole 2 3/8"
- Round Base End
- Diameter 5"
- Shpg. 310 lbs.

Truck freight only

6" x 45" x 4"



SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore x Stroke 6" x 45"
- Pressure 3500 PSI max.
- Rod dia. 4"
- Wall thickness 1 1/2"

- Ports 1 1/4" four bolt flange, code 61
- Retracted lgth. 69"
- Tang ends w/swivel eye rod 3 1/2", base 3 1/8"
- Pin holes 3 1/4"
- Shpg. 650 lbs.

Truck freight only.

ITEM 9-10292-L

\$599.95

- Ports face to the left when looking at base end of cylinder. Part# 708-7623.

ITEM 9-10292-R

\$599.95

- Ports face to the right when looking at base end of cylinder. Part# 708-7624.

6" x 47.5" x 3.25"



ITEM 9-9039

\$699.95

- Cylinder has cartridge valve in port manifold marked E2B060 7 3800 N MK2 AC.

SPECIFICATIONS

- Unused, old inventory.
- Double Acting
- Bore x Stroke 6" x 47.5"
- Pressure 3000 PSI max.
- Rod Dia. 3.25"
- Ports SAE 10

- Retracted Length 86.75"
- Pin Holes 2 1/2"
- Cross-Tube Ends
- Width 4.625"
- Base End: Width 6.75"
- Shpg. 371 lbs.

Truck freight only

6" x 50" x 3.5"



ITEM 9-9094

\$599.95

SPECIFICATIONS

- Unused, old inventory.
- Double Acting
- Bore x Stroke 6" x 50"
- Pressure 3000 PSI max.
- Rod Dia. 3 1/2"
- Ports SAE 16
- Retracted Length 70 1/4"

- Pin Holes 2 1/2"
- Tang w/ Swivel Eye Ends
- Rod End: Max Thickness 2 3/16"
- Base End: Max Thickness 2 3/16"
- Shpg. 450 lbs.

Truck freight only

6.25" x 51.75" x 3.5"



ITEM 9-9819

\$599.95

- Two extend ports and two retract ports.

SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore x Stroke 6 1/4" x 51 3/4"
- Pressure 3000 PSI max.
- Rod dia. 3 1/2"
- Wall thickness 1 1/2"

- Ports SAE 16
- Retracted lgth. 77"
- Rod tang w/swivel eye 2 1/4"
- Base end clevis 4 7/8" wide
- Pin holes 2 1/2"
- Shpg. 570 lbs.

Truck freight only.

6.5" x 17.75" x 3.5"



ITEM 9-20104

\$599.95

SPECIFICATIONS

- New, Double-Acting
- Bore x Stroke 6 1/2" x 17 3/4"
- Pressure 3000 PSI max.
- Rod Dia. 3 1/2"
- Ports 1" Four-Bolt Flange,

- Code 61
- Retracted Length 44 1/4"
- Tang Ends
- Pin Holes 100mm (3.937")
- Max Thickness 4 9/16"
- Shpg. 500 lbs.

Truck freight only

6.5" x 49.5" x 3"



ITEM 9-10175

\$599.95

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 6 1/2" x 49 1/2"
- Pressure 3000 PSI max.
- Rod Dia. 3"
- Ports 1 1/4" Four-Bolt Flange, Code 61
- Retracted Length 35"
- Rod End Clevis

- Pin Hole 1 3/4"
- Trunnion Female
- Pin Outside Width 11 1/8"
- Pin Inside Width 7 1/4"
- Pin Center to Rod Pin Center 35"
- Pin Center to Base End 37 1/4"
- Pin Diameter 2 1/2"
- Shpg. 490 lbs.

Truck freight only

6.5" x 50" x 3"



ITEM 9-9833

\$599.95

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 6.5" x 50"
- Pressure 3000 PSI max.
- Rod Dia. 3"
- Ports 4 bolt 1" code 6 flange size 16

- Retracted Length 67.75"
- Cross-Tube Ends
- Rod End: Width 8.5"
- Pin Hole 3"
- Base End: Width 4.5"
- Pin Hole 3-1/2"
- Shpg. 443 lbs.

Truck freight only

6.5" x 54" x 3"



ITEM 9-9823

\$599.95

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 6.5" x 54"
- Pressure 3000 PSI max.
- Rod Dia. 3"
- Ports 4 bolt 1" Code 61 flange size 16
- Retracted Length 35"
- Overall Length 81.5"
- Rod End Female Trunnion

- Pin Outside/Inside Width 11.188" / 7.25"
- Pin-Center-To-Rod Pin Center 35"
- Pin Center To Base End 44.5"
- Pin Diamter 2.526"
- Pin Hole 2 1/2"
- Base End Clevis
- Pin Hole 1 3/4"
- Shpg. 473 lbs.

Truck freight only

6.5" x 55.875" x 3"



ITEM 9-10291

\$599.95

SPECIFICATIONS

- Bore x Stroke 6" x 55.875"
- Pressure 3000 PSI max.
- Rod Dia. 3"
- Ports SAE 12
- Retracted Length 76"
- Swivel Ends

- Rod End: Thickness Max 2.41"
- Base End: Thickness, Max 2.42"
- Thru-hole Width 2.62"
- Pin Holes 3"
- Shpg. 422 lbs.

Truck freight only

6.5" x 54" x 3"



ITEM 9-9588

\$599.95

- Internal cushion valves at end of extend and retract strokes.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 6 1/2" x 54"
- Pressure 3000 PSI max.
- Rod End Clevis
- Outside Width 7"
- Pin Hole 1 3/4"
- Trunnion Female
- Pin Outside Width 11 1/8"

- Pin Inside Width 7 3/16"
- Pin Center to Rod Pin Center 34 7/8"
- Pin Center to Base End 44 1/2"
- Pin Diameter 2 1/2"
- Rod Dia. 3"
- Ports 1" Four Bolt Flange, Code 61
- Retracted Length 34 7/8"
- Shpg. 540 lbs.

Truck freight only

6.5" x 67.375" x 5"



ITEM 9-10119

\$699.95

- One SUN model CKEB-XCN pilot-to-open check valve with 3:1 pilot ratio and 30 gpm capacity, and one unidentifiable SUN model cartridge valve.

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 6 1/2" x 67 3/8"
- Pressure 3000 PSI max.
- Rod Dia. 5", Hollow
- Ports SAE 12
- Retracted Length 89"

- Pin Holes 3"
- Tang w/ Swivel Eye Ends
- Rod End: Max Thickness 2 5/8"
- Base End: Max Thickness 2 5/8"
- Shpg. 575 lbs.

Truck freight only

7" x 17.25" x 4"



ITEM 9-9023

\$429.95

- Features a SUN pilot-to-open check valve with sealed pressure.

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 7" x 17 1/4"
- Pressure 3000 PSI max.
- Rod Dia. 4"

- Ports SAE 8
- Retracted Length 56 1/2"
- Tang Ends
- Pin Holes 2 1/2"
- Max Thickness 2"
- Shpg. 490 lbs.

Truck freight only

7" x 24.25" x 3"



ITEM 9-9764

\$599.95

- Base end of cylinder has mount for manifold block and associated valving with two 1/4" I.D. ports (for retract port) and two 1/2" I.D. ports (for extend port).

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 7" x 24 1/4"
- Pressure 3000 PSI max.
- Rod Dia. 3"
- Ports SAE 10
- Retracted Length 33 3/8"
- Rod End Tang
- Max Thickness 2"

- Pin Center to Tang End 2 1/4"
- Pin Hole 2.229"
- Trunnion Male
- Pin Outside Width 11 1/8"
- Pin Inside Width 7 7/8"
- Pin Center to Rod Pin Center 33 3/8"
- Pin Center to Base End 1 3/4"
- Pin Diameter 2 1/2"
- Shpg. 310 lbs.

Truck freight only