




3 Bolt Mount

• New White Drive Products low speed high torque motors. Interchangeable with many different brands of similar type motors. Pictures are representative of motors. More information including pictures and additional specifications can be found on website.



2 Bolt Mount



4 Bolt Mount

Item	Model	Displ		PS		Torque		RPM		GPM		Mount	Shaft	Ports	Shpg.	Price
		cu. In.	Cont.	Cont.	Cont.	Cont.	Cont.	Cont.	Cont.	Cont.	Cont.					
9-8630-A	125008J05C3AAAAA	0.5	1450	97	1864	4	3-bolt round	5/8" keyed	SAE 6 End	7 lbs.	\$149.99					
9-8630-B	125032JL5C3AAAAA	1.9	1450	354	622	5	3-bolt round	5/8" keyed	SAE 6	7 lbs.	\$149.99					
9-12499-A	145032A11B1AAAAA	1.9	1450	372	1244	16	2-bolt SAE A	1" keyed	SAE 10	14 lbs.	\$119.95					
9-8837-A	276040F3114AAAAA	2.5	2000	630	830	9	4-bolt square	1" tapered keyed threaded	SAE 10	18 lbs.	\$169.99					
9-8831-D	155060F3153AAAAAC	3.6	2320	1106	1185	16	4-bolt square	1" w/crosshole	SAE 10	16 lbs.	\$129.99					
9-8834-B	255060F3705AAAAA	3.6	2250	1221	890	14	4-bolt square	1" w/crosshole	Manifold	14 lbs.	\$149.99					
9-12499-E	155060A11B1AAAAA	3.6	2320	1106	1185	16	2-bolt SAE A	1" keyed	SAE 10	16 lbs.	\$129.95					
9-12499-F	155060A17B1AAAAA	3.6	2320	1106	1185	16	2-bolt SAE A	1" keyed	Manifold	16 lbs.	\$129.95					
9-8825	276070A1710AAAAA	4.3	2000	1120	650	12	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.99					
9-12499-B	155100A17B1AAAAA	5.9	2320	1726	720	16	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.95					
9-12499-J	155100A1102AAAAA	5.9	2320	1726	728	16	2-bolt SAE A	1" keyed	SAE 10	18 lbs.	\$129.95					
9-12499-D	255100A1710AAAAA	6.1	3000	2122	610	16	2-bolt SAE A	1" keyed	Manifold	20 lbs.	\$129.95					
9-8632-X	255130A1316BAAAA	7.9	2500	2797	472	16	2-bolt SAE A	25mm keyed	1/2" BSPP and Manifold	18 lbs.	\$119.99					
9-8632-Y	255130A1901ABAAA	7.9	2500	2797	472	16	2-bolt SAE A	7/8" 13T spline	SAE 10	18 lbs.	\$119.99					
9-8672-H	281130A6321BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	1/2" BSPP and Manifold	18 lbs.	\$139.99					
9-8672-G	281130A6821BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	1/2" BSPP	16 lbs.	\$139.99					
9-12499-C	155160A17B1AAAAA	9.4	2320	2840	452	16	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.95					
9-8673	155200A6310BAAAA	11.6	2180	3365	367	16	2-bolt SAE A	1" keyed	1/2" BSPP and Manifold	18 lbs.	\$139.99					
9-8632-CCC	255200A1001AAAAA	12.1	2500	4088	308	16	2-bolt SAE A	7/8" 13T spline	1/2" NPT	20 lbs.	\$149.99					
9-8834-I	255200A1713AAAAA	12.1	2500	4088	308	16	2-bolt SAE A	1" keyed	1/2" BSPP and Manifold	20 lbs.	\$129.99					



3 Bolt Mount

• New Chief Drive Products low speed high torque motors. Interchangeable with many different brands of similar type motors. Pictures are representative of motors. More information including pictures and additional specifications can be found on website.



2 Bolt Mount



4 Bolt Mount

Item	Model Number	Model Series	Displ cu in	PSI Cont	Torque Cont	RPM Cont	GPM Cont	Mount	Shaft	Ports	Shpg	Price
9-12316-12-S	273037	BJM	0.8	1450	150	1521	5	3 bolt	5/8" keyed	SAE 6	6 lbs.	\$109.95
9-12316-50-S	273040	BJM	3.1	1885	389	395	5	3 bolt	5/8" keyed	SAE 6	6 lbs.	\$109.95
9-12315-60-2-S	273009	BHD	3.6	1800	903	880	14	2 bolt SAE A	1" keyed	SAE 10	15 lbs.	\$109.95
9-12315-80-2-S	273010	BHD	4.9	1800	1133	752	16	2 bolt SAE A	1" keyed	SAE 10	15 lbs.	\$111.95
9-12315-80-4-P	273017	BHD	4.9	1800	1133	752	16	4 bolt square	1" keyed	1/2" NPT	14 lbs.	\$111.95
9-12315-160-2-P	273004	BHD	6.9	1800	2222	383	14	2 bolt SAE A	1" keyed	1/2" NPT	16 lbs.	\$115.95
9-12318-240-2-S	273061	BSR	14.4	2500	4850	247	16	2 bolt SAE A	1" keyed	SAE 10	21 lbs.	\$154.95
9-12315-250-2-S	273013	BHD	14.7	1500	2806	248	16	2 bolt SAE A	1" keyed	SAE 10	17 lbs.	\$119.95
9-12315-250-4-P	273022	BHD	14.7	1500	2806	248	16	4 bolt square	1" keyed	1/2" NPT	16 lbs.	\$119.95

11.87 cu in Hydraulic Motor

ITEM 9-7079-200-S \$139.95

• New. DYNAMIC BMRS series low speed high torque hydraulic motor.

SPECIFICATIONS

- Model BMRS200H2KS
- Displacement 11.87 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 2321 PSI cont. 2900 PSI int.
- Torque: 3186 in-lbs. cont. 3894 in-lbs. int.
- Speed:
- 310 RPM cont. 385 RPM int.
- Flow: 15.85 GPM cont. 19.81 GPM int.
- Mount 2 bolt SAE A
- Shaft 1" dia. x 1.84" long w/ 1/4" keyway, threaded 1/4"-20
- Ports SAE 8
- Case Drain None
- Size 6.85" x 5.17" x 3.81"
- Shpg. 22 lbs.



13.91 cu in Hydraulic Motor

ITEM 9-8974-I \$189.95

• New. DYNAMIC hydraulic motor.

SPECIFICATIONS

- Model BMER1230FSRWSR
- Disp. 13.91 cu. in. / rev.
- Pressure 2973 PSI (Cont.) 3481 PSI (Int.)
- Torque 5531 in-lb. (Cont.) 6284 in-lb. (Int.)
- Speed 290 RPM (Cont.)
- 365 RPM (Int.)
- Flow: 17.96 GPM (Cont.) 22.45 GPM (Int.)
- Rotation Reversible
- Mount Four-bolt magneto and two-bolt SAE A
- Shaft 1" dia. x 1.96" long shaft w/ 1/4" wide keyway
- Ports SAE 10
- Size 6 9/16" x 5 5/8" x 5 5/8"
- Shpg. 32 lbs.



18.3 cu in Hydraulic Motor

ITEM 9-8467-A \$199.95

• New. WHITE DR series low speed high torque hydraulic motor.

SPECIFICATIONS

- Model 600300A8523AAAAA
- Displacement 18.3 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3000 PSI cont. 3500 PSI int.
- Torque: 7450 in-lbs. cont. 8600 in-lbs. int.
- Speed:
- 320 RPM cont. 380 RPM int.
- Flow: 25 GPM cont. 30 GPM int.
- Mount 4 bolt magneto on 4.18" bolt circle
- Shaft 1 1/4" dia. x 2.42" long, 14T splined, tapped 5/8"-18
- Ports SAE 10
- Case Drain SAE 4
- Size 6.74" x 5.35" x 5.41"
- Shpg. 41 lbs.

