

Steel Shaft Collars

• Brand new. Solid collars include a set screw, split collars include clamping screws.

Choose from three collar styles.

Solid Shaft Collars
Zinc Plated



Single Split Shaft Collars
Black Oxide Finish



Double Split Shaft Collars
Black Oxide Finish



| ITEM | Bore | O.D. | Width | Price | ITEM | Bore | O.D. | Width | Price | ITEM | Bore | O.D. | Width | Price | Shpg. |
|------------|----------|--------|---------|--------|------------|----------|---------|---------|--------|------------|----------|---------|---------|---------|---------|
| 1-2766-18 | 3/16" | 7/16" | 1/4" | \$0.80 | 1-2767-18 | 3/16" | 5/8" | 5/16" | \$3.70 | 1-2768-18 | 3/16" | 5/8" | 5/16" | \$4.95 | 0.1 lb. |
| 1-2766-25 | 1/4" | 1/2" | 5/16" | \$0.90 | 1-2767-25 | 1/4" | 11/16" | 5/16" | \$3.70 | 1-2768-25 | 1/4" | 11/16" | 5/16" | \$4.95 | 0.1 lb. |
| 1-2766-31 | 5/16" | 5/8" | 5/16" | \$1.10 | 1-2767-31 | 5/16" | 11/16" | 5/16" | \$3.70 | 1-2768-31 | 5/16" | 11/16" | 5/16" | \$4.95 | 0.1 lb. |
| 1-2766-37 | 3/8" | 3/4" | 3/8" | \$1.25 | 1-2767-37 | 3/8" | 7/8" | 11/32" | \$3.85 | 1-2768-37 | 3/8" | 7/8" | 11/32" | \$5.10 | 0.1 lb. |
| 1-2766-43 | 7/16" | 7/8" | 7/16" | \$1.40 | 1-2767-43 | 7/16" | 15/16" | 3/8" | \$3.85 | 1-2768-43 | 7/16" | 15/16" | 3/8" | \$5.20 | 0.1 lb. |
| 1-2766-50 | 1/2" | 1" | 7/16" | \$1.65 | 1-2767-50 | 1/2" | 1 1/8" | 13/32" | \$4.15 | 1-2768-50 | 1/2" | 1 1/8" | 13/32" | \$5.40 | 0.1 lb. |
| 1-2766-62 | 5/8" | 1 1/8" | 1/2" | \$1.70 | 1-2767-62 | 5/8" | 1 5/16" | 7/16" | \$4.60 | 1-2768-62 | 5/8" | 1 5/16" | 7/16" | \$5.80 | 0.1 lb. |
| 1-2766-75 | 3/4" | 1 1/4" | 9/16" | \$2.05 | 1-2767-75 | 3/4" | 1 1/2" | 1/2" | \$4.95 | 1-2768-75 | 3/4" | 1 1/2" | 1/2" | \$6.15 | 0.1 lb. |
| 1-2766-87 | 7/8" | 1 1/2" | 9/16" | \$2.45 | 1-2767-87 | 7/8" | 1 5/8" | 1/2" | \$4.55 | 1-2768-87 | 7/8" | 1 5/8" | 1/2" | \$6.45 | 0.2 lb. |
| 1-2766-93 | 15/16" | 1 1/2" | 9/16" | \$2.45 | 1-2767-93 | 15/16" | 1 3/4" | 1/2" | \$5.20 | 1-2768-93 | 15/16" | 1 3/4" | 1/2" | \$7.10 | 0.2 lb. |
| 1-2766-100 | 1" | 1 5/8" | 5/8" | \$2.55 | 1-2767-100 | 1" | 1 3/4" | 1/2" | \$5.20 | 1-2768-100 | 1" | 1 3/4" | 1/2" | \$7.10 | 0.3 lb. |
| 1-2766-112 | 1 1/8" | 1 3/4" | 5/8" | \$2.95 | 1-2767-112 | 1 1/8" | 1 7/8" | 1/2" | \$5.20 | 1-2768-112 | 1 1/8" | 1 7/8" | 1/2" | \$7.10 | 0.4 lb. |
| 1-2766-118 | 1 3/16" | 2" | 1 1/16" | \$3.75 | 1-2767-118 | 1 3/16" | 2 1/16" | 1/2" | \$5.50 | 1-2768-118 | 1 3/16" | 2 1/16" | 1/2" | \$7.45 | 0.4 lb. |
| 1-2766-125 | 1 1/4" | 2" | 1 1/16" | \$3.75 | 1-2767-125 | 1 1/4" | 2 1/16" | 1/2" | \$5.50 | 1-2768-125 | 1 1/4" | 2 1/16" | 1/2" | \$7.45 | 0.5 lb. |
| 1-2766-137 | 1 3/8" | 2 1/8" | 3/4" | \$4.35 | 1-2767-137 | 1 3/8" | 2 1/4" | 9/16" | \$6.15 | 1-2768-137 | 1 3/8" | 2 1/4" | 9/16" | \$8.10 | 0.6 lb. |
| 1-2766-143 | 1 7/16" | 2 1/4" | 3/4" | \$4.35 | 1-2767-143 | 1 7/16" | 2 1/4" | 9/16" | \$6.15 | 1-2768-143 | 1 7/16" | 2 1/4" | 9/16" | \$8.10 | 0.6 lb. |
| 1-2766-150 | 1 1/2" | 2 1/4" | 3/4" | \$4.35 | 1-2767-150 | 1 1/2" | 2 3/8" | 9/16" | \$6.55 | 1-2768-150 | 1 1/2" | 2 3/8" | 9/16" | \$8.50 | 0.6 lb. |
| 1-2766-162 | 1 5/8" | 2 1/2" | 13/16" | \$4.60 | 1-2767-162 | 1 5/8" | 2 5/8" | 1 1/16" | \$7.90 | 1-2768-162 | 1 5/8" | 2 5/8" | 1 1/16" | \$9.75 | 0.7 lb. |
| 1-2766-168 | 1 11/16" | 2 1/2" | 13/16" | \$4.60 | 1-2767-168 | 1 11/16" | 2 3/4" | 1 1/16" | \$8.65 | 1-2768-168 | 1 11/16" | 2 3/4" | 1 1/16" | \$10.60 | 0.7 lb. |
| 1-2766-175 | 1 3/4" | 2 3/4" | 7/8" | \$5.90 | 1-2767-175 | 1 3/4" | 2 3/4" | 1 1/16" | \$8.65 | 1-2768-175 | 1 3/4" | 2 3/4" | 1 1/16" | \$10.60 | 0.8 lb. |
| 1-2766-187 | 1 7/8" | 2 3/4" | 7/8" | \$5.90 | 1-2767-187 | 1 7/8" | 2 7/8" | 1 1/16" | \$8.65 | 1-2768-187 | 1 7/8" | 2 7/8" | 1 1/16" | \$10.60 | 0.8 lb. |
| 1-2766-193 | 1 15/16" | 3" | 7/8" | \$6.55 | 1-2767-193 | 1 15/16" | 3" | 1 1/16" | \$9.35 | 1-2768-193 | 1 15/16" | 3" | 1 1/16" | \$11.40 | 0.9 lb. |
| 1-2766-200 | 2" | 3" | 7/8" | \$6.55 | 1-2767-200 | 2" | 3" | 1 1/16" | \$9.35 | 1-2768-200 | 2" | 3" | 1 1/16" | \$11.40 | 0.9 lb. |

3/4-16 Swivel Eye Rod End




ITEM 1-3778
\$10.95

• New, Radial Bearing Corporation Model RF-12TH high strength precision swivel eye rod end. Chrome moly ball with Teflon fabric liner, steel housing.

SPECIFICATIONS

- Body: female right hand thread
- Swivel eye bore 3/4" diam.
- Length thru bore 7/8"
- Max. statis load 28,081 lbs.
- Misalignment angle 14° max.
- Thread size 3/4-16
- End to center 2.875"
- Wrench flat 1"
- Shpg. 1 lb.

PTO Shaft



63 HP, 33.25"


ITEM 1-3720-A **\$99.99**

• New BUSH HOG Model 50041190 fixed length PTO shaft. Plastic shaft and joint shielding.

SPECIFICATIONS

- Power 63 HP at 540 RPM
- Series/Category T60
- Lgth. end-to-end min. 33.25"
- Shaft Type Tri-Lobe
- End 1: 1 3/8-6T slide collar
- End 2: 1 3/8-21T w/ int. bolt
- Shaft nominal dia. 1.77" inner, 2.126" outer
- Shpg. 32 lbs.

3 Point Ratchet Jack



ITEM 1-3964 **\$32.99**


• New, BULLDOG model 690058 ratchet jack to adjust 3 point hitch on tractors. Plated clevis ends (no pins). Grease zerks for threads.

SPECIFICATIONS

- Travel 3"
- Load Capacity 16,000 lbs. tension
- Clevis Pin Holes 1"
- Clevis Inner width 1 1/16"
- Handle 10"
- Thread Size 1 1/8"-5 ACME
- Retracted Length 15"
- Shpg. 12 lbs.

Steel Square Key Stock

• Brand new, steel key stock. Use with motors, engines, gear reducers, shafting. One foot length can be cut to get the exact size needed.



| ITEM | Size | Length | Shpg. | Price |
|-------------|-------|--------|----------|---------|
| 1-5030-18-A | 3/16" | 1 1/4" | 1/10 lb. | \$0.80 |
| 1-5030-18-B | 3/16" | 12" | 1/4 lb. | \$3.00 |
| 1-5030-25-A | 1/4" | 1 1/2" | 1/10 lb. | \$1.00 |
| 1-5030-25-B | 1/4" | 12" | 1/4 lb. | \$4.00 |
| 1-5030-31-A | 5/16" | 1 1/2" | 1/10 lb. | \$1.10 |
| 1-5030-31-B | 5/16" | 12" | 1/2 lb. | \$6.00 |
| 1-5030-38-A | 3/8" | 1 5/8" | 1/10 lb. | \$1.35 |
| 1-5030-38-B | 3/8" | 12" | 3/4 lb. | \$7.00 |
| 1-5030-50-A | 1/2" | 1 7/8" | 1/5 lb. | \$1.95 |
| 1-5030-50-B | 1/2" | 12" | 1 lb. | \$10.00 |

60 HP 540 RPM PTO Shaft



ITEM 1-5507 **\$59.95**

• New surplus, Waltersheid W-2300-2507-0815 PTO shaft w/ quick disconnects on each end.

SPECIFICATIONS

- Power 60 HP @ 540 RPM
- Speed 540 RPM
- Series/Category ASAE
- Length: End to End Min. 23"
- Center-of-Cross to Center-of-Cross Min. 14 1/4"
- End to End Max. 29"
- Center-of-Cross to Center-of-Cross Max. 22 1/2"
- End Mountings: Drive End; Connector Type***
- 1 3/8" dia. 6T w/ quick disconnect
- Speed 540 RPM
- Series/Category ASAE
- Length: End to End Min. 23"
- Center-of-Cross to Center-of-Cross Min. 14 1/4"
- End to End Max. 29"
- Center-of-Cross to Center-of-Cross Max. 22 1/2"
- End Mountings: Drive End; Connector Type***
- 1 3/8" dia. 6T w/ quick disconnect
- Cross Width 2.925"
- Cap Diam. 1.062"
- Driven End; Connector Type 1 3/8" dia. 6T w/quick disconnect
- Cross Width 2.925"
- Cap dia. 1.062"
- Class 3
- Shaft Type Square shaft
- Shaft Nominal Dia. 1"
- Shpg. 26 lbs.