


5 RPM, 24 VDC Inline Gearmotor



ITEM 5-1840 \$129.95

• New take-off, SolFocus P/N 350-000062-000 permanent magnet inline gearmotor. Rated for 24 volts but will operate on 12 volts at reduced speed and output.

SPECIFICATIONS

- Speed 5 RPM
- Voltage 24 VDC
- Amperage 4.2 Amps
- Power 1/10 HP
- Torque 109 Nm (964.8 in.lbs.)
- Gear ratio 266.3:1
- Rotation reversible
- Duty continuous
- Enclosure TENV
- Face mount 2 bolt, 106mm (4.173") bolt circle
- Mount pilot 68mm (2.677")
- Shaft 25mm (0.984") dia. x 1 1/2" long 18T spline
- Size 185/8" x 5 3/16" x 6 1/4"
- Shpg. 40 lbs.

171 RPM, 24 VDC Inline Gearmotor



ITEM 5-1839 \$119.95

• New take-off, SolFocus P/N 350-000058-000 permanent magnet inline gearmotor. Rated for 24 volts but will operate on 12 volts at reduced speed and output.

SPECIFICATIONS

- Speed 171 RPM
- Voltage 24 VDC
- Amperage 12 Amps
- Power 1/3 HP
- Torque 9.1 Nm (80.5 in.lbs.)
- Gear ratio 18.7:1
- Rotation reversible
- Duty continuous
- Enclosure TENV
- Face mount 4 bolt, 80mm (3.150") bolt circle
- Mount pilot 60mm (2.362")
- Shaft 14mm (0.551") dia. x 1 3/4" long with 5mm keyway
- Size 12 1/8" x 4 9/16" x 5 1/2"
- Shpg. 19 lbs.

13 RPM 24 VDC Right Angle Gearmotor




ITEM 5-1899 \$12.99

• New, right angle permanent magnet gearmotor. High torque in a compact size for many applications.

SPECIFICATIONS

- Speed 13 RPM no load
- Voltage 24 DC
- Amperage 40 mA no load
- Torque 4 in.-lbs.
- Rotation Reversible
- Duty Continuous
- Mount M3 tapped 4 bolt on 18mm x 33mm centers
- Shaft 6mm dia. x 9/16" long w/flat tapped M3
- Size 3 1/8" x 1 1/4" x 1 1/8"
- Shpg. 1/2 lb.

131 RPM 24 Volt DC Gearmotor



ITEM 5-1887 \$29.95

• New VON WEISE model# V06999AB76 linear actuator. Power extend and power retract, rated to push and pull up to 500 pounds.

SPECIFICATIONS

- Voltage 24 VDC
- Amperage 2.7 Amps
- Capacity 500 lb. max, 250 lb. cont. (Push and Pull)
- Ratio 19:1
- Power 1/20 HP
- Thread 3/4"-5 Acme thread
- Stroke 6 1/8"
- Extension Speed 0.317" / sec. (no load)
- Direction Reversible
- Duty Intermittent
- Size 8 1/4" x 6" x 3 1/8"
- Shpg. 7 lb.

142 RPM 24 Volt DC Inline Gearmotor




ITEM 5-1911 \$8.95

• New, HENKHELL, very compact permanent magnet precision inline gearmotor. Will operate on 6-24 VDC. Planetary gear reduction, dual ball bearings.

SPECIFICATIONS

- Speed 142 RPM no load, 113 RPM rated load
- Voltage 24 DC rated
- Gear Ratio 84:1
- Torque 1.3 in.lb. rated, 4.9 in.lb. stall
- Amps 0.1 no load, 0.2 rated load
- Rotation Reversible
- Duty Continuous
- Mount 4 M2 tapped holes, 18mm B.C.
- Shaft 6mm dia. x 14mm w/crosshole
- Size 11mm dia. x 50mm
- Shpg. 1/2 lb.

90 RPM 12 Volt DC Inline Gearmotor



ITEM 5-1912 \$8.95

• New, KINDLY MOTOR model KC55-37G50-3162 compact permanent magnet inline gearmotor. Operates on 12-24 VDC.

SPECIFICATIONS

- Speed 90 RPM (no load)
- Voltage 12 DC
- Amps 160 mA (no load)
- Torque 8 in.lbs.
- Gear Ratio 50:1
- Rotation Reversible
- Duty Continuous
- Mount 6 holes on face tapped M3
- Shaft 5.5mm x 15" w/flat
- Size 35mm dia. x 83mm
- Shpg. 1 lb.

30 RPM, 24 VDC Gearmotor



ITEM 5-1358 \$24.95

• New MULTI-PRODUCTS CO. INC. #2738. Offset gearbox.

SPECIFICATIONS

- RPM 30
- Duty continuous
- Voltage 24 DC
- Shaft 11 mm dia. x 12 mm
- Amps 0.68 no load w/ dual flats
- HP 1/45
- Mt. 4 bolt 2 1/2" x 2" pattern
- Torque 47 in. lbs.
- Size 4 1/2" x 3" x 4 3/4"
- Rotation reversible
- Shpg. 5 lbs.

45 RPM, 24 VDC Inline Gearmotor




ITEM 5-1660 \$9.95

• New, Molon Model CHM-2435-1. High torque output. 4 7/8" wheel with o-ring on edge to friction drive equipment. Use for drive wheel on robots. Operates at 1/2 speed on 12 VDC. Permanent magnet motor.

SPECIFICATIONS

- Speed 45 RPM
- Voltage 24 DC
- Amperage 0.28
- Torque 7.5 in.-lbs.
- Rotation reversible
- Duty continuous
- Mount 4 tapped holes 2 3/8" x 2 1/2"
- Shaft 5/16" dia.
- Size 2 3/4" x 2 1/4" x 3"
- Shpg. 1 1/2 lbs.

180 RPM, 24 VDC Gearmotor



ITEM 5-1812 \$8.95

• New, inline gearmotor. Die cast zinc gear housing. Will operate on 12 volts at reduced output speed.

SPECIFICATIONS

- Speed 180 RPM
- Voltage 24 DC
- Amperage 0.6 Amps
- Torque 2.5 in. - lbs.
- Rotation reversible
- Duty continuous
- Shaft 1/4" dia. x 5/8" w/dual flats and crosshole
- Shaft crosshole 1/8"
- Mount 4 bolt 1.25" x 1.56" centers
- Size 2 3/4" x 2 1/2" x 2 3/4"
- Shpg. 1 lb.

12 VDC, 5.9" Stroke Linear Actuator



ITEM 5-1833 \$129.95

• New DUFF NORTON model LT225-1-150. Limit switches at end of stroke

SPECIFICATIONS

- Stroke 150 mm (5.9")
- Voltage 12 DC
- Load rating 225 lbs. max.
- Extension speed No load 8 mm/sec Max load 6 mm/sec
- Amps 3.25 Full load
- Duty 25%
- Enclosure IP66
- Pin holes 1/4" dia.
- Retracted lgth. 10"
- Shaft dia. 20 mm (0.787")
- Size 10 3/4" x 1 1/2" x 3"
- Shpg. 3 lbs.

120 RPM, 22 VDC Inline Gearmotors



ITEM 5-1810 \$9.99

• New, IGARASHI permanent magnet inline gearmotor. Spur geartrain. Includes rubber boot over brushholders.

SPECIFICATIONS

- Speed 120 RPM-no load
- Voltage 22 DC
- Amperage 90 mA no-load
- Performance 70 RPM w/50 oz.in. torque, 500 mA
- Gear ratio 50
- Rotation reversible
- Duty continuous
- Mount 3 holes on face, M3 thread
- Shaft 5mm dia. x 7mm w/flat
- Size 1.3" dia. x 2.5"
- Shpg. 1 lb.

15 RPM, 24 VDC



ITEM 5-1451 \$4.95

• New CKD Model J209-056. DC synchronous motor attached to removable mtg. bracket.

SPECIFICATIONS

- RPM 15
- Voltage 24 DC
- Amps 0.2 no load
- Rotation CW
- Duty intermittent
- Shaft 3/16" diam. x 1/2" long w/flat
- Mount 2 bolt on 3 13/32" BC
- Size 4" x 1 3/4" x 2"
- Shpg. 1 lb.

152 RPM, 36 VDC Gearmotor



ITEM 5-1801 \$7.99

• New, MAXON A-max, very compact permanent magnet precision gearmotor. Will operate on 12-36 VDC.

SPECIFICATIONS

- Speed 152 RPM
- Voltage 36 DC
- Gear ratio 64.4:1
- Power consumption 5 watts
- Rotation reversible
- Duty continuous
- Mount three M2x1.5 holes, 17mm B.C.
- Shaft 2.7mm dia. x 4mm w/flat
- Size 1 9/16" dia. x 2"
- Shpg. 1/2 lb.

30 RPM, 50 VDC Gearmotor



ITEM 5-1687 \$89.95

• Used PARVALUX permanent magnet right angle gearmotor. Heavy duty construction.

SPECIFICATIONS

- Speed 30 RPM
- Voltage 50 DC
- Amperage 1.3 Amps
- Torque 62 in. - lbs.
- Gear ratio 96:1
- Rotation reversible
- Duty continuous
- Mount base
- Shaft 15 mm x 2" w/keyway
- Size 9" x 5" x 5 1/2"
- Shpg. 16 lbs.