

**5.25 ft lb Torque
Briggs & Stratton
Recoil
Start
Engine**



ITEM 28-116255
\$169.95

• Brand new, BRIGGS & STRATTON 525 series engine. Features include Dura-Bore cast iron cylinder sleeve, float carburetor for consistent easy starting, maintenance-free electronic ignition, low oil shutdown, overhead valves for cooler operation, Dual-Clean air cleaner, compression release for easy starting, engine mounted controls and TransportGuard fuel shut off to prevent fuel from diluting oil during transport. EPA compliant for all 50 states.

SPECIFICATIONS

- Model 097302-0016-F1
- Torque 5.25 ft.-lbs.
- Power 3.5 HP (Calculated)
- Disp. 12.51 cu. in (205 cc)
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Shaft 3/4" diam. x 2-27/64" w/ 3/16" keyway tapped 1/4-28
- Accessory Mount None
- Base Mount 6 3/8" x 3 1/8"
- Fuel Tank 3 qt.
- Size 13 1/2" x 8 1/2" x 13"
- Shpg. 32 lbs.

**9.5 ft. lb. Torque
Briggs & Stratton
Recoil Start
Engine**



ITEM 28-1928
\$199.95

• New, BRIGGS & STRATTON 950XR series engine. Features include Dura-Bore cast iron cylinder sleeve, electronic ignition, overhead valves, dual ball bearing forged crankshaft, Dual-Clean air cleaner, manual or remote throttle, manual choke. Low oil sensor, metal fuel tank. EPA compliant for all 50 states.

SPECIFICATIONS

- Model 130G32-0022-F1
- Engine Family FBSXS.2091HB
- Torque 9.5 ft.-lbs.
- Power (calculated) 6 HP at 3600 RPM
- Disp. 208 cc
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Shaft 3/4" diam. x 2 27/64" w/ keyway tapped 9/16"-24
- Accessory Mount 4 Bolt 3 5/8" B.C.
- Fuel Tank 3 qt.
- Size 11.3" x 14.4" x 14.9"
- Actual Weight 36 lbs.
- Dimensional Shpg. 48 lbs.

**7.5
Torque
Briggs & Stratton
Snowblower
Engine**



ITEM 28-1940

\$99.95

• New, Briggs & Stratton horizontal shaft engine. Snowblower applications, no air cleaner. Fixed speed governor. 60 watt AC alternator. Manual choke with primer bulb. Dual ball bearing crankshaft. Push/Pull keyswitch. Wire muffler guard. Steel fuel tank. Extended crankcase drain. Oversized hand grip for use with gloves.

SPECIFICATIONS

- Model 10D136-0007-F9
- Engine Family FBSXS.1631SC
- Displacement 163 cc
- Torque 7.5 ft.-lbs. @ 3600 RPM
- HP (calculated) 4.5 @ 3600 RPM
- Speed 3600 RPM
- Start Recoil
- Shaft 3/4" dia. x 3.93" w/ keyway, tapped 3/8"-24.
- Mount 4 hole, 6 3/8" x 3 1/8"
- Fuel Tank 3 quart
- Size 14 1/2" x 10 1/4" x 13 1/4"
- Actual Weight 35 lbs.
- Dimensional Shpg. 63 lbs.

**23 HP
Vanguard
Engine**



ITEM 28-1964
\$1499.95

• New, Briggs and Stratton Vanguard V-twin horizontal crankshaft engine. Supplied with fuel pump. No fuel tank. Pressurized lubrication system with oil filter and cooler. 20 amp alternator. Cast iron cylinder sleeve, low oil alert, float style carburetor. Keyswitch on front. Set up for remote manual choke. 5" round muffler with starter motor side outlet.

SPECIFICATIONS

- Model 386447-0084
- Power 23 HP
- Bore/Stroke 2.97" x 2.76"
- Displacement 627 cc.
- Speed 3600 RPM
- Start Electric w/recoil backup
- Shaft Horizontal
- Shaft 1" dia. x 2 29/32" w/ 1/4" keyway, tapped 3/8"-24
- Mount 7.68" x 4.02"
- Accessory Mount 5" B.C., 6.5" B.C., 7.75" B.C.
- Fuel Tank No
- Size 16.1" x 12.3" x 17.7"
- Shpg. 150 lbs.

**21 Torque
Briggs & Stratton
Engine**



ITEM 28-1962
\$299.95

• New BRIGGS & STRATTON horizontal crankshaft engine. Features cast iron cylinder sleeve, dual ball bearings. Manual choke and throttle. Steel muffler guard. Designed for remote air filter (not included). Low oil shutdown.

SPECIFICATIONS

- Model 25T232-0173-F1
- Torque 21 Ft.-lbs.
- Horsepower 14.4 HP calculated
- Disp. 420 cc.
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Shaft 1" dia. x 3 3/64" w/ 1/4" keyway, tapped 7/16"-24.
- Base Mount 7 5/8" x 4 1/2"
- Accessory Mount 6 1/2" bolt circle with 5 3/4" pilot
- Fuel Tank 6.6 liter
- Size 18" x 14 1/2" x 19"
- Actual Weight 73 lbs.
- Dimensional Shpg. 85 lbs.

**9 HP
Loncin
Engine**



ITEM 28-1963
\$219.95

• New, LONCIN single cylinder engine. Model G300FA. Built for use with KARCHER pressure washers. Low oil shutdown, cast iron cylinder sleeve. Muffler with guard.

SPECIFICATIONS

- Model G300FA
- Power 9 HP
- Disp. 302 cc
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Shaft 1" dia. x 3 3/32" w/ 1/4" keyway, tapped 7/16"-20
- Base Mount
- Accessory Mount
- Fuel Tank 5.5 liter
- Size 15" x 17" x 16 1/4"
- Shpg. 66 lbs.

Truck freight only.

**10 HP
Tecumseh
Engine**



ITEM 28-1741
\$139.95

• New, TECUMSEH horizontal engine built for driving electric generators. Cast iron sleeve, fixed speed governor. Low oil shutdown. Lighted on/off switch. Not for sale or use in California.

SPECIFICATIONS

- Model LH358XA-15493
- Power 10 HP
- Speed 3600 RPM
- Disp. 358 cc
- Start recoil
- Shaft horizontal
- No fuel tank
- Size 12" x 13 1/2" x 13"
- Shaft 1 1/8" dia. x 1 1/8", stepped to 7/8" dia. x 1 7/8" then tapered
- Overall length 4.33" tapped 5/16"-24 no keyway
- Mount 3 1/4" x 6 3/8"
- Accessory mount 4 bolt on 3 5/8" B.C.
- Shpg. 60 lbs.

**3/4" 2 Bolt Flange
Bearing**



ITEM 1-204-12-2-S
\$7.29

• Brand new, DURA-ROLL 200 series 2 bolt flange bearing. Stainless steel construction (304 SS housing, 440C SS bearing, SS grease zerk and flinger seal), with self-aligning ball bearing insert. Mobil FN222 food grade grease. Set screw on the inner race to lock shaft.

SPECIFICATIONS

- Bore 3/4"
- Bore Thru-Length 1.2"
- Bearing # SSUC204-12
- Housing # SSFL204
- Mount 3.56"
- Bolt Size 3/8"
- Overall Length 4.5"
- Shpg. 1.5 lbs.

**Hydrostatic
Transaxle**



ITEM 13-1607
\$269.95

• New Tuff Torq model K57R. Hydrostatic transaxle. Part #7A646084020. Vertical input for belt drive. Internal wet disc brake. Bypass lever allow vehicle to be moved without power.

SPECIFICATIONS

- Husqvarna Part 437814
- Input speed 3600 RPM max
- Max speed 5.5 mph
- Pump/Motor Displacement 7/10 cc
- Gear Ratio 23:1
- Axle Torque 150 ft.lbs.
- Max axle wt. 915 lbs.
- Input Direction CW
- Pulley 4 1/4" dia.
- Axles 3/4" diam. x 4 5/8" w/ keyway and snap ring groove
- Max Tire Size 23" dia.
- Recommended Oil 5W-50 Synthetic
- Three four-bolt mounts
- Inner mtg. centers: 1 3/4" x 13"
- Middle mtg. centers: 2 1/2" x 16 1/4"
- Outer mtg. centers: 2 1/2" x 17 1/4"
- Overall Size 29" x 15" x 10"
- Actual wt. 35 lbs.
- Shpg. 48 lbs.

5/8" Ball Bearing



ITEM 1-5456-58
\$1.99

• New, model 203KRR2 shielded ball bearing.

SPECIFICATIONS

- Bore 5/8"
- Outside Dia. 40mm
- Width 18.2mm
- Shpg. 1/4 lb.

See our complete selection of bearings on pages 122-125