




3 Bolt Mount

• New White Drive Products low speed high torque motors. Interchangeable with many different brands of similar type motors. Pictures are representative of motors. More information including pictures and additional specifications can be found on website.



2 Bolt Mount



4 Bolt Mount

Item	Model	Displ cu. In.	PS Cont.	Torque Cont.	RPM Cont.	GPM Cont.	Mount	Shaft	Ports	Shpg.	Price
9-8630-A	125008J05C3AAAAA	0.5	1450	97	1864	4	3-bolt round	5/8" keyed	SAE 6 End	7 lbs.	\$149.99
9-8630-B	125032JL5C3AAAAA	1.9	1450	354	622	5	3-bolt round	5/8" keyed	SAE 6	7 lbs.	\$149.99
9-12499-A	145032A11B1AAAAA	1.9	1450	372	1244	16	2-bolt SAE A	1" keyed	SAE 10	14 lbs.	\$119.95
9-8837-A	276040F3114AAAAA	2.5	2000	630	830	9	4-bolt square	1" tapered keyed threaded	SAE 10	18 lbs.	\$169.99
9-8831-D	155060F3153AAAAAC	3.6	2320	1106	1185	16	4-bolt square	1" w/crosshole	SAE 10	16 lbs.	\$129.99
9-8834-B	255060F3705AAAAA	3.6	2250	1221	890	14	4-bolt square	1" w/crosshole	Manifold	14 lbs.	\$149.99
9-12499-F	155060A17B1AAAAA	3.6	2320	1106	1185	16	2-bolt SAE A	1" keyed	Manifold	16 lbs.	\$129.95
9-8825	276070A1710AAAAA	4.3	2000	1120	650	12	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.99
9-12499-B	155100A17B1AAAAA	5.9	2320	1726	720	16	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.95
9-12499-J	155100A1102AAAAA	5.9	2320	1726	728	16	2-bolt SAE A	1" keyed	SAE 10	18 lbs.	\$129.95
9-12499-D	255100A1710AAAAA	6.1	3000	2122	610	16	2-bolt SAE A	1" keyed	Manifold	20 lbs.	\$129.95
9-8632-X	255130A1316BAAAA	7.9	2500	2797	472	16	2-bolt SAE A	25mm keyed	1/2" BSPP and Manifold	18 lbs.	\$119.99
9-8632-Y	255130A1901ABAAA	7.9	2500	2797	472	16	2-bolt SAE A	7/8" 13T spline	SAE 10	18 lbs.	\$119.99
9-8672-H	281130A6321BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	1/2" BSPP and Manifold	18 lbs.	\$139.99
9-8672-G	281130A6821BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	1/2" BSPP	16 lbs.	\$139.99
9-12499-C	155160A17B1AAAAA	9.4	2320	2840	452	16	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.95
9-8673	155200A6310BAAAA	11.6	2180	3365	367	16	2-bolt SAE A	1" keyed	1/2" BSPP and Manifold	18 lbs.	\$139.99
9-8632-CCC	255200A1001AAAAA	12.1	2500	4088	308	16	2-bolt SAE A	7/8" 13T spline	1/2" NPT	20 lbs.	\$149.99
9-8834-I	255200A1713AAAAA	12.1	2500	4088	308	16	2-bolt SAE A	1" keyed	1/2" BSPP and Manifold	20 lbs.	\$129.99

**2.13 cu in Hydraulic Piston Motor**



ITEM 9-12810  
**\$169.95**



• New, AUBURN GEAR model# A6VM-107DA1/63W-VZB027B hydraulic piston motor. Variable displacement axial piston motor. Pilot operated servo valve on motor controls speed. Crossover to Danfoss LC 35,15cc min.

**SPECIFICATIONS**

- Disp. Range 0.92-2.13 cu. in. / rev.
- Control Valve: Pilot operated
- Pilot Control Valve Pressure: 203-1000 PSI
- Motor Type: Piston
- Pressure : 2030 PSI Cont. 4350 PSI Max.
- Flow 33 GPM max.
- Power
- Torque

- Speed 5300 RPM max.
- Rotation Reversible
- Mount: 2 bolt on 155mm (6.1") bolt circle with 165mm (5.315") pilot
- Pilot Extension: 83mm (3.267")
- Shaft 1" dia. 15 tooth spline x 1.25" long
- Work Ports SAE 12
- Pilot Control Port SAE 6
- Case Drain SAE 4
- Size 1 1/2" x 7 1/2" x 13 1/4"
- Shpg. 36 lbs.

**6.5 cu in Hydraulic Piston Motor**

ITEM 9-12680  
**\$599.95**



• New, REXROTH model# A6VM-107DA1/63W-VZB027B hydraulic piston motor. Variable displacement bent axis piston motor for use in open and closed loop hydraulic systems. Pilot operated servo valve on motor controls speed and direction from 1.9 to 6.5 cu. in. per revolution.

**SPECIFICATIONS**

- Disp. Max. 6.5 cu. in. / rev.
- Disp. Pilot Control Valve Setting Range 1.9 cu. in. / rev. to 6.5 cu. in. / rev
- Control Valve Pilot operated
- Motor Type Piston
- Pressure 6000 PSI max.
- Pilot Control Valve Pressure 348 PSI
- Flow 100 GPM max.
- Power 339 HP @ 3550 RPM, 5800 PSI (calculated)
- Torque 502 ft-lbs. @ 3550 RPM, 5800 PSI

- Speed 3600 RPM max.
- Rotation Reversible
- Mount Four bolt on 200mm (7.874") bolt circle with 160mm (6.299") pilot
- Shaft 40mm dia. 18T spline, DIN 5480 W40x2x30x18x9g
- Ports Size 16 4 bolt flange 27.8mm (1.094") x 57.2mm (2.25") bolt centers w/25mm (1") port
- Control Ports M12x1.5 with GE-BLM steel line adapters
- Case Drain M18x1.5
- Size 11 1/2" x 7 1/2" x 13 1/4"
- Shpg. 165 lbs.

**10.0 cu in Hydraulic Motor**

ITEM 9-12687

**\$149.95**



• New. PARKER model TB0165F-S130AAAA hydraulic motor. Compact size. Shaft has groove for snap ring.

**SPECIFICATIONS**

- Disp. 10.0 cu. in. / rev.
- Motor Type: Geroler
- Pressure: 1800 PSI cont. 2250 PSI int.
- Torque: 2432 in-lbs. cont. 3062 in-lbs. int.
- Speed: 275 RPM cont.

- 343 RPM int.
- Flow: 12 GPM cont. 15 GPM int.
- Rotation Reversible
- Mount 4 bolt on 3.25" b.c.
- Shaft 1" dia. x 1.94" w/1/4" key
- Ports SAE 10
- Case Drain none
- Size 6 1/4" x 3 1/4" x 3 1/4"
- Shpg. 16 lbs.

**11.87 cu in Hydraulic Motor**

ITEM 9-7079-200-S  
**\$139.95**



• New. DYNAMIC BMRS series low speed high torque hydraulic motor.

**SPECIFICATIONS**

- Model BMRS200H2KS
- Displacement 11.87 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 2321 PSI cont. 2900 PSI int.
- Torque: 3186 in-lbs. cont. 3894 in-lbs. int.
- Speed:

- 310 RPM cont. 385 RPM int.
- Flow: 15.85 GPM cont. 19.81 GPM int.
- Mount 2 bolt SAE A
- Shaft 1" dia. x 1.84" long w/ 1/4" keyway, threaded 1/4"-20
- Ports SAE 8
- Case Drain None
- Size 6.85" x 5.17" x 3.81"
- Shpg. 22 lbs.

**13.91 cu in Hydraulic Motor**

ITEM 9-8974-I  
**\$189.95**



• New, DYNAMIC hydraulic motor.

**SPECIFICATIONS**

- Model BMER1230FSRWSR
- Disp. 13.91 cu. in. / rev.
- Pressure 2973 PSI (Cont.) 3481 PSI (Int.)
- Torque 5531 in-lb. (Cont.) 6284 in-lb. (Int.)
- Speed 290 RPM (Cont.)

- 365 RPM (Int.)
- Flow: 17.96 GPM (Cont.) 22.45 GPM (Int.)
- Rotation Reversible
- Mount Four-bolt magneto and two-bolt SAE A
- Shaft 1" dia. x 1.96" long shaft w/ 1/4" wide keyway
- Ports SAE 10
- Size 6 1/4" x 5 5/8" x 5 5/8"
- Shpg. 32 lbs.

**18.3 cu in Hydraulic Motor**

ITEM 9-8467-A

**\$199.95**



• New. WHITE DR series low speed high torque hydraulic motor.

**SPECIFICATIONS**

- Model 600300A8523AAAAA
- Displacement 18.3 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3000 PSI cont. 3500 PSI int.
- Torque: 7450 in-lbs. cont. 8600 in-lbs. int.
- Speed:

- 320 RPM cont. 380 RPM int.
- Flow: 25 GPM cont. 30 GPM int.
- Mount 4 bolt magneto on 4.18" bolt circle
- Shaft 1 1/4" dia. x 2.42" long, 14T splined, tapped 5/8"-18
- Ports SAE 10
- Case Drain SAE 4
- Size 6.74" x 5.35" x 5.41"
- Shpg. 41 lbs.