


HYDRAULIC WHEEL MOTORS.



5.4 cu in Hydraulic Motor

ITEM 9-8837-B
\$149.99

• New, WHITE DRIVE PRODUCTS hydraulic motor. Model 276090W3114AAEG

SPECIFICATIONS

- Motor Type Roller Stator
- Rotation Reversible
- Pressure: 2000 PSI cont. 2750 PSI cont.
- Torque: 1430 in-lbs. cont. 1985 in-lbs. int.
- Speed: 520 RPM cont. 650 RPM int.
- Flow: 12 GPM cont. 15 GPM int.
- Mount Four-bolt wheel
- Shaft 1" tapered x 2³/₁₆" shaft w/ 1/4" key and threaded end w/ castle nut
- Ports SAE 10 Side Ports, Aligned
- Case Drain None
- Size 4.53" x 4⁷/₈" x 4⁷/₈"
- Shpg. 20 lbs.



14.5 cu in Hydraulic Motor

ITEM 9-12507

\$269.95

• New, PARKER PF (DF) series hydraulic wheel mount motor with removable four bolt wheel hub and parking brake. Parking brake lever attaches to the left side of brake actuator plate facing wheel hub. Model number PF0240ASA00AAK

SPECIFICATIONS

- Brand Parker
- Family PF (DF) series
- Displacement 14.5 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 2000 PSI cont. 3000 PSI int.
- Torque: 3782 in-lbs. cont. 5928 in-lbs. int.
- Speed: 394 RPM cont.
- Flow: 20 GPM cont. 25 GPM int.
- Mount 4 bolt wheel mount with 1/2" holes on 5.812 b.c.
- Wheel Hub Mount Four, 1/2"-20 bolts on 4" b.c.
- Shaft 1 1/4" tapered x 4.21" long with 5/16" keyway, threaded 1"-20
- Ports SAE 10
- Case Drain None
- Size 6.23" x 5.18" x 5.18"
- Shpg. 44 lbs.

ITEM 9-12509

\$269.95

Same as 9-12507 above except right side brake. Model number PF0240CSA00AAK



29.1 cu in Hydraulic Motor

ITEM 9-12508

\$279.95

• New, PARKER TF series hydraulic wheel mount motor.

SPECIFICATIONS

- Brand Parker
- Model TF0475US081AALU
- Family TF series
- Displacement 29.1 cu. in. / rev.
- Motor Type Gerotor
- Pressure: 1645 PSI cont. 2000 PSI int.
- Torque: 6027 in-lbs. cont. 7528 in-lbs. int.
- Speed: 195 RPM int.
- Flow: 20 GPM cont. 25 GPM int.
- Mount 4 bolt wheel mount with 1/2" holes on 5.812" b.c.
- Shaft 1 1/4" tapered x 4.21" long with 5/16" keyway, threaded 1"-20
- Ports SAE 10
- Case Drain None
- Size 8.5" x 5.27" x 5.27"
- Shpg. 46 lbs.



5 Bolt Wheel Hub

ITEM 1-1726

\$47.20

• Brand new, machined cast iron hub for use in drive wheel applications. Mounts on 1 1/4" tapered keyed shaft.

SPECIFICATIONS

- Bolt holes tapped 1/2"-20
- 1 1/4" I.D. hub tapers 1 1/2" per ft.
- 5/16" wide hub keyway
- 2 1/2" dia. wheel pilot
- Size 5 3/8" dia. x 1 1/2" thick
- Shpg. 6 lb.

1.53 cu in Hydraulic Motor

ITEM 9-8915

\$129.95

• New, SALAMI model# 2,5MB25R-R55S3-MOTOR hydraulic motor. Aluminum body.

SPECIFICATIONS

- Displacement 1.53 cu. in. / rev.
- Motor Type Gear
- Rotation Reversible
- Pressure: 3625 PSI cont. 4060 PSI int.
- Torque: 883 in-lbs. @ 3625 PSI 989 in-lbs. @ 4060 PSI
- Speed: 3000 RPM max.
- Flow: 500 RPM min. 24 GPM @ 3625 RPM 26.9 GPM @ 4060 RPM
- Mount Two-bolt SAE B
- Shaft 7/8" dia. x 1 1/8" long 13T spine
- Inlet Port SAE 16
- Outlet Port SAE 12
- Case Drain SAE 4
- Size 4 3/4" x 6 7/8" x 5 1/2"
- Shpg. 11 lbs.



4.45 cu in Hydraulic Motor

ITEM 9-12235-B

\$104.95

• New. Low speed high torque motor that incorporates an industry proven spool valve design and high performance gerotor power element.

SPECIFICATIONS

- Brand Brevini
- Model FH0073AS100AAAA
- Family FH Series
- Displacement 4.45 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 1900 PSI cont. 2400 PSI int.
- Torque: 1020 in-lbs. cont. 1332 in-lbs. int.
- Speed: 820 RPM cont. 1025 RPM int.
- Flow: 15 GPM cont. 20 GPM int.
- Mount 2 bolt SAE A
- Pilot Mount Size 3.25"
- Shaft 1" dia. x 1.89" long w/ 1/4" keyway
- Ports SAE 10
- Case Drain None
- Size 5.42" x 5.10" x 3.81"
- Shpg. 15 lbs.



6.1 cu in Hydraulic Motor

ITEM 9-12500

\$189.95

• New, EXTREME low speed high torque hydraulic motor.

SPECIFICATIONS

- Brand Extreme
- Model EXT-M598WMB
- Displacement 6.1 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3045 PSI cont. 4350 PSI int.
- Torque: 2564 in-lbs. cont. 3359 in-lbs. int.
- Speed: 742 RPM cont. 924 RPM int.
- Flow: 20 GPM cont. 25 GPM int.
- Mount 4 bolt magneto
- Shaft 1 1/4" dia. x 2.08" long 14T splined, tapped 3/8"-16
- Ports SAE 10
- Case Drain None
- Size 7.75" x 5.34" x 3.75"
- Shpg. 27 lbs.



9.7 cu in Hydraulic Motor

ITEM 9-12501

\$199.95

• New, EXTREME low speed high torque hydraulic motor.

SPECIFICATIONS

- Brand Extreme
- Model EXT-M561WNB
- Displacement 9.65 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3045 PSI cont. 3770 PSI int.
- Torque: 4058 in-lbs. cont. 4685 in-lbs. int.
- Speed: 460 RPM cont. 713 RPM int.
- Flow: 20 GPM cont. 30 GPM int.
- Mount 4 bolt magneto
- Shaft 1 1/4" dia. x 2.08" long 14T splined, tapped 3/8"-16
- Ports SAE 10
- Case Drain None
- Size 7.25" x 5.34" x 3.75"
- Shpg. 25 lbs.

12.2 cu. in. Hydraulic Motor

ITEM 9-7567

\$148.95

• New, BUCHER Hydraulics Model BRGL200A18.

SPECIFICATIONS

- Displ. 12.2 cu. in. / rev.
- Motor type gerotor
- PSI 2000 cont., 2750 int.
- Torque 3350 in-lbs. cont., 4650 in-lbs. int.
- RPM 220 cont., 280 int.
- GPM 12 cont., 15 int.
- Rotation reversible
- Mount 2 bolt SAE A
- Shaft 25 mm dia. x 1 1/8" keyed
- Ports 1/2" BSPP
- Size 7 3/8" x 5 1/4" x 4"
- Shpg. 21 lbs.



12.3 cu in Hydraulic Motor

ITEM 9-114092

\$299.95

• New, DANFOSS TMK series hydraulic motor. Model 151F6131.

SPECIFICATIONS

- Displacement 12.3 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3625 PSI cont. 4715 PSI int.
- Torque: 6370 in-lbs. cont. 8000 in-lbs. int.
- Speed: 400 RPM cont. 500 RPM int.
- Flow: 21.1 GPM cont. 26.4 GPM int.
- Mount 4 Bolt SAE C (6 3/8" bolt circle)
- Pilot 5" dia.
- Shaft 1.25" dia. x 2.10" long w/ 5/16" keyway, tapped 3/8"-16
- Ports SAE 12 (1 1/8"-12 ORB)
- Case Drain SAE 4 (7/16"-20 ORB)
- Size 5 3/4" x 5 3/4" x 8 1/4"
- Shpg. 39 lbs.



12.4 cu. in. Hydraulic Motor

ITEM 9-9324

\$149.95

• New BUCHER HYDRAULICS BREL200-A38-10-E0G hydraulic motor. SAE A or magneto mount. Built-in relief valve.

SPECIFICATIONS

- Disp. 12.4 cu. in. / rev.
- Motor Type Gerotor
- Pressure: 3000 PSI cont. 3500 PSI int.
- Torque: 4800 in-lbs. cont. 5600 in-lbs. int.
- Speed: 300 RPM cont. 370 RPM int.
- Flow: 18 GPM cont. 22 GPM int.
- Relief Valve 1500 PSI (Adjustable)
- Rotation Reversible
- Mount 2 bolt SAE A or Magneto
- Shaft 1" dia. x 1.97" keyed
- Ports 1/2" BSPP
- Case Drain None
- Size 6 1/2" x 5 1/4" x 7"
- Shpg. 28 lbs.

