




2 HP Air Compressor Motor



ITEM 4-1955
\$129.95

• New, twin cylinder single stage air compressor. Aluminum crankcase with cast iron cylinder. Oil level sight glass. Embedded air filter. Uni-Electric motor supplied with pulley. V-belt not included. Ships in one box. **Shpg 52 lbs.**

COMPRESSOR SPECIFICATIONS

- Cylinders 2
- Stages Single
- Displacement 7.6 CFM
- Pressure 145 PSI max.
- Power Req'd. 2 HP max.

- Speed 920 RPM max.
- Rotation CCW
- Flywheel 11" A belt
- Port 3/4 BSPP
- Mount 5 1/2" x 6 1/4"
- Size 10" x 11" x 11"

MOTOR

SPECIFICATIONS

- Power 2 HP
- Voltage 230 VAC 50 Hz
- Amperage 7.3 Amps
- Speed 2700 RPM

115 Volt AC Air Pump



ITEM 4-1951
\$39.95

• New, HAILEA model AC0110 air pump. Use for large or multiple aquariums. Finned aluminum housing. Linear piston design for long life, low noise and vibration. Oilfree air. Optional 13mm barbed inlet port to allow remote intake.

SPECIFICATIONS

- Voltage 115 AC
- Power Consumption 160 watts
- Flow 145 Liters/Min. open flow
- Pressure 5 PSI

- Noise Level <60 db
- Duty Continuous
- Port 3/8" ID barb
- Mount Rubber cushion feet
- Size 11 1/4" 5" x 6 5/8"
- **Shpg. 13 lbs.**

10 Gallon Wheelbarrow Air Tank



ITEM 4-9070
\$119.95

• New. Wheelbarrow style steel twin tank with powder-coated exterior. Compressor mounting plate with various patterns. Originally designed for use with a 5.5 HP Honda engine. Handle tubing 1" dia. Does not include wheel, hand grips, rubber feet. Use with 10" dia. wheel and 5/8" x 4 1/2" axle. Left side of mounting plate is angled and has holes for gauges, regulators, etc.

SPECIFICATIONS

- Capacity 10 gallons
- Pressure 175 PSI max.
- Inlet Port 1/2" NPT
- Right side tank 1/4" NPT
- Left side tank Two 1/4" NPT, One x 1/2" NPT
- Drain Ports 1/4" NPT each tank
- Tank size 6" dia. x 39 3/4" (each)
- Tank Material 14 gauge steel

- Mounting plate 28" x 9"
- Compressor Mounting holes 3 sets: 6 7/8" x 3 5/8", 8 3/8" x 4 5/8", 8 3/8" x 5 1/2"
- Motor Mounting Slots 3" wide for 56 frame electric motor 3 1/4" wide for gas engine
- Overall Size 44" x 18" x 12"
- Actual weight 70 lbs.
- **Shpg. 87 lbs. (oversize)**

60 Gallon Vertical Air Tank



ITEM 4-1944
\$249.95

• Air tank is from a warranty store return from a complete air compressor with a motor or compressor issue. Vertical steel tank with black exterior paint. Mount on top with holes for compressor and holes for motor. Certified by Twin Lakes Tanks.

SPECIFICATIONS

- Capacity 60 gallons
- Pressure 175 PSI max.
- Gauge Port 1/4" NPT
- Compressor Port 1/2" NPT
- Outlet Port 3/4" NPT
- Drain Port 1/4" NPT
- Tank size 20.25" dia. x 47.5"
- **Shpg. 170 lbs.**

- Mounting plate 17" x 8"
- Compressor Mounting Holes
- 6.625" x 5.875"
- Motor Mounting Holes
- 4.875" x 3"
- Overall Size 23" x 22" x 54"

Truck freight only.

7.5 CFM, Single Stage Air Compressor



ITEM 4-1916
\$149.95

• New, V-twin cylinder single stage air compressor. Cast iron block and cylinder with aluminum head. Oil level sight glass.

SPECIFICATIONS

- One stage, two cylinders
- Flow 7.5 CFM open flow 4.28 CFM at 110 PSI
- Pressure 115 PSI max.
- Power req'd. 2 HP max.
- Speed 980 RPM max.
- Rotation CCW
- Flywheel 10 1/2" A belt
- Port 1/2" OD tube
- 1st stage bore/stroke 55mm x 45mm
- Mount 6 7/8" x 3 3/8"
- Size 13" x 10 1/2" x 10 1/2"
- **Shpg. 37 lbs.**

6 CFM, Single Stage Air Compressor



ITEM 4-1917
\$179.95

• New, twin cylinder single stage air compressor. Cast iron cylinder with aluminum block and head. Oil level sight glass. Embedded air filter.

SPECIFICATIONS

- One stage, two cylinders
- Flow 6 CFM open flow 3.7 CFM at 110 PSI
- Pressure 115 PSI max.
- Power req'd. 2 HP max.
- Speed 1030 RPM max.
- Rotation CCW
- Flywheel 10 1/2" A belt
- Port 1/2" OD tube
- Bore/Stroke 55mm x 35mm
- Mount 5" x 4 1/4"
- Size 11 3/4" x 10 1/2" x 11"
- **Shpg. 25 lbs.**

2 HP Air Compressor



ITEM 4-1950
\$119.95

• New, POWERPRO model 22060 single cylinder compressor. Compact portable unit. Complete with pressure regulator, gauges, line cord and carrying handle. Manual on/off control on pressure switch. Compressor uses splash lubrication with furnished oil. Ball valve to shut off output port.

SPECIFICATIONS

- Horsepower 2
- Voltage 120 AC
- Amps 14.1
- Tank 6 gallon
- Port 1/4" NPT male
- Pressure 145 PSI max.
- Pressure switch setting
- Cut-out 125 PSI
- Cut-in 85 PSI
- Air Flow 4.2 CFM @ 40 PSI 3.2 CFM @ 90 PSI
- Size 23" x 12" x 23"
- **Shpg. 63 lbs.**

43.5 CFM, Two Stage Air Compressor



ITEM 4-1920
\$699.95

• New, four cylinder V-twin two stage air compressor. All cast iron construction. Oil level sight glass. Automotive style air filters. Safety valves on all coolers.

SPECIFICATIONS

- Two stage, four cylinders
- Flow 43.5 CFM open flow 21.6 CFM at 110 PSI
- Pressure 180 PSI max.
- Power req'd. 10 HP max.
- Speed 860 RPM max.
- Rotation CCW
- Flywheel 19" two groove B belt
- Port 3/4" ID tube fitting
- Bore/Stroke 105mm-55mm x 89mm
- Mount 9" x 9 1/2"
- Size 18" x 27" x 19"
- **Shpg. 270 lbs.**

Truck freight only.

38.2 CFM Two Stage Air Compressor



ITEM 4-1934
\$495.95

• New, Fini model BK120. Two cylinder two stage belt drive compressor. Aluminum head and crankcase. Oil sight gauge.

SPECIFICATIONS

- Cylinders Two
- Stages Two
- Pressure 145 PSI max.
- Flow @1100 RPM (10 HP)
- 38.2 CFM open flow
- 31.8 CFM @ 200 PSI
- Rotation CCW
- Flywheel 19 3/4" dia. Dual 5/8" groove
- Port 1" NPT
- Mount 6 1/2" x 9"
- Size 19 3/4" x 15" x 20"
- **Shpg. 160 lbs.**

Truck freight only.

Mobile Air Tanks

• Brand new. Steel tank with black powder-coated exterior and rust preventative sprayed inside. D.O.T. approved. Round body with mounting brackets on both ends for easy installation. One 3/8" NPT port in each end, under the mounting bracket.

SPECIFICATIONS

- 150 PSI max.
- Four bolt mount
- Two 3/8" NPT ports; one 3/4" NPT port; one 1/4" NPT port



ITEM	Capacity	Mount Centers	Size	Shpg.	Price
4-1754	6.44 gallon	2 1/4" x 27 1/2" ctrs.	9 5/8" O.D. x 29" long	25 lbs.	\$51.95
4-1755	12.40 gallon	2 1/4" x 29 1/2" ctrs.	12 1/4" O.D. x 31" long	40 lbs.	\$73.95