



Premium Efficiency Three Phase Motors

• Brand new LEESON premium efficiency motors. Meets or exceeds NEMA premium efficiency standards. Cast iron frame and base. No overload protection. Available as base mount only or as face & base mount. Keyed shafts. All motors over 150 lbs. ship truck freight only. All motors are 1800 RPM.



SPECIFICATIONS FOR ALL

- Voltage 208-230/460 VAC
- Electrically reversible
- Continuous duty
- Service factor 1.15
- Enclosure TEFC
- Ball bearings

Base Mount							Face & Base Mount						
ITEM	Model	HP	Amps	Frame	Shpg.	Price	ITEM	Model	HP	Amps	Frame	Shpg.	Price
10-2721	171640	1	3.2/1.6	145T	50 lbs.	\$415.90	10-2734	LM32822	1	3.8/1.9	145TC	47 lbs.	\$322.90
10-2722	171646	1½	4.8/2.4	145T	54 lbs.	\$365.50	10-2735	121180	1½	4.8/2.4	145TC	37 lbs.	\$260.05
10-2723	171647.6	2	6/3	145T	58 lbs.	\$407.35	10-2736	LM32829	2	5.8/2.9	145TC	43 lbs.	\$339.85
*10-2724	182TTFC6026	3	8.0/4.0	182T	104 lbs.	\$358.95	10-2737	182TTFBD6028	3	8/4	182TC	104 lbs.	\$320.95
*10-2725	184TTFC6026	5	12.8/6.4	184T	109 lbs.	\$410.95	*10-2738	184TTFBD6028	5	13.0/6.5	184TC	109 lbs.	\$375.95
*10-2726	213TTFC6026	7½	19.0/9.5	213T	205 lbs.	\$707.85	*10-2739	213TTFBD6028	7½	19.0/9.5	213TC	205 lbs.	\$746.35
Motors below Drop Ship Freight FREE in lower 48 states.													
10-2727	215TTFC6026	10	25/12.5	215T	227 lbs.	\$652.95	10-2740	215TTFBD6028	10	25/12.5	215TC	217 lbs.	\$537.95
10-2728	254TTFC6026	15	36/18	254T	330 lbs.	\$781.95	10-2741	254TTFBD6028	15	36/18	254TC	340 lbs.	\$783.95
10-2729	256TTFC6026	20	49/24.5	256T	372 lbs.	\$942.95	10-2742	256TTFBD6028	20	49/24.5	256TC	382 lbs.	\$980.95
*10-2730	284TTFC6026	25	61.0/30.5	284T	435 lbs.	\$1211.95	10-2743	284TTFBD6028	25	59/29.5	284TC	445 lbs.	\$1268.95
10-2731	286TTFC6026	30	70/35	286T	482 lbs.	\$1286.95	*10-2744	286TTFBD6028	30	72.5/36.5	286TC	482 lbs.	\$1333.95
10-2732	324TTFC6026	40	92/46	324T	578 lbs.	\$1621.95	*10-2745	324TTFBD6028	40	95/47.5	324TC	646 lbs.	\$1659.95
10-2733	326TTFC6026	50	117/58.5	326T	637 lbs.	\$1977.95	10-2746	326TTFBD6028	50	117/58.5	326TC	647 lbs.	\$2072.95
10-2817	364TTFC6036	60	139/69.5	364T	900 lbs.	\$2695.95	Motor Frame and Shaft Size	Base Mount	Face Mount	Shaft			
10-2818	365TTFC6036	75	171/85	365T	1030 lbs.	\$2862.95		56	56C	5/8" dia. x 1 7/8", 3/16" keyway			
10-2819	405TTFC6036	100	225/112.5	405T	1070 lbs.	\$3407.95		145T	145TC	7/8" dia. x 2 1/4", 3/16" keyway			
10-2820**	444TTFC6036	125	137.5	444T	1580 lbs.	\$4893.95		182T, 184T	182TC, 184TC	1 1/8" dia. x 2 3/4", 5/16" keyway			
10-2821**	445TTFC6036	150	163	445T	1630 lbs.	\$5478.95		213T, 215T	213TC, 215TC	1 3/8" dia. x 3 3/8", 5/16" keyway			
10-2822**	447TTFC6038	200	219	447T	2790 lbs.	\$6260.95		254T, 256T	254TC, 256TC	1 5/8" dia. x 4", 3/8" keyway			
10-2823**	171516.60	250	275	449T	2550 lbs.	\$14483.95		284T, 286T	284TC, 286TC	1 7/8" dia. x 4 5/8", 1/2" keyway			
10-2824**	171529.60	300	330	449T	2560 lbs.	\$16385.95		324T, 326T	324TC, 326TC	2 1/8" dia. x 5 1/4", 1/2" keyway			
**460 VAC Only *Marathon							364T, 365T		2 3/8" dia. x 5 7/8", 5/8" keyway				
							405T, 444T		2 7/8" dia. x 7", 3/4" keyway				
							445T, 447T, 449T		3 3/8" dia. x 8 1/2", 7/8" keyway				



50 HP, 460 VAC Motor

ITEM 10-3046

\$1395.95

• New, GENERAL ELECTRIC Model 5K5405SL229.

SPECIFICATIONS

- Power 50 HP
- Voltage 460 AC
- Amperage 56 Amps
- Speed 1785
- Rotation reversible
- Phase 3
- Service factor 1.15
- Bearings ball
- Enclosure TENV
- Duty continuous
- Frame 405TZ
- Mount rigid base
- Shaft 2 1/8" dia. x 5 7/8" with 1/2" keyway
- Size 31" x 26" x 20"
- Shpg. 1040 lbs.

Truck freight only.

Electric Motor Slide Mounts

• Brand new, WORLDWIDE ELECTRIC T-frame motor slide base. Use to mount NEMA standard electric motor. Simplifies alignment and positioning, ideal for tensioning belts. Steel construction with baked-on primer. Washers included.



Find dimensional specifications and drawings for these items online.



100 RPM 230 VAC Gearmotor

ITEM 5-1909

\$109.95

• New, BODINE model#34Y68VFYP-Z2 parallel-shaft gearmotor.

SPECIFICATIONS

- Speed 100 RPM
- Horsepower 1/8
- Voltage 230 VAC, 60 Hz
- Amperage 1.4 Amps
- Torque 35 lb. in.
- Ratio 16:1
- Rotation Reversible
- Duty Continuous
- Enclosure TEAO
- Mount Four 10-32. holes on 3 3/4" bolt circle
- Shaft 1/2" dia. x 1 1/4" long w/ 3/16" keyway & flat
- Size 8 1/4" x 4" x 6"
- Shpg. 14 lbs.

ITEM	Compatible				Foot Print	Shpg.	Price
	Motor Frame Size	Slide Length	Adjusting Screw	Base Mount Centers			
10-2431-56	56	3"	1	7 5/8" x 5 3/4"	10 5/8" x 6 1/2"	5 lbs.	\$12.70
10-2431-143T	143	3"	1	7 1/2" x 6 3/4"	10 1/2" x 7 1/2"	8 lbs.	\$24.40
10-2431-145T	145	3"	1	7 1/2" x 7 3/4"	10 1/2" x 8 1/2"	9 lbs.	\$24.40
10-2431-182T	182	3"	2	9" x 8 1/2"	12 3/4" x 9 1/2"	13 lbs.	\$33.25
10-2431-184T	184	3"	2	9" x 9 1/2"	12 3/4" x 10 1/2"	13 lbs.	\$33.25
10-2431-213T	213	3 1/2"	2	10 1/2" x 9 1/2"	15" x 11"	18 lbs.	\$49.40
10-2431-215T	215	3 1/2"	2	10 1/2" x 11"	15" x 12 1/2"	20 lbs.	\$49.40
10-2431-254T	254	4"	2	12 1/2" x 13 1/4"	17 3/4" x 15 1/8"	22 lbs.	\$67.30
10-2431-256T	256	4"	2	12 1/2" x 15"	17 3/4" x 16 7/8"	23 lbs.	\$67.30
10-2431-284T	284	4 1/2"	2	14" x 15"	19 3/4" x 16 7/8"	27 lbs.	\$75.70
10-2431-286T	286	4 1/2"	2	14" x 16 1/2"	19 3/4" x 18 3/8"	28 lbs.	\$75.70
10-2431-324T	324	5 1/4"	2	16" x 17"	22 3/4" x 19 1/4"	38 lbs.	\$110.15
10-2431-326T	326	5 1/4"	2	16" x 18 1/2"	22 3/4" x 20 3/4"	39 lbs.	\$110.15