



**5 HP, 230 VAC  
Motors**

• Brand new, LEESON. General purpose heavy duty motors for air compressors, pumps. No thermal overload.

**SPECIFICATIONS FOR BOTH**

- Power 5 HP
- Voltage 208-230 AC
- Rotation reversible
- Phase 1
- Service factor 1.15
- Bearings ball
- Enclosure ODP
- Duty continuous
- Frame 184T
- Mount rigid welded base
- Shaft 1 1/8" dia. x 2 3/4" w/ 1/4" keyway

**\$628.25**

**ITEM 10-1435  
SPECIFICATIONS**

- Model 131537
- Speed 1740 RPM
- Amperage 23-21 amps
- Size 12 1/2" x 10 3/4" x 8"
- Shpg. 90 lbs.

**ITEM 10-2753  
SPECIFICATIONS**

- Model 131616
- Speed 3600 RPM
- Amperage 24-22 amps
- Size 12 1/4" x 11" x 11 1/4"
- Shpg. 87 lbs.



**5 HP  
208-230 VAC  
Compressor  
Duty Motor  
\$260.90**

**ITEM 10-2530**  
• Brand new, LEESON ELECTRIC Model 116523 motor. Special duty motor designed to replace motors on compressors. Motor is rated for a breakdown torque of 5 HP and a continuous compressor duty at 3 HP. Overload protection with manual reset. Steel frame and base. Welded base. Capacitor start/capacitor run.

• Confirm your motor name plate data tag including voltage, amperage, speed, frame and shaft diameter to match this motor specifications for proper operation.

**SPECIFICATIONS**

- 5 HP Definite Purpose Special Compressor Duty
- Voltage 208-230 VAC
- Amperage 15 Amps
- Speed 3450 RPM
- Phase 1
- Rotation Reversible
- Service factor 1.0
- Bearings Ball
- Enclosure ODP
- Cont. compressor duty
- Frame 56H
- Mount base
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 9 1/4" x 7" x 8"
- Shpg. 38 lbs.



**3/4 HP 3600 RPM  
115/230 Volt  
AC Motor  
\$49.95**

**ITEM 10-3129**  
• New, Century Electric model# C48AB86A03.

**SPECIFICATIONS**

- Power 3/4 HP
- Voltage 110/220 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 10/5 Amps no load
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1
- Bearings Ball
- Thermal Overload
- Protection Automatic
- Enclosure ODP
- Duty Continuous
- Frame 48Y
- Face Mount
- Shaft 5/8" dia. x 1 5/8" smooth then threaded 1/2"-20 x 3/4" (2-1/8" overall length)
- Size 11 1/4" x 6 1/2" x 6 1/2"
- Shpg. 20 lbs.



**Leeson Farm Duty Motors**

• Brand new LEESON heavy duty motors. High starting torque. Totally enclosed fan cooled for outdoor use. Capacitor start. Manual reset thermal overload protection. Cont. duty, reversible rotation, rigid mount. Single phase.

ITEM	HP	Voltage	Amps	RPM	Frame	Shaft	Shpg.	Price
10-1024	1/2	115/230	8.8/4.4	1725	56	5/8"	25 lbs.	\$220.75
10-1025	3/4	115/230	10.8/5.4	1725	56	5/8"	28 lbs.	\$266.00
10-1026	1	115/230	14/7	1725	56	5/8"	32 lbs.	\$299.35
10-1027	1 1/2	115/230	17.2/8.6	1725	56	5/8"	41 lbs.	\$362.95
10-1028	2	230	9.2	1725	56Hz	7/8"	48 lbs.	\$416.05
10-1029	3	230	19	1740	184T	1 1/8"	99 lbs.	\$600.00
10-1323	5	230	23	1740	184T	1 1/8"	106 lbs.	\$740.60
10-1324	7 1/2	230	33.6	1740	215T	1 3/8"	165 lbs.	\$991.75
10-1325	10	230	40	1740	215T	1 3/8"	197 lbs.	\$1231.20



**Crop Dryer Motors**

• Brand new LEESON crop dryer motors. For use in air over and fan shaft design. Thermostats provide thermal overload protection. Steel housing. Grey epoxy painted. Double sealed ball bearings. Motor venting protected against insects and rodents. End of shaft tapped 1/4"-20. Capacitor start and run motor. Capacitor shipped loose.

**SPECIFICATIONS**

- Voltage 230 VAC
- Ball Bearings
- Speed 3450 RPM
- Continuous Duty
- Rotation Reversible
- Base Mount
- Phase 1
- SF 1.0



• UDP

ITEM	HP	Amps	Frame	Shaft	Shpg.	Price
10-2896	3-4.5	13-19	145TZ	7/8" dia. x 2 1/4"	50 lbs.	\$516.05
10-2766	5-7.5	27.2-35	182TZ	1 1/8" dia. x 3 1/2"	94 lbs.	\$599.60
10-2767	7.5-10	31-42	182TZ	1 1/8" dia. x 3 1/2"	98 lbs.	\$715.10
10-2768	10-15	39.5-61.5	213TZ	1 1/8" dia. x 4 1/2"	195 lbs.	\$917.25



**1/4 HP 208/230 Volt  
AC 2 Speed Motor  
\$19.99**

**ITEM 10-1654**

• New AO Smith Dual Shaft Motor. Ideal replacement for blowers and fans. Air over continuous duty. Requires capacitor (not included).

**SPECIFICATIONS**

- 1/4 HP
- 208/230 Volt AC
- 1.5 amps
- 1050/925 RPM, 2 speed
- CCW Rotation
- Single Phase
- 1.0 service factor
- Open enclosure
- Cont. duty
- Shaft 1/2" dia x 1 5/8"
- Shaft 1/2" dia x 2 1/4"
- Requires 5 mfd capacitor
- 5 1/2" dia x 4"
- Shpg 11 lbs



**1/3 HP  
1625 RPM  
115 VAC  
Instant  
Reversing  
Motor  
\$209.95**

**ITEM 10-2779**

• New, LEESON model M4P17DJ21A instant reversing electric motor. Specially designed for use on "instant-reversing" parking gates, doors, slide gates or other moderate starting torque instant reversing applications. Capable of frequent reversing service. Instant "plug-reversing" with simple three wire connection. Capacitor start induction run with solid state, instant reversing switch. Manual overload protection.

**SPECIFICATIONS**

- Power 1/3 HP
- Voltage 115 AC
- Amperage 4 Amps
- Speed 1625 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure ODP
- Duty 60 min.
- Frame JS56
- Base Mount Four 0.33" on 3" x 4 7/8" to 5 5/8" centers
- Shaft 5/8" dia. X 2" w/ 3/16" keyway
- Size 8 1/4" x 5 7/8" x 8 5/8"
- Shpg. 23 lbs.



**1/2 HP 1800 RPM  
230 Volt AC Motor  
\$109.95**

**ITEM 10-2807**

• New, MARATHON model 5KH-39QN9518BX base mount electric motor. Automatic thermal overload protection.

**SPECIFICATIONS**

- Power 1/2 HP
- Voltage 230 AC
- Amperage 4.2 Amps
- Speed 1725 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Mount Base 4 slots on 5" x 3" centers
- Shaft 5/8" dia. x 1 7/8" w/ 3/16" keyway
- Size 8 1/4" x 6 1/2" x 6 3/4"
- Shpg. 18 lbs.