

3/4 HP Electric Motor

ITEM 10-3126
\$49.95

• New, AO Smith Electric model# J218-1006.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 12.5/3 Amps
- Speed 3600 RPM
- Rotation CCW
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 12mm dia. tapered x 3/4" long with M10-1.0 threaded end
- Size 12" x 8" x 8"
- Shpg. 23 lbs.



3/4 HP Electric Motor

ITEM 10-3128
\$49.99

• New, AO Smith Electric model# J218-590B.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1.25
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 10 1/2" x 6 1/2" x 6 1/2"
- Shpg. 22 lbs.



1 HP Electric Motor

ITEM 10-3130
\$54.95

• New, AO Smith Electric model# J218-596B

SPECIFICATIONS

- Power 1 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 14.5/7.25 Amps
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1.3
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 11 1/4" x 6 1/2" x 6 1/2"
- Shpg. 25 lbs.



1/2 HP Electric Motor

ITEM 10-3127
\$49.99

• New, AO Smith Electric model# J218-582A-LS.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3450 RPM
- Rotation CCW
- Service Factor 1.3
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 12" x 6 1/2" x 6 1/2"
- Shpg. 17 lbs.



3/4 HP 1725 RPM 115 Volt AC Leeson Electric Motor

ITEM 10-3204
\$129.95

• Brand new, Leeson Electric model# C6S17DB9A.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115 Volt AC
- Phase 1
- Frequency 60 Hz
- Amperage 10.6 Amps
- Speed 1725 RPM
- Rotation CCW
- Service Factor 1.15
- Bearings Ball
- Thermal Overload Protection None
- Enclosure DP
- Duty Continuous
- Frame 56
- Base Mount
- Shaft 5/8" dia. x 1 7/8" overall length keyed
- Size 8 3/8" x 6 1/2" x 6 5/8"
- Shpg. 24 lbs.



3/4 HP 3450 RPM Jet Motor

ITEM 10-3019
\$89.95

• New, Myers model# F48Y05A03 (25051A008) thermally protected, capacitor start jet pump motor. Automatic thermal overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 10.0/5.0 Amps
- Speed 3450 RPM
- Rotation Counterclockwise
- Phase 1
- Service Factor 1.30
- Enclosure ODP
- Duty Continuous
- Frame 48Y
- Mount Face Mount w/ Four 3/8" Holes on 7 1/4" Bolt Circle
- Shaft 5/8" dia. x 2 1/8" Overall Length, 1/2"-20 x 1/4" Long RH Threaded End
- Size 12 1/8" x 5 3/4" x 8"
- Shpg. 25 lbs.



2 HP 1800 RPM Motor

ITEM 10-3121
\$229.95

• New, MARATHON model 145TBDR5337 general purpose electric motor. Capacitor start and run. Steel housing. Thermal overload protection with manual reset. Made in the USA.

SPECIFICATIONS

- Power 2 HP
- Voltage 115/230 AC
- Amperage 18.8/9.4 Amps
- Speed 1800 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 145T
- Rigid Base Mount
- Six 0.34" diam. holes on 5 1/2" x 4" to 5" centers
- Shaft 7/8" diam. x 2 1/8" w/ 3/16" keyway
- Size 11.62" x 8.89" x 8.58"
- Shpg. 48 lbs.



3/4 HP 3600 RPM Motor

ITEM 10-3120
\$59.95

• New, BLUFFTON MOTOR WORKS model B1244 pool pump motor. Smooth portion of shaft measures 1 9/16" from the bearing overall length 2 1/16". Automatic thermal overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 12.8/6.4 Amps
- Speed 3450 RPM
- Rotation CCW
- Phase 1
- Service Factor 1.27
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56Y
- Mount Square flange 4 bolt on 7 1/8" diam. B.C.
- Shaft 5/8" diam. x 2 1/16" w/ 1/2"-20 RH threaded end
- Size 10 7/8" x 6 5/8" x 6 5/8"
- Shpg. 24 lbs.



2 HP 3450 RPM Motor

ITEM 10-2638
\$119.95

• New, MARATHON model 5KC49RN2520Y electric motor. Manual thermal protection. Welded base mount.

SPECIFICATIONS

- Power 2 HP
- Voltage 115/230 AC
- Amperage 23.8/11.8
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Mount 4 bolt base 4 7/8" x 3" centers
- Shaft 5/8" diam. x 2" w/ 3/16" keyway
- Size 10" x 6 7/16" x 8 15/16"
- Shpg. 33 lbs.



7 1/2 HP 1740 RPM Motor

ITEM 10-3199
\$379.95

• New, A.O. SMITH/CENTURY general purpose electric motor. Capacitor start. Steel housing. No thermal overload protection.

SPECIFICATIONS

- Catalog Number K314
- Power 7 1/2 HP
- Voltage 230 AC
- Amperage 38 Amps
- Speed 1740 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 215TCZ
- Face Mount: Four 1/2"-13 tapped holes on 7 1/4" diameter bolt circle
- Rigid Base Mount: Six 0.41" diam. holes on 8 1/2" x 5 1/2" to 7" centers
- Shaft: 1 1/8" diam. x 3 3/8" w/ 5/16" keyway
- Size 15 1/2" x 14" x 11"
- Shpg. 130 lbs.



Ceiling Fan Motor

ITEM 10-1134
\$12.88

• New GE. 3 lug mount or hang from threaded end cap. Requires 5 mfd capacitor.

SPECIFICATIONS

- Voltage 115 AC
- RPM 225
- Amps 1
- Cont. duty
- Reversible
- Hollow shaft 17 mm dia. x 1 1/2" w/flat
- Size 5" diam. x 3"
- Shpg. 10 lbs.



230 VAC Fan Motor

ITEM 10-2756
\$4.99

• New FASCO Model 7162588. Fan motor with thermal protection. Sealed ball bearings. Requires 4 MFD, 370 VAC capacitor (not included).

SPECIFICATIONS

- Voltage 230 VAC
- Amps 0.50
- Speed 3200 RPM
- Rotation CCW
- Enclosure open
- Duty continuous air over
- Mount 2 studs from body
- 4 studs on face, 2.6" B.C.
- Shaft 5/16" dia. x 1 3/8" w/flat
- Size 3 3/8" dia. x 3 1/2"
- Shpg. 5 lbs.

