

**Handheld Two Button Pendant Switch**



**ITEM 11-2201**  
**\$17.95**

• Brand new. For power-up, gravity down powerpacks. Ideal for remote control of single acting hydraulic power units, etc. Weatherproof plastic housing.

**SPECIFICATIONS**

- Pushbuttons 2 Normally open
- Cord 18/3 14 ft. long
- Contact rating 5 amp 250 VAC • **Shpg. 3 lbs.**

**12 VDC Heavy Duty Reversing Switch**



**ITEM 11-3295**  
**\$16.95**

• Brand new, BUYERS PRODUCTS Part # SW710 reversing switch. Heavy-duty 50 Amp rotary switch controls forward and reverse motion of a 12-volt motor without requiring a relay. Ideal for use with 12 VDC linear actuators, gearmotors and other permanent magnet motors. Commonly used on 12-volt truck and trailer tarp systems. Three positions: momentary-ON, OFF, momentary-ON. Terminal hardware included.

**SPECIFICATIONS**

- Contacts DPDT-CO
- Contact rating 50 Amps at 12 VDC
- Switch type rotary reversing
- Four screw terminals
- Action momentary
- Switch positions ON-OFF-ON
- Face size 2" dia.
- Mounting 1/2" hole
- Mounting depth 1 1/8"
- **Shpg. 2 lbs.**

**4 Position 4 Pole 4 Amp Key Switch**



**ITEM 11-1622**  
**\$2.99**

• New four position keyswitch. Key can be removed in any position. Does not include jam nut for housing.

**SPECIFICATIONS**

- Contacts rated 4 Amps @ 125 VAC, 2 Amps @ 250 VAC Max.
- Fits into 3/4" dia. opening
- Two flats on body, 5/16" across
- Does not include jam nut
- Includes 2 keys
- **Shpg. 1/2 lb.**

**SPST Momentary Push Button Switch**



**ITEM 11-3297**  
**\$6.55**

• Brand new, BUYERS SW901 panel mount momentary push button switch. Moisture repellent insulator.

**SPECIFICATIONS**

- Contacts SPST N.O.
- Switch Type Pushbutton
- Termination Screw Terminals
- Action Momentary
- Switch Positions Two
- Face Size 7/16" diam.
- Mounting Stem 5/8"-32 thread x 3/4"
- Mounting Depth 1 3/4"
- **Shpg. 1/4 lbs.**



**Reversing Drum Switches**

• Brand new, drum type reversing switches. Heavy duty copper contacts, painted metal housing. UL and CSA listed. Available for single or three phase operation and momentary or maintained operation.

| ITEM      | Action     | Horsepower Ratings |   |               |     | Size               | Shpg   | Price           |
|-----------|------------|--------------------|---|---------------|-----|--------------------|--------|-----------------|
|           |            | 1 Phase Volts      |   | 3 Phase Volts |     |                    |        |                 |
| 11-3390   | Maintained | 1.5                | 2 | —             | —   | 2.5" x 4" x 4.5"   | 2 lbs. | <b>\$59.10</b>  |
| 11-3390-M | Momentary  | 1.5                | 2 | —             | —   | 2-5" x 4" x 4.5"   | 2 lbs. | <b>\$65.50</b>  |
| 11-3391   | Maintained | 1.5                | 2 | 2             | 1   | 2.5" x 4" x 4.5"   | 2 lbs. | <b>\$72.10</b>  |
| 11-3391-M | Momentary  | 1.5                | 2 | 2             | 1   | 2.5" x 4" x 4.5"   | 2 lbs. | <b>\$79.50</b>  |
| 11-3392   | Maintained | 2                  | 3 | 5             | 7.5 | 3.5" x 6.2" x 5.6" | 4 lbs. | <b>\$157.15</b> |

**12 VDC Heavy Duty Disconnect Switch**



**ITEM 11-3294**  
**\$17.40**

• Brand new, BUYERS Model SW700 heavy duty master disconnect switch.

**SPECIFICATIONS**

- Contacts SPST
- Contact ratings: 20 Amps at 12 VDC cont. 125 Amps at 12 VDC int. 15 sec. ON & 5 min. OFF
- Switch type rotary
- Screw terminals
- Action maintained
- Switch positions two
- Face size 2 1/2" diam.
- Mounting panel 3/4"-16
- Mounting depth 2 15/16"
- **Shpg. 1 lb.**

**SPST N.O. Heavy Duty Momentary Switch**



**ITEM 11-3296**  
**\$16.05**

• Brand new, BUYERS BSW002 heavy duty flange mount momentary pushbutton switch. Heavy duty spring.

**SPECIFICATIONS**

- Termination 5/16"-24 stud terminals
- Switch positions two
- Mounting depth 1 7/16"
- Face size 2 1/8" x 2 7/16"
- Mounting two holes on 1 3/4" centers
- **Shpg. 1/2 lb.**

**SPST 10 Amp Toggle Switch w/ Recessed Pan**



**ITEM 11-3298**  
**\$7.30**

• Brand new, BUYERS Model SW911 toggle switch recessed in a pan. Recessed pan prevents accidental activation and protects switch from impacts. 20 gauge plated steel pan. Mounts in 2" diameter hole, with 3 holes on 2 5/8" diameter bolt circle.

**SPECIFICATIONS**

- Contacts SPST
- Contact ratings 10 Amps at 12 VDC 12 VDC max.
- Switch type toggle
- Spade terminals
- Action maintained
- Switch positions two
- Face size 3 3/16" dia.
- Mounting flange
- Mounting depth 2"
- **Shpg. 1/4 lb.**

**Waterproof 12 VDC Battery Isolator Switch**



**ITEM 11-3299**  
**\$8.30**

• Brand new, BUYERS PRODUCTS CO. Part # 6391200 battery isolator key-switch. Excellent for marine or automotive use. Circuit closes when key is locked in place. Waterproof plastic housing with water-resistant rubber cover. Removable twist-lock plastic key.

**SPECIFICATIONS**

- Contacts SPST
- Contact ratings at 12 VDC 100 Amps cont. 500 Amps max surge
- Switch type rotary isolator
- Termination two 3/8"-16 studs
- Action maintained
- Switch positions two
- Face size 2 1/2" dia.
- Mounting four 3/16" holes
- Mounting depth 1 1/2"
- **Shpg. 1/2 lb.**

**SPST Momentary Pushbutton Starter Switch**



**ITEM 11-3428**  
**\$3.99**

• New, panel mount momentary push button starter switch. Ideal for many automotive and other DC electrical circuits. Weather and dust proof housing with rubber cover.

**SPECIFICATIONS**

- Contacts SPST (normally open)
- Contact rating 60 amps at 12 VDC
- Switch type pushbutton
- Screw terminals
- Action momentary
- Switch positions two
- Face size 1 1/16" diam.
- Mtg. stem 5/8" x 2 1/32" long
- Size 1 1/8" dia. x 1 1/2"
- **Shpg. 1/4 lb.**

**SPST Momentary Pushbutton Switch**



**ITEM 11-3293**  
**\$5.10**

• Brand new, BUYERS BSW90030 panel mount momentary normally open pushbutton switch. Weather and dust proof housing. Originally intended for vehicle uses.

**SPECIFICATIONS**

- Contacts SPST
- Contact ratings 35 amps at 12 VDC
- Switch type pushbutton
- Screw terminals
- Action momentary
- Switch positions two
- Face size 1 5/16" diam.
- Mtg. stem 5/8"-32 x 2 1/32"
- Mounting depth 1 3/4"
- **Shpg. 1/4 lb.**