

5" x 1 1/2" Swivel Stem Caster

w/ Swivel & Wheel Lock

ITEM 1-3311
\$19.99

• New, FAULTLESS swivel stem caster. Originally intended for scaffold. Swivel and wheel lock. Solid hard rubber wheel. Zinc plated steel yoke.

SPECIFICATIONS

- Wheel size 5" x 1 1/2"
- Load capacity 325 lbs.
- Mounting height 6 1/4"
- Stem friction grip stem mount 1" dia. x 2 1/2"
- Shpg. 6 lbs.



5" x 1 5/16" Swivel Stem Caster

w/ Wheel Lock

ITEM 1-3307
\$5.99

• New FAULTLESS swivel stem caster with wheel lock. Thermoplastic tire on black polypropylene wheel.

SPECIFICATIONS

- Wheel size 5" x 1 5/16"
- Load capacity 125 lbs.
- Mounting height 5 3/4"
- Stem threaded 1/2"-13 x 1 1/2"
- Shpg. 1 1/2 lbs.



3" x 1 1/4" Stem Swivel Caster

ITEM 1-2404
\$5.99

• New. Swivel stem caster with 3" diam. x 1 1/4" wide solid polypropylene wheel. 1"-12 diam. x 5/8" threaded stem. Working height 4 1/4" (floor to base of stem). Load capacity 100 lbs. Shpg. 5 lbs.



5" x 1 1/4" Swivel Plain Stem Caster

ITEM 1-4538
\$4.95

• New, MEDCASTER model# HC05RPP125TLCL02 plain stem caster with sheet metal threadguards and central total brake. Intended for use with hospital beds. Braking mechanism is operated by rotating 11mm (0.433") hex.

SPECIFICATIONS

- Wheel Size 5" x 1 1/4"
- Load Capacity 260 lbs.
- Mounting Height 6 7/8"
- Brake Wheel and Swivel
- Mount 32mm x 2" long
- plane stem w/ two M6-1.0 tapped bolt holes
- Wheel Tread Grey TPR
- Caster Wheel Core Material Polypropylene
- Caster Wheel Bearing Ball
- Shpg. 5 lbs.



5" x 1 5/16" Threaded Stem Swivel Caster

ITEM 1-4751
\$3.95

• New, FAULTLESS model# 30807 threaded stem caster. Ball bearing in swivel head.

SPECIFICATIONS

- Wheel Diameter 5"
- Wheel Width 1 5/16"
- Load Capacity 125 lbs.
- Mounting Height 5 3/4"
- Mount 1/2"-13 x 1 1/2" long
- threaded stem
- Wheel Tread Grey TPR
- Caster Wheel Core TPR
- Caster Wheel Bearing Roller
- Shpg. 2 1/2 lbs.



3" x 1 1/4" Swivel Stem Caster

ITEM 1-3329
\$2.99

• New, FAULTLESS swivel stem caster. Solid hard rubber wheel. Zinc plated steel caster yoke.

SPECIFICATIONS

- Wheel size 3" x 1 1/4"
- Load capacity 270 lbs.
- Mounting height 3 3/4"
- Stem threaded 1/2"-13 x 3/4"
- Shpg. 1 1/2 lbs.



5" x 1 1/4" Swivel Square Stem Caster

ITEM 1-4251
\$4.95

• New, ALBION Model 02XS05051S004 swivel square stem caster. X-tra soft rubber flat tread. Delrin bushing. Plated caster yoke.

SPECIFICATIONS

- Wheel size 5" dia. x 1 1/4" w.
- Load capacity 325 lbs.
- Square stem
- Mount square 7/8" x 1 3/4" long stem w/ 2 bolt holes
- Bolt holes 1/4" dia.
- Shpg. 2 lbs.



5" x 1 5/16" Threaded Stem Swivel Caster w/ Brake

ITEM 1-4234
\$3.95

• New, FAULTLESS model EY6522RB 1/2"-13 X 1 1/2 W/PP/P swivel threaded stem caster with brake. Zinc plated steel yoke. Solid polypropylene wheel.

SPECIFICATIONS

- Wheel Size 5" dia. x 1 5/16" wide
- Load Capacity 150 lbs.
- Stem Threaded
- Mounting height 5 13/16"
- Mount: 1/2"-13 x 1 1/2"
- Shpg. 1 1/2 lbs.



3" x 1 5/16" Swivel Plate Caster w/ Brake

ITEM 1-4967
\$2.49

• New, FAULTLESS model# 29896 plate caster with wheel brake. Ball bearing in swivel head.

SPECIFICATIONS

- Wheel Diameter 3"
- Wheel Width 1 5/16"
- Load Capacity 90 lbs.
- Mounting Height 3 3/4"
- Top Plate 3 5/8" x 2 9/16" x 1 5/8"
- Mount Four slots on 2 15/16" x 1 3/4" centers
- Bolt Holes 3/8" x 5/16"
- Wheel Tread Grey TPR
- Caster Wheel Core Material Polyolefin
- Caster Wheel Bearing Plain
- Shpg. 2 lbs.



5" x 1 1/8" Swivel Stem Caster

ITEM 1-1591
\$6.95

• New. Ball bearing swivel stem caster with 5" diam. x 1 1/8" wide cushion rubber wheel. 7/16" diam. x 1 1/2" stem with retention ring. 150 lb. capacity. Shpg. 4 lbs.



4 3/4" x 1" Swivel Caster w/ Swivel Lock

ITEM 1-3257
\$4.99

• New, swivel caster rubber tire on plastic wheel. Chemical, water, salt and oil resistant non-marking wheel. Plastic yoke with a 1 1/8" long metal insert where a bolt passes thru the yoke and swivel. Two position swivel lock, 180° offset. Shipped with the wheel unattached to yoke for easier installation.

SPECIFICATIONS

- Wheel size 4 3/4" dia. x 1"
- Mounting height 6 1/2"
- Mounting bore 1/2" diam.
- Load capacity 275 lbs.
- Size 5 7/8" x 6 1/2" x 2 1/4"
- Shpg. 2 lbs.



3" x 1 3/16" Rigid Stem Caster

ITEM 1-3394
\$1.99

• New, FAULTLESS rigid stem caster. "DYNA-TRED II" thermoplastic rubber on polypropylene. Zinc plated caster yoke.

SPECIFICATIONS

- Wheel size 3" x 1 3/16"
- Load capacity 90 lbs.
- Mounting height 3 1/2"
- Stem grip ring 7/16" dia. x 2"
- Shpg. 1 lb.



Grip Ring Caster Sockets



1-3667 1-3668 1-5361 1-3832 1-4898

• Brand new, use to mount grip ring casters with 7/16" dia. stem into steel tubing. Shpg. 1/10 lb.

ITEM	Fits into	Length	Price
1-3667	1" OD 16 gauge tubing	1 1/2"	\$.35
1-3668	3/4" OD 16 gauge tubing	1 1/2"	\$1.50
1-5361	9/16" OD 16 gauge tubing	1 3/8"	\$.39
1-3832	5/8" ID Square tubing	2 1/8"	\$.50
1-4898	Steel Corner Bracket	1 3/8"	\$.59

4" x 1" Grip Ring Caster

ITEM 1-3766
\$2.99

• New, JARVIS swivel grip ring stem caster. Solid polyolefin wheel. Plated steel caster yoke.

SPECIFICATIONS

- Wheel size 4" dia. x 1"
- Load capacity 150 lbs.
- Mounting height 4 3/4"
- Stem grip ring 0.845" dia. x 2"
- Shpg. 3 lbs.



Caster Grip Ring Socket

ITEM 1-4860
\$1.19

• New, FAULTLESS part ER4983 square tubular grip ring caster socket. Polyethylene. Set of 4.

SPECIFICATIONS

- Caster Stem 7/16" dia.
- Tubing size 18 gauge 1" OD, 0.902 ID
- Minimum hole depth 1 7/8"
- Size 1.125" square x 2"
- Shpg. 1/4 lb.

