

### 23 HP Vanguard Engine



ITEM 28-1964  
**\$1499.95**

• New, Briggs and Stratton Vanguard V-twin horizontal crankshaft engine. Supplied with fuel pump. No fuel tank. Pressurized lubrication system with oil filter and cooler. 20 amp alternator. Cast iron cylinder sleeve, low oil alert, float style carburetor. Keyswitch on front. Set up for remote manual choke. 5" round muffler with starter motor side outlet.

**SPECIFICATIONS**

- Model 386447-0084
- Power 23 HP
- Bore/Stroke 2.97" x 2.76"
- Displacement 627 cc.
- Speed 3600 RPM
- Start Electric w/recoil backup
- Shaft Horizontal
- Shaft 1" dia. x 2<sup>29</sup>/<sub>32</sub>" w/ 1/4" keyway, tapped 3/8"-24
- Mount 7.68" x 4.02"
- Accessory Mount 5" B.C, 6.5" B.C, 7.75" B.C.
- Fuel Tank No
- Size 16.1" x 12.3" x 17.7"
- Shpg. 150 lbs.

Truck freight only.

### 11.5 HP Vertical Briggs & Stratton Engine



ITEM 28-1989  
**\$349.95**

• New, BRIGGS & STRATTON single cylinder vertical engine. Cast iron cylinder sleeve. Splash Lubrication. 12 VDC electric start with recoil backup. CARB and EPA certified for all states.

**SPECIFICATIONS**

- Model 21R807
- Power 11.5 HP
- Disp. 344cc
- Start Electric w/ recoil backup
- Shaft Orientation Vertical
- Shaft 1" dia. x 3.16" w/ 1/4" keyway and tapped 7/16"-20
- Mount 10" bolt circle
- Fuel Tank 2.8 qt.
- Size 16" x 16 1/2" x 16"
- Shpg. 66 lbs.

### 10 HP Tecumseh Engine



ITEM 28-1741  
**\$139.95**

• New, TECUMSEH horizontal engine built for driving electric generators. Cast iron sleeve, fixed speed governor. Low oil shutdown. Lighted on/off switch. Not for sale or use in California.

**SPECIFICATIONS**

- Model LH358XA-159493Y
- Power 10 HP
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Fuel Tank No
- Shaft 1 3/8" dia. x 1 1/8", stepped to 7/8" dia. x 1 7/8"
- then tapered from 0.875" to 0.670" by 1.25" length taper. OA length 4.33" tapped 3/16"-24 no keyway
- Mount 3 1/4" x 6 3/8"
- Accessory Mount 4 bolt on 3 5/8" B.C.
- Size 12" x 13 1/2" x 13"
- Shpg. 60 lbs.

### 9.5 HP Horizontal Kohler Engine



ITEM 28-1988  
**\$349.95**

• New, KOHLER Command Pro CH395 horizontal shaft engine. Features overhead valves, cast iron sleeve liner, mechanical governor, low-oil shutdown, and electronic ignition. Muffler heat shield and industrial air cleaner.

**SPECIFICATIONS**

- Model CH395
- Power 9.5 HP @ 4000 RPM
- Disp. 277 cc
- Torque 13.9 ft-lbs. @ 2800 RPM
- Speed 3600 RPM
- Start Recoil
- Fuel Tank 7.4 quarts
- Shaft Orientation Horizontal
- Shaft 1" dia. x 3 1/2" w/ 1/4" key and tapped 7/16"-20
- Base Mount Four bolt holes on 3 1/2" x 7 1/16" centers
- Accessory Mount Inner 4 bolt on 5" B.C. Outer 4 bolt on 6.5" B.C.
- Size 17 1/2" X 16" X 18"
- Actual Weight 61 lbs.
- Dimensional Shpg 77 lbs.

### 9 HP Loncin Engine



ITEM 28-1963  
**\$219.95**

• New, LONCIN single cylinder engine. Model G300FA. Built for use with KARCHER pressure washers. Low oil shutdown, cast iron cylinder sleeve. Muffler with guard.

**SPECIFICATIONS**

- Model G300FA
- Power 9 HP
- Disp. 302 cc
- Speed 3600 RPM
- Start Recoil
- Shaft Horizontal
- Shaft 1" dia. x 3 2/3" w/ 1/4" keyway, tapped 7/16"-20
- Base Mount
- Accessory Mount
- Fuel Tank 5.5 liter
- Size 15" x 17" x 16 1/4"
- Shpg. 66 lbs.

### 7.4 HP Briggs & Stratton Engine



ITEM 28-1986  
**\$219.95**

• New, BRIGGS & STRATTON XR1150 horizontal shaft engine. Engines feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, mechanical governor, low-oil sensor, electronic ignition, fuel valve and easy to use controls. Meets EPA and CARB emission regulations for all states.

**SPECIFICATIONS**

- Model 15T2320224F8
- Power 7.4 HP (calculated)
- Torque 11.5 ft-lbs
- Bore/Stroke 75mm/56mm
- Disp. 250 cc
- Speed 3600 RPM
- Start Recoil
- Fuel Tank 3.3 quarts
- Shaft Horizontal
- Shaft 3/4" dia. x 2 1/2" w/ 3/16" key, tapped 3/16"-24 UNF
- Base Mount Four 0.35" bolt holes on 6 3/8" x 3 1/8" centers
- Accessory Mount 4 bolt on 3 5/8" B.C.
- Size 16 1/2" X 13" X 16 3/4"
- Actual Weight 34 lbs.
- Dimensional Shpg. 48 lbs.

### 6.5 HP Kohler Engine



ITEM 28-1979  
**\$179.95**

• New, KOHLER SH265 horizontal shaft engine. Engines feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, mechanical governor, low-oil sensor, electronic ignition, fuel valve and easy to use controls. Meets EPA and CARB emission regulations for all states.

**SPECIFICATIONS**

- Model SH265
- Power 6.5 HP
- Torque 10 ft-lbs
- Bore/Stroke 68mm/54mm
- Disp. 196 cc
- Speed 3600 RPM
- Start Recoil
- Fuel Tank 3.3 quarts
- Shaft Horizontal
- Shaft 3/4" dia. x 2 3/8" keyed, tapped 3/16"-24 UNF
- Base Mount Four 0.39" bolt holes on 6 3/8" x 3 1/8" centers
- Accessory Mount 4 bolt on 3 5/8" B.C.
- Size 14 3/4" X 13" X 15"
- Actual Weight 34 lbs.
- Dimensional Shpg. 48 lbs.

### 6.1 HP Briggs & Stratton Engine



ITEM 28-1985  
**\$189.95**

• New, BRIGGS & STRATTON horizontal shaft engine. Engines feature overhead valves, cast iron sleeve liner, ball bearing supported crankshaft, mechanical governor, low-oil sensor, electronic ignition, fuel valve and easy to use controls. Meets EPA and CARB emission regulations for all states.

**SPECIFICATIONS**

- Model CR950
- Power 6.1 HP
- Torque 9.5 ft-lbs
- Bore/Stroke 70mm/54mm
- Disp. 208 cc
- Speed 3600 RPM
- Start Recoil
- Fuel Tank 3.3 quarts
- Shaft Horizontal
- Shaft 3/4" dia. x 2 3/8" w/ 3/16" key, tapped 3/16"-24 UNF
- Base Mount Four hole on 3 1/8" x 6 3/8" centers
- Accessory Mount 4 bolt on 3 5/8" B.C.
- Size 16" X 13" X 14"
- Actual Weight 33 lbs.
- Dimensional Shpg. 47 lbs.

### 4.5 HP Briggs & Stratton Engine



ITEM 28-1940  
**\$99.95**

• New, Briggs & Stratton horizontal shaft engine. Snowblower applications, no air cleaner. Fixed speed governor. 60 watt AC alternator. Manual choke with primer bulb. Dual ball bearing crankshaft. Push/Pull keyswitch. Wire muffler guard. Steel fuel tank. Extended crankcase drain. Oversized hand grip for use with gloves.

**SPECIFICATIONS**

- Model 10D136-0007-F9
- Engine Family FBSXS.1631SC
- Displacement 163 cc
- Torque 7.5 ft-lbs. @ 3600 RPM
- HP (calculated) 4.5 @ 3600 RPM
- Speed 3600 RPM
- Start Recoil
- Shaft 3/4" dia. x 3.93" w/ keyway, tapped 3/8"-24.
- Mount 4 hole, 6 3/8" x 3 1/8"
- Fuel Tank 3 quart
- Size 14 1/2" x 10 1/4" x 13 1/4"
- Actual Weight 35 lbs.
- Dimensional Shpg. 63 lbs.