



## 12 Volt DC BUCHER WUXI Hydraulics Power Units



• Brand new BUCHER WUXI Hydraulics. Hydraulic power units for operating hydraulic cylinders. Ideal for many applications including dump trailers, flatbed dumps, forklift stackers, lift gates, pallet trucks, aerial lifts, auxiliary power and many other applications. Built-in check and adjustable main relief valves. Double acting units with external control solenoids have adjustable 1500 PSI relief installed on retract port. See chart below for availability details on single or double acting valving, tank size and pressure ratings.

**Single Acting Valve** Power up, hold and gravity/external force lower.

**Double Acting Valve** Power extend, hold and power retract.

### SPECIFICATIONS

- 12 VDC motor
- 12 VDC solenoid valve
- Intermittent duty

ITEM	Valve Type	Ports	Flow at 1500 PSI	Relief Valve Set	Tank Size Cap.	Tank Usable	Size	Shpg	Price
9-12367-13	Single Acting 12 Volt DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	1.3 gal.	1.0 gal.	18 1/4" x 5 1/4" x 8"	40 lbs.	\$390.95
9-12367-32	Single Acting 12 Volt DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	3.2 gal.	2.5 gal.	22" x 8 5/8" x 9 1/2"	45 lbs.	\$410.40
9-12367-53	Single Acting 12 VOLT DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	5.3 gal.	4.2 gal.	24 1/4" x 10" x 11 1/4"	50 lbs.	\$437.95
9-12366	Double Acting Reversible Motor no remote	SAE 4	0.3 GPM	2500 PSI	1.4 qt.	1.1 qt.	14 1/2" x 6 3/4" x 6"	21 lbs.	\$310.85
9-12368-11	Double Acting 12 Volt DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	1.1 gal.	0.8 gal.	16" x 6 3/4" x 8 1/4"	40 lbs.	\$446.95
9-12368-16	Double Acting 12 Volt DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	1.6 gal.	1.2 gal.	22" x 6 3/4" x 8 1/4"	42 lbs.	\$463.95
9-12368-21	Double Acting 12 Volt DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	2.1 gal.	1.7 gal.	26 1/4" x 7 1/8" x 8 3/4"	52 lbs.	\$483.95
9-12369	Double Acting 12 Volt DC w/handheld remote	SAE 6	1.4 GPM	3000 PSI	3.1 qt.	2.5 qt.	21 1/2" x 7 1/8" x 8 3/4"	43 lbs.	\$505.35

## AC Hydraulic Power Units

• Brand new BUCHER WUXI Hydraulics. Ideal for use auto lifts, hoists, material handling, work tables and other applications that require power up, hold and gravity down. Adjustable lowering flow control. Built-in relief and check valves. Momentary pushbutton switch for raising and a manual lever for lowering. Vertical mount.



### ITEM 9-12371 SPECIFICATIONS

- 1.75 HP MOTOR
- 115 VAC, 1 PH
- 14 Amps
- Intermittent duty
- 0.8 GPM

- 2900 PSI max.
- Relief Set 2900 PSI
- Port SAE 6
- 2 Gallon Reservoir (usable)
- Size 11 1/8" x 9" x 31 1/2"
- 60 lbs.

**\$370.60**

### ITEM 9-12372 SPECIFICATIONS

- 3 HP MOTOR
- 208/240 VAC, 1 PH
- 16 Amps
- Intermittent duty
- 1.5 GPM

- 2900 PSI max.
- Relief Set 2900 PSI
- Port SAE 6
- 3 Gallon Reservoir (usable)
- Size 11 1/8" x 9" x 31 1/2"
- 60 lbs.

**\$383.15**

## 12 Volt DC Single Acting Power Unit

• New HYDRO-TEK. Hydraulic power unit for operating a single acting hydraulic cylinder. Power up, gravity down. 12 Volt DC solenoid release valve with check valve for directional control of single acting cylinder. Built-in check and adjustable main relief valve.



### ITEM 9-12513 SPECIFICATIONS


- Power 2 HP
- Voltage 12 DC
- Amperage 130 Amps
- Duty Intermittent
- Flow 1.2 GPM at 1500 PSI
- Pressure 3000 PSI max.
- Relief Valve Setting Adjustable set @ 3000 PSI
- Pendant Control No
- Valve Type Single Acting

- Valve Operation 12 Volt DC Solenoid
- Port SAE 6
- Mounting Horizontal
- Reservoir Size 2 Gallon
- Reservoir Size Useable 1.5 Gallon
- Reservoir Material Poly
- Size 25" x 7" x 8"
- Shpg. 28 lbs.

**\$279.95**

## 12 Volt DC Snow Plow Power Unit

• Brand new, BUCHER WUXI Hydraulics. Power unit with built-in 12 volt DC solenoid valves for operating snow plows. Provides power up, hold and gravity down for single acting cylinder blade lift plus left and right control for two single acting cylinders or one double acting cylinder for blade angle. Features include heavy duty 12 volt motor, 12 volt directional control valves, adjustable main relief valve, steel reservoir, check valves for load holding and adjustable cross-over relief valves on power angle circuit. Horizontal mount. Includes reservoir breather and 12 volt DC motor solenoid



### ITEM 9-12370 SPECIFICATIONS

- Voltage 12 VDC
- Amperage 210 amps
- Duty Intermittent
- Flow 1.4 GPM
- Pressure 2600 PSI max.
- Main Relief Valve Adjustable set @ 2600 PSI

- Cross-over Relief Valve Adj. set @3480 PSI
- Reservoir 2.8 quart usable
- Ports 1/4" NPT
- Mount 2 bolt base on 3 1/4" c/c
- Orientation Horizontal
- Size 17 3/4" x 9" x 7"
- Shpg. 40 lbs.

**\$727.30**

## 12 Volt DC Double Acting Power Unit

• New MAVERICK by DALTON. Hydraulic power unit for operating a double acting hydraulic cylinder. Ideal for many applications including dump trailers, flatbed dumps, forklift stackers, lift gates, pallet trucks, aerial lifts, auxiliary power and many other applications. Handheld remote with detachable 14 ft. cord.



### ITEM 9-12514 SPECIFICATIONS

- Power 2 HP
- Voltage 12 DC
- Amperage 260 Amps
- Duty Intermittent
- Flow 1.2 GPM at 1500 PSI
- Pressure 3000 PSI max.
- Relief Valve Setting Adjustable set @ 3000 PSI
- Pendant Control Yes
- Valve Type Double Acting

- Valve Operation 12 Volt DC Solenoid
- Ports SAE 6
- Mounting Horizontal
- Reservoir Size 2 Gallon
- Reservoir Size Useable 1.5 Gallon
- Reservoir Material Plastic
- Size 22" x 7" x 8"
- Shpg. 34 lbs.

**\$309.95**

## 12 Volt Hydraulic Power Unit

### ITEM 9-7917 \$249.99

• New, BARNES model 130-1306 hydraulic power unit. Hydraulic power source ideal for use with separate directional control valve (not included). Steel reservoir for horizontal mounting.



### SPECIFICATIONS


- Voltage 12 DC
- Amperage 150 Amps max
- Duty Intermittent
- Flow 1 GPM @ 500 PSI
- Flow 0.5 GPM @ 2250 PSI
- Pressure 2300 PSI max
- Valving None

- Relief Valve Set at 2100-2300 PSI
- Reservoir 1.6 gallon
- Ports SAE 6
- Mount Two tapped holes
- Orientation Horizontal
- Size 22" x 7" x 9"
- Shpg. 22 lbs.

## 12 Volt DC Power Unit

### ITEM 9-12818 \$232.55

• Brand new MTE Hydraulics. Hydraulic pump/motor unit. Ideal for many applications including dump trailers, flatbed dumps, forklift stackers, lift gates, pallet trucks, aerial lifts, auxiliary emergency power and many other applications. Includes 12 volt DC relay.



### SPECIFICATIONS

- Model D203-4852
- Voltage 12 Volt DC
- Amperage 260 Amps max.
- Duty Intermittent
- Pressure 3000 PSI max.
- Flow, Pressure, Amperage and Duty Ratings: 2.9 GPM at 500 PSI at 130 Amps with 29% duty
- 2.0 GPM at 1000 PSI at 170 Amps with 22% duty
- 1.4 GPM at 1500 PSI at 205 Amps with 29% duty
- 1.1 GPM at 2000 PSI at 245 Amps with 15% duty
- Relief Valve Setting No Relief
- Inlet Port SAE 8
- Outlet Port SAE 6
- Horizontal Mounting
- Mount 2 bolt tapped 3/16 on 3.25" centers
- Size 10 5/8" x 5 1/16" x 7 1/4"
- Shpg. 30 lbs.