

Double Acting Hydraulic Trunnion Cylinder

• Double acting with trunnion mount on gland end. Two SUN counterbalance valves installed on rod end manifold block.

2.75" x 186" x 2"



ITEM 9-5584 SPECIFICATIONS

- New, double acting
 - Bore x Stroke 2¾" x 186"
 - Pressure 2500 PSI max.
 - Rod dia. 2"
 - Ports SAE 8
 - Base to pin retracted lgth. (pin next to gland) 211"
 - Counterbalance valves set at 1000 and 1200 PSI
 - Trunnion to crosstube pin retracted lgth. 6½" (pin next to gland)
 - Base end plain w/bracket
 - Rod end steel manifold block
 - Block dimensions 8¾" x 8" x 3½"
 - Two pin holes 1¼"
 - Pin centers 3"
 - Trunnion end rectangle male pins
 - Outside pin width 10½"
 - Inside pin width 8"
 - Pin size 1⅞" x 2¼"
 - Pin length 1¼"
 - Overall lgth. 215½"
 - **Shpg. 400 lbs.**
- Truck freight only.*

\$599.95

3" x 4.375" x 1.25"



ITEM 9-12512 SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 4.375"
- Pressure 3000 PSI
- Rod Dia. 1.25"
- Ports ¼" NPT
- Retracted Length 11.38"
- Rod End: Threaded 1"-14 Thread Length 1"
- Base End: Cross-Tube Width 4"
- Pin Hole 1"
- **Shpg. 18 lbs.**

\$109.95

ITEM 9-12512-B

Same as above except Black

\$109.95

3" x 6.125" x 1.5



ITEM 9-2191 SPECIFICATIONS

- Unused, old inventory
- Double acting
- Retracted lgth. 21¾"
- 1⅞" self aligning
- Bore/stroke 3" x 6⅞"
- Single eye both ends
- 2500 PSI
- Rod end width 2"
- Rod diam. 1½"
- Base end width 2½"
- Ports SAE 8
- **Shpg. 45 lbs.**

\$76.50

3" x 7.5" x 0.93"



ITEM 9-11656 SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 3"(76mm) x 7.5"(190mm)
- Pressure 2500 PS
- Rod dia. 0.93"
- Ports ⅝" NPT
- Retracted Length 14.5"
- Rod End: Threaded Thread Size-Pitch ⅞"-14 TPI Thread Length 1.5"
- Base End: Clevis Outside Width 3.25"
- Pin hole ⅞"
- **Shpg. 19 lbs.**

\$69.95

3" x 8" x 1.5"



ITEM 9-9223 SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 8"
- Pressure 3000 PSI max.
- Rod Dia. 1½"
- Ports SAE 8
- Retracted Length 31½"
- Tang w/ Swivel Eye Ends Max Thickness ⅞"
- Pin Center to Tang End 15½"
- Pin Hole 1"
- **Shpg. 18 lbs.**

\$149.95

3" x 8" x 1.5"



ITEM 9-9572 SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore x Stroke 3" x 8"
- Pressure 3000 PSI max.
- Rod dia. 1½"
- Ports SAE 8
- Retracted lgth. 31"
- Rod thread-on tang w/ swivel eye ⅞" thick
- Base tang w/ swivel eye ⅞" thick
- Pin holes 1"
- **Shpg. 39 lbs.**

\$149.95

3" x 10" x 1.5"



ITEM 9-12842 SPECIFICATIONS

- New, Double Acting
- Bore/Stroke 3" x 10"
- Pressure 3000 PS
- Rod dia. 1.5"
- Ports SAE 8
- Retracted Length 18"
- Crosstube Ends
- Width 5"
- Pin holes 1½"
- **Shpg. 30 lbs.**

\$139.95

3" x 11" x 1.25"



ITEM 9-9301

- Cartridge block has one counterbalance valve and one pilot-to-open check valve.
- New, double acting
- Bore x Stroke 3" x 11"
- Pressure 3000 PSI max.
- Rod dia. 1¼"
- Ports SAE 8
- Retracted lgth. 11"
- Rod crosstube 2" w.
- Male trunnion trunnion pin width outside 9¾", inside 6"
- pin ctr. to rod pin ctr. 11"
- pin ctr. to base end 9½"
- trunnion pin 1¾" dia.
- **Shpg. 49 lbs.**

\$83.95

3" x 12" x 1.5"



ITEM 9-7261-12 SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 12"
- Pressure 3000 PSI
- Rod Dia. 1½"
- Ports SAE 8
- Retracted Length 20¼"
- Swivel-Ball Ends
- Ball width 1.75"
- Ball O.D. 3.13"
- Pin Holes 1.00"
- **Shpg. 26 lbs.**

\$211.70

3" x 15" x 1.375"



ITEM 9-12470 SPECIFICATIONS

- New, Double Acting
- Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3000 PSI
- Rod Dia. 1.375"
- Ports SAE 8
- Retracted Length 24.375"
- Pin Holes 1½"
- Crosstube Ends
- Rod End: Width 2.75"
- Rod End: Width 3.5"
- Base End: Width 3.5"
- **Shpg. 35 lbs.**

\$129.95

3" x 15" x 1.5"



ITEM 9-7338 SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 55"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- **Shpg. 33 lbs.**

\$109.99

3" x 15" x 1.5"



ITEM 9-7339 SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- **Shpg. 60 lbs.**

\$109.99

3" x 15" x 1.5"



ITEM 9-7340 SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- **Shpg. 60 lbs.**

\$109.99

3" x 15" x 1.5"



ITEM 9-7341 SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- **Shpg. 60 lbs.**

\$109.99

3" x 16" x 1.75"



ITEM 9-10314

- Two independent 3" x 16" x 1.75" welded cylinders joined in the middle. Four SUN model CACA-LHN adjustable, atmospherically-ferenced, vented counterbalance valves.
- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1⅞"-12
- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1¾"
- Ports SAE 6, See Above
- Overall Length 92½"
- **Shpg. 190 lbs.**

\$89.95

Truck freight only