

4" x 6.25" x 2"



ITEM 9-9999

\$144.95

SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore x Stroke 4" x 6 1/4"
- Pressure 3000 PSI max.
- Rod dia. 2"
- Ports SAE 6
- Retracted lgth. 25 1/2"
- Tang ends 2 1/4" thick
- Pin holes 1 1/16"
- Shpg. 58 lbs.

4" x 8" x 2"



ITEM 9-030-08-S

\$139.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 8"
- Pressure 2500 PSI
- Ports 1/2" NPT
- Retracted Length 17"
- Crosstube Ends
- Thru hole Width 2"
- Width 4.5"
- Pin Holes 1 1/4"
- Shpg. 43 lbs.

4" x 8" x 2"



ITEM 9-12844

\$139.95

SPECIFICATIONS

- New, Double Acting
- Bore/Stroke 4" x 8"
- Pressure 2500 PSI
- Rod dia. 2"
- Ports SAE 8
- Retracted Length 17"
- Crosstube Ends
- Rod End : O.D. 2.25" Width 2"
- Base End: O.D. 1.875" Width 4.5"
- Pin Holes 1 1/4"
- Shpg. 48 lbs.

4" x 9" x 2"



ITEM 9-9560

\$194.95

SPECIFICATIONS

- Two cartridge valves installed in base end.
- Unused, old inventory
- New, Double Acting
- Bore x Stroke 4" x 9 1/2"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Ports SAE 4/6
- Retracted Length 21 1/4"
- Pin Holes 1 1/16"
- Rod End Crosstube
- Rod End Width 2"
- Base End Tang
- Base End Max Thickness 2"
- Shpg. 56 lbs.

4" x 9.5" x 2"



ITEM 9-9220

\$199.95

SPECIFICATIONS

- Counter-balance valve with 4.5:1 pilot ratio, rated for 15 GPM, set to 3900 PSI.
- Unused, old inventory
- Double acting
- Bore x Stroke 4" x 9 1/2"
- Pressure 3000 PSI max.
- Rod dia. 2"
- Ports SAE 6
- Retracted lgth. 21 1/4"
- Tang w/ swivel eye ends 1 1/16" thick
- Pin holes 1 1/4"
- Shpg. 64 lbs.

4" x 16" x 1.5"



ITEM 9-12203

\$119.95

SPECIFICATIONS

- Double Acting
- Bore x Stroke 4" x 16"
- Pressure 2500 PSI max.
- Rod Dia. 1.5"
- Ports 1/2" NPT
- Retracted Length 26.25"
- Clevis Ends
- Pin Holes 1"
- Shpg. 55 lbs.

4" x 17" x 2"



ITEM 9-9680

\$189.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 4" x 17"
- Pressure 3000 PSI
- Rod dia. 2"
- Ports SAE 6
- Retracted Length 32.5"
- Rod End: Crosstube Width 2 1/2"
- Base End: Tang Max Thickness 2 1/2"
- Pin Holes 48mm (1.889")
- Shpg. 100 lbs.

4" x 18" x 2"



ITEM 9-10958

\$194.95

SPECIFICATIONS

- Both ports in rod end.
- Unused, old inventory
- Double acting
- Bore x Stroke 4" x 18"
- Pressure 3000 PSI max.
- Rod dia. 2", hollow
- Rod thickness 7/16"
- Ports 1/4" NPT
- Retracted lgth. 29 5/8"
- Thru-hole ends rod 2 7/8" w., base 2" w.
- Pin holes rod 1 1/8", base 1 1/4"
- Shpg. 67 lbs.

4" x 20" x 2"



ITEM 9-030-20-S

\$129.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 20"
- Pressure 2500 PSI
- Rod Dia. 2"
- Ports 1/2" NPT
- Retracted Length 29"
- Crosstube Ends
- Width 2"
- Width 3.25"
- Pin Holes 1 1/4"
- Shpg. 62 lbs.

4" x 20" x 2"



ITEM 9-8750

\$239.99

SPECIFICATIONS

- New, Double acting
- Bore x Stroke 4" x 20"
- Pressure 3000 PSI max.
- Rod dia. 2"
- Ports JIC 6 male
- Retracted lgth. 29 3/4"
- Rod crosstube 9 1/4" w.
- Base tang 2 1/2" thick
- Pin holes rod 1 3/4", base 1"
- Shpg. 68 lbs.

4" x 22" x 1.75"



ITEM 9-9245

\$189.95

SPECIFICATIONS

- Unused old inventory
- Double-Acting
- Bore x Stroke 4" x 22"
- Pressure 3000 PSI max.
- Rod Dia. 1 3/4"
- Ports SAE 10
- Retracted Length 36 3/8"
- Rod End Clevis
- Pin Hole 3/4"
- Base End Ball Joint Socket (Half)
- Ball Dimensions 2 1/2" dia.
- Bolt Holes Two 5/8"-18 tapped holes on 3 1/2" centers
- Shpg. 65 lbs.

4" x 24" x 1.75"



ITEM 9-12269

\$129.95

SPECIFICATIONS

- Trunnion (gimble) mount cylinder used on many popular brands of log splitters.
- New, Double Acting
- Double Acting
- Bore x Stroke 4" x 24"
- Pressure 3000 PSI max.
- Push Force 18.84 Tons
- Rod Dia. 1.75"
- Ports SAE 8
- Retracted Length 3 1/8" (center of rod pin hole to center of trunnion pin)
- Overall Length 30 1/2" (base end to center of pinhole)
- Rod End: Width 1 1/2" Pin Hole 9/16"
- Trunnion Male
- Pin Outside Width 8.46"
- Pin Inside Width 5.60"
- Pin Diameter 1 1/2"
- Pin Length 1 1/16"
- Shpg. 54 lbs.

4" x 24" x 2"



ITEM 9-8867

\$295.30

SPECIFICATIONS

- WOLVERINE by PRINCE hydraulic cylinder. Ideal for log splitter applications.
- Brand New
- Double acting
- Bore x Stroke 4" x 24"
- PSI Max. 3,000
- Rod End Thru-Hole
- Pin hole 9/8"
- Base End Clevis
- Inner width 1 1/8"
- Outer width 2 5/8"
- Pin hole 1"
- Rod Dia. 2"
- Ports SAE 8
- Retracted length 32"
- Shpg. 68 lbs.

4" x 28" x 2.25"



ITEM 9-8752

\$249.99

SPECIFICATIONS

- New, Double acting
- Bore x Stroke 4" x 28"
- Pressure 4000 PSI max.
- Rod dia. 2 1/4"
- Ports SAE 8
- Retracted lgth. 39"
- Crosstube ends rod 4" w., base 4 3/4" w.
- Pin holes 1 1/4"
- Shpg. 102 lbs.

4" x 30" x 2"



ITEM 9-12792

\$299.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 30"
- Pressure 3000 PSI
- Rod Dia. 2"
- Ports SAE 12
- Retracted Length 40.25"
- Crosstube Ends
- Width 3"
- Pin Holes 1"
- Shpg. 95 lbs.

4" x 42" x 1.5"



ITEM 9-12466

\$189.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 4" x 42"
- Pressure 3000 PSI max.
- Rod Dia. 1.5"
- Retracted Length 56"
- Rod End: Tang Thickness, Max 2.75"
- Pin Hole 2.14"
- Base End: Clevis Pin Hole 1 1/4"
- Shpg. 80 lbs.

4" x 44.125" x 2.75"



ITEM 9-20244-A

\$399.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 4" x 44.125"
- Pressure 3000 PSI
- Rod dia. 2.75"
- Extend Ports SAE 6
- Retract Ports SAE 8
- Retracted Length 57.5"
- Swivel Eye Ends
- Rod End Width 2.04"
- Base End Width 1.98"
- Swivel Eye Width 1.375"
- Pin Hole 1 1/2"
- Shpg. 234 lbs.

Truck freight only.

4" x 45" x 2"



ITEM 9-7810

\$349.95

SPECIFICATIONS

- New, double acting
- Bore x stroke 4" x 45"
- Pressure 3000 PSI max.
- Rod dia. 2"
- Ports SAE 16/12 Ext/Ret
- Retracted lgth. 63"
- Rod tang w/ swivel ball O.D. 4 9/16"
- Base tang 4" wide
- Pin holes 2"
- Shpg. 214 lbs.

Truck freight only.