




3 Bolt Mount

• New White Drive Products low speed high torque motors. Interchangeable with many different brands of similar type motors. Pictures are representative of motors. More information including pictures and additional specifications can be found on website.



2 Bolt Mount



4 Bolt Mount

Item	Model	Displ PS Torque RPM GPM					Mount	Shaft	Ports	Shpg.	Price
		cu. In.	Cont.	Cont.	Cont.	Cont.					
9-12499-A	145032A11B1AAAAA	1.9	1450	372	1244	16	2-bolt SAE A	1" keyed	SAE 10	14 lbs.	\$119.95
9-8837-A	276040F3114AAAAA	2.5	2000	630	830	9	4-bolt square	1" tapered keyed threaded	SAE 10	18 lbs.	\$169.99
9-8831-D	155060F3153AAAAAC	3.6	2320	1106	1185	16	4-bolt square	1" w/crosshole	SAE 10	16 lbs.	\$129.99
9-8834-B	255060F3705AAAAA	3.6	2250	1221	890	14	4-bolt square	1" w/crosshole	Manifold	14 lbs.	\$149.99
9-12499-F	155060A17B1AAAAA	3.6	2320	1106	1185	16	2-bolt SAE A	1" keyed	Manifold	16 lbs.	\$129.95
9-8825	276070A1710AAAAA	4.3	2000	1120	650	12	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.99
9-12499-B	155100A17B1AAAAA	5.9	2320	1726	720	16	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.95
9-12499-J	155100A1102AAAAA	5.9	2320	1726	728	16	2-bolt SAE A	1" 6T spline	SAE 10	18 lbs.	\$129.95
9-12499-D	255100A1710AAAAA	6.1	3000	2122	610	16	2-bolt SAE A	1" keyed	Manifold	20 lbs.	\$129.95
9-8632-X	255130A1316BAAAA	7.9	2500	2797	472	16	2-bolt SAE A	25mm keyed	1/2" BSPP and Manifold	18 lbs.	\$119.99
9-8632-Y	255130A1901ABAAA	7.9	2500	2797	472	16	2-bolt SAE A	7/8" 13T spline	SAE 10	18 lbs.	\$119.99
9-8672-H	281130A6321BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	1/2" BSPP and Manifold	18 lbs.	\$139.99
9-8672-G	281130A6821BAAAA	7.9	2000	2135	350	12	2-bolt SAE A	32mm keyed	1/2" BSPP	16 lbs.	\$139.99
9-12499-C	155160A17B1AAAAA	9.4	2320	2840	452	16	2-bolt SAE A	1" keyed	Manifold	18 lbs.	\$129.95
9-8673	155200A6310BAAAA	11.6	2180	3365	367	16	2-bolt SAE A	1" keyed	1/2" BSPP and Manifold	18 lbs.	\$139.99
9-8632-CCC	255200A1001AAAAA	12.1	2500	4088	308	16	2-bolt SAE A	7/8" 13T spline	1/2" NPT	20 lbs.	\$149.99
9-8834-I	255200A1713AAAAA	12.1	2500	4088	308	16	2-bolt SAE A	1" keyed	1/2" BSPP and Manifold	20 lbs.	\$129.99

### 1.53 cu in Hydraulic Motor



ITEM 9-8915  
**\$129.95**

• New, SALAMI model# 2,5MB25R-R55S3-MOTOR hydraulic motor. Aluminum body.

**SPECIFICATIONS**

- Displacement 1.53 cu. in. / rev.
- Motor Type Gear
- Rotation Reversible
- Pressure: 3625 PSI cont. 4060 PSI int.
- Torque: 883 in-lbs. @ 3625 PSI 989 in-lbs. @ 4060 PSI
- Speed: 3000 RPM max.
- 500 RPM min.
- Flow: 24 GPM @ 3625 RPM 26.9 GPM @ 4060 RPM
- Mount Two-bolt SAE B
- Shaft 7/8" dia. x 1 1/2" long 13T spline
- Inlet Port SAE 16
- Outlet Port SAE 12
- Case Drain SAE 4
- Size 4 3/4" x 6 7/8" x 5 1/2"
- Shpg. 11 lbs.

### 4.45 cu in Hydraulic Motor



ITEM 9-12235-B **\$104.95**

• New. Low speed high torque motor that incorporates an industry proven spool valve design and high performance gerotor power element.

**SPECIFICATIONS**

- Brand Brevini
- Model FH0073AS100AAAA
- Family FH Series
- Displacement 4.45 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 1900 PSI cont. 2400 PSI int.
- Torque: 1020 in-lbs. cont. 1332 in-lbs. int.
- Speed: 820 RPM cont. 1025 RPM int.
- Flow: 15 GPM cont. 20 GPM int.
- Mount 2 bolt SAE A
- Pilot Mount Size 3.25"
- Shaft 1" dia. x 1.89" long w/ 1/4" keyway
- Ports SAE 10
- Case Drain None
- Size 5.42" x 5.10" x 3.81"
- Shpg. 15 lbs.

### 6.16 cu in Hydraulic Motor



ITEM 9-12235-D **\$109.95**

• New Brevini.

**SPECIFICATIONS**

- Displacement 6.16 cu. in. / rev.
- Rotation Reversible
- Pressure: 1900 PSI cont. 2400 PSI int.
- Torque: 1416 in-lbs. cont. 1764 in-lbs. int.
- Speed: 590 RPM cont.
- 740 RPM int.
- Flow: 15 GPM cont. 20 GPM int.
- Mount 4 bolt on 2.32" b.c
- Shaft 1" dia. x 1.89" long w/ 1/4" keyway
- Ports SAE 10
- Size 5.54" x 3.29" x 3.39"
- Shpg. 15 lbs.

### 2.13 cu in Hydraulic Piston Motor



ITEM 9-12810  
**\$169.95**

• New, AUBURN GEAR model# A6VM-107DA1/63W-VZB027B hydraulic piston motor. Variable displacement axial piston motor. Pilot operated servo valve on motor controls speed. Crossover to Danfoss LC 35,15cc min.

**SPECIFICATIONS**

- Disp. Range 0.92-2.13 cu. in. / rev.
- Control Valve: Pilot operated
- Pilot Control Valve Pressure: 203-1000 PSI
- Motor Type: Piston
- Pressure: 2030 PSI Cont. 4350 PSI Max.
- Flow 33 GPM max.
- Power
- Torque
- Speed 5300 RPM max.
- Rotation Reversible
- Mount: 2 bolt on 155mm (6.1") bolt circle with 165mm (5.315") pilot
- Pilot Extension: 83mm (3.267")
- Shaft 1" dia. 15 tooth spline x 1.25" long
- Work Ports SAE 12
- Pilot Control Port SAE 6
- Case Drain SAE 4
- Size 11 1/2" x 7 1/2" x 13 1/4"
- Shpg. 36 lbs.

### 6.1 cu in Hydraulic Motor



ITEM 9-12500 **\$189.95**

• New. EXTREME low speed high torque hydraulic motor.

**SPECIFICATIONS**

- Brand Extreme
- Model EXT-M598WMB
- Displacement 6.1 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3045 PSI cont. 4350 PSI int.
- Torque: 2564 in-lbs. cont. 3359 in-lbs. int.
- Speed: 742 RPM cont. 924 RPM int.
- Flow: 20 GPM cont. 25 GPM int.
- Mount 4 bolt magneto
- Shaft 1 1/4" dia. x 2.08" long 14T splined, tapped 3/8"-16
- Ports SAE 10
- Case Drain None
- Size 7.75" x 5.34" x 3.75"
- Shpg. 27 lbs.

### 6.5 cu in Hydraulic Piston Motor



ITEM 9-12680  
**\$599.95**

• New, REXROTH model# A6VM-107DA1/63W-VZB027B hydraulic piston motor. Variable displacement bent axis piston motor for use in open and closed loop hydraulic systems. Pilot operated servo valve on motor controls speed and direction from 1.9 to 6.5 cu. in. per revolution.

**SPECIFICATIONS**

- Disp. Max. 6.5 cu. in. / rev.
- Disp. Pilot Control Valve Setting Range 1.9 cu. in. / rev. to 6.5 cu. in. / rev
- Control Valve Pilot operated
- Motor Type Piston
- Pressure 6000 PSI max.
- Pilot Control Valve Pressure 348 PSI
- Flow 100 GPM max.
- Power 339 HP @ 3550 RPM, 5800 PSI (calculated)
- Torque 502 ft-lbs. @ 3550 RPM, 5800 PSI
- Speed 3600 RPM max.
- Rotation Reversible
- Mount Four bolt on 200mm (7.874") bolt circle with 160mm (6.299") pilot
- Shaft 40mm dia. 18T spline, DIN 5480 W40x2x30x18x9g
- Ports Size 16 4 bolt flange 27.8mm (1.094") x 57.2mm (2.25") bolt centers w/25mm (1") port
- Control Ports M12x1.5 with GE-8LM steel line adapters
- Case Drain M18x1.5
- Size 11 1/2" x 7 1/2" x 13 1/4"
- Shpg. 165 lbs.

Truck freight only.