



5.4 cu in Hydraulic Motor

ITEM 9-8837-B
\$149.99

• New, WHITE DRIVE PRODUCTS hydraulic motor. Model 276090W3114AAAEG

SPECIFICATIONS

- Motor Type Roller Stator
- Rotation Reversible
- Pressure: 2000 PSI cont. 2750 PSI cont.
- Torque: 1430 in.-lbs. cont. 1985 in.-lbs. int.
- Speed: 520 RPM cont. 650 RPM int.
- Flow: 12 GPM cont. 15 GPM int.
- Mount Four-bolt wheel
- Shaft 1" tapered x 2 3/16" shaft w/ 1/4" key and threaded end w/ castle nut
- Ports SAE 10 Side Ports, Aligned
- Case Drain None
- Size 4.53" x 4 7/8" x 4 7/8"
- Shpg. 20 lbs.



9.7 cu in Hydraulic Motor

ITEM 9-12501
\$199.95

• New, EXTREME low speed high torque hydraulic motor.

SPECIFICATIONS

- Brand Extreme
- Model EXT-M561WNB
- Displacement 9.65 cu. in. / rev.
- Motor Type Gerotor
- Rotation Reversible
- Pressure: 3045 PSI cont. 3770 PSI int.
- Torque: 4058 in.-lbs. cont. 4685 in.-lbs. int.
- Speed: 460 RPM cont. 713 RPM int.
- Flow: 20 GPM cont. 30 GPM int.
- Mount 4 bolt magneto
- Shaft 1 1/4" dia. x 2.08" long 14T splined, tapped 3/8"-16
- Ports SAE 10
- Case Drain None
- Size 7.25" x 5.34" x 3.75"
- Shpg. 25 lbs.

Super Savings On Hydraulic Hose

• New, one-wire braided SAE 100R17 hydraulic hose assemblies. NPT solid male pipe fittings on each end. 3000 PSI Working Pressure.



3/8" ID Hose with 3/8" NPTM Fittings



ITEM	Lgth.	Shpg.	Price
9-12819-24	24"	1 1/4 lbs.	\$4.95
9-12819-36	36"	1 1/2 lbs.	\$5.95
9-12819-48	48"	1 1/2 lbs.	\$6.95
9-12819-72	72"	2 lbs.	\$7.95
9-12819-108	108"	5 lbs.	\$9.95
9-12819-120	120"	6 lbs.	\$10.95
9-12819-144	144"	7 lbs	\$12.95

Hydraulic Rotary Actuator

ITEM 9-12814
\$399.95



• New, HELAC T30 hydraulic rotary actuator. Sliding-spline technology converts linear piston motion into rotary motion. Dual spline output shafts. High torque, high bearing capacity, self braking and dual counterbalance valve. Foot or side mount. Includes two spline shaft couplers for welding on various attachment arms or shafts. Can drive off one or both output shafts.

SPECIFICATIONS

- Model T30-27-E-FT-220/200-DS-C-H
- Operating Torque 27000 in.-lbs.
- Holding Torque 54200 in.-lbs.
- Maximum Primary Output Torque 66% of total
- Radial and Axial Load 4500 lbs.
- Nominal Degrees Rotation 200°
- Rotation Reversible
- Displacement 44 cubic inches
- Pressure 3000 PSI
- Counter Balance Valve 1.5:1 pilot ratio with 2.5 GPM restrictor cartridge
- Mount 8 bolt 5/8"-11, 4 bolt Foot 4.25" x 10.947" bolt centers or 4 bolt Side 5.25" wide x 8.697" bolt centers
- Dual Shafts 1.812" dia. x 1.38" long 28T spline
- Shaft Couplers 2.5" diameter x 1.85" long
- Ports SAE 4
- Size 13.21" x 5.25" x 6.65"
- Shpg. 75 lbs.

12.2 cu. in. Hydraulic Motor

ITEM 9-7567
\$148.95



• New, BUCHER Hydraulics Model BRGL200A18.

SPECIFICATIONS

- Displ. 12.2 cu. in. / rev.
- Motor type geroler
- PSI 2000 cont., 2750 int.
- Torque 3350 in.-lbs. cont., 4650 in.-lbs. int.
- RPM 220 cont., 280 int.
- GPM 12 cont., 15 int.
- Rotation reversible
- Mount 2 bolt SAE A
- Shaft 25 mm dia. x 1 1/8" keyed
- Ports 1/2" BSPP
- Size 7 3/8" x 5 1/4" x 4"
- Shpg. 21 lbs.

12.4 cu. in. Hydraulic Motor

ITEM 9-9324
\$149.95



• New BUCHER HYDRAULICS

SPECIFICATIONS

- Disp. 12.4 cu. in. / rev.
- Pressure: 3000 PSI cont. 3500 PSI int.
- Torque: 4800 in.-lbs. cont. 5600 in.-lbs. int.
- Speed: 300 RPM cont.
- Flow: 370 RPM int.
- Relief Valve 1500 PSI (Adj.)
- Rotation Reversible
- Mount 2 bolt SAE A
- Shaft 1" dia. x 1.97" keyed
- Ports 1/2" BSPP
- Size 6 1/2" x 5 1/4" x 7"
- Shpg. 28 lbs.

1/2" ID Hose with 1/2" NPTM Fittings



ITEM	Lgth.	Shpg.	Price
9-12820-12	12"	1 lb.	\$3.95
9-12820-18	18"	1 lb.	\$4.95
9-12820-24	24"	1 1/4 lbs.	\$5.95
9-12820-30	30"	1 1/2 lbs.	\$6.95
9-12820-36	36"	1 1/2 lbs.	\$7.95
9-12820-48	48"	2 lbs.	\$8.95
9-12820-60	60"	2 lbs.	\$9.95
9-12820-72	72"	3 lbs.	\$10.95
9-12820-84	84"	3 lbs.	\$11.95
9-12820-96	96"	4 lbs.	\$12.95
9-12820-108	108"	5 lbs.	\$13.95
9-12820-120	120"	6 lbs.	\$14.95
9-12820-144	144"	7 lbs.	\$16.95
9-12820-180	180"	8 lbs.	\$18.95

Coupler Adapters

• Brand New SAFEWAY hydraulic coupler adapters. Allows interconnect of non-compatible tips and bodies. Shpg. 1 lb.

ITEM	Model Picture Number	End 1 Male	End 2 Female	Price
9-12780	A FAE49-56-4	ISO 5675 (Pioneer Universal Ag 1/2")	Flush Face ISO 16028	\$60.40
9-12781	B FAE56-49-4	Flush Face ISO 16028	ISO 5675 (Pioneer Universal Ag 1/2")	\$46.50
9-12782	C S25-4-1	John Deere (Old Style)	ISO 5675 (Pioneer Universal Ag 1/2")	\$19.30
9-12783	D S25-4-2	International Harvester (Old Style)	ISO 5675 (Pioneer Universal Ag I 1/2")	\$20.20
9-12784	E S25-4-3	ISO 5675 (Pioneer Universal Ag 1/2")	John Deere Cone (Old Style)	\$22.60
9-12785	F S25-4-3D	John Deere New Style ISO Casting	John Deere Cone (Old Style)	\$28.25
9-12786	G S25-4-4	International Harvester (Old Style)	John Deere Cone (Old Style)	\$23.05
9-12787	H S25-4-5	John Deere Cone (Old Style)	International Harvester (Old Style)	\$26.50
9-12788	I S25-4-6	J.I. Case Old Style	ISO 5675 (Pioneer Universal Ag 1/2")	\$22.15
9-12789	J S25-4-7	International Harvester (Old Style)	ISO 5675 (Pioneer Universal Ag 1/2")	\$23.90
9-12790	K S25-4-7D	ISO 5675 (Pioneer Universal Ag 1/2")	International Harvester (Old Style)	\$29.75
9-12791	L S25-4-9	J.I. Case Old Style	John Deere Cone (Old Style)	\$24.35

