

Humphrey Multi-Mount Air Cylinders

• New, HUMPHREY. Multi-mount style air cylinders. Aluminum construction, rated to 100 PSI working pressure. 10-32 ports.

Bore - Rod Dimensions

1/4" = 0.118" 3/8" = 0.197" 5/8" = 0.236"

Double Acting



| ITEM | Bore | Stroke | R. Lgth. | Shpg. | Price |
|---------|------|--------|----------|---------|--------|
| 4-10618 | 1/4" | 1/2" | 2.193" | 1/2 lb. | \$5.95 |
| 4-10613 | 1/4" | 3/4" | 2.443" | 1/2 lb. | \$5.95 |
| 4-10624 | 3/8" | 1/2" | 2.39" | 3/4 lb. | \$5.95 |
| 4-10631 | 3/8" | 3/4" | 2.64" | 1/2 lb. | \$5.95 |
| 4-10637 | 5/8" | 3/4" | 2.837" | 1 lb. | \$7.99 |

1.125" x 2" SA Pneumatic Cylinder



ITEM 4-1964

\$8.99

• New. SHEFFER single acting pneumatic cylinder with spring return. Numbers on cylinder ClaS2.

SPECIFICATIONS

- Single Acting
- Bore x Stroke 1.125" x 2"
- Gland Retainer Tie-Rod
- Pressure 150 PSI
- Rod Dia. 0.3125"
- Ports 1/8" NPT
- Retracted Length 5.5"
- Gland Face to Rod Pin Center 0.75"
- Rod End Threaded
- Thread Size-Pitch 5/16"-24 TPI
- Thread Length 0.5"
- Base End Flat
- Mount Dimensions Two 0.21" bolt holes on 1.125" centers
- Shpg. 1 lb.

1 1/16" x 1 1/2" DA Pneumatic Cylinder



ITEM 4-1966

\$7.99

• New. HUMPHREY double acting pneumatic cylinder. Numbers on cylinder 6-DP-1-1/2.

SPECIFICATIONS

- Double Acting
- Bore x Stroke 1 1/16" x 1 1/2"
- Pressure 150 PSI
- Rod Dia. 5/16"
- Ports 1/8" NPT
- Retracted Length 5.75"
- Gland Face to Rod Pin Center 0.625"
- Rod End Threaded
- Thread Size-Pitch 5/16"-24
- Thread Length 0.5"
- Base End Tang
- Width 0.375"
- Pin-Center-To-Tang-End 0.25"
- Pin Hole 1/8"
- Shpg. 0.5 lbs.

12 mm x 2 3/4" DA Air Cylinder



ITEM 4-1630

\$5.95

• New, FESTO Model DO-12-74-PP-SA air cylinder. Stainless steel tubing with aluminum end-caps. 10-32 ports with adapters to 1/16" hosebarbs. Rod end threaded 4 mm, 0.70" pitch. Base end-cap tapped 4 mm, 0.70" pitch. Cushions at both ends of stroke.

SPECIFICATIONS

- Double acting
- Bore 12 mm (0.472")
- Stroke 2 3/4"
- Rod dia. 4 mm (0.156")
- Press. 8 Bar (116 PSI) max
- Ports 1/16" hosebarbs
- Retracted lgth. 6 3/4" end-to-end
- Shpg. 1 lb.

Buyers Double Acting Pneumatic Cylinders

• New. BUYERS double acting pneumatic cylinder. Has a cushion valve on each end. H Models have hinge mount accessory kit. Ideal for remote tailgate latches.

SPECIFICATIONS


• Double Acting

- Gland Retainer Tie-Rod
- Pressure 200 PSI

- Ports 1/4" NPT
- Rod End Clevis w/ Jam Nut

- Base End Clevis
- Pin Holes 1/2"

| ITEM | Bore | Stroke | Rod | | Shpg. | Price |
|------------|-------|--------|-------|----------|----------|----------|
| | | | Dia. | R. Lgth. | | |
| 4-1968-6 | 2.5" | 6" | 0.75" | 14.5" | 8.5 lbs. | \$65.20 |
| 4-1968-8 | 2.5" | 8" | 0.75" | 16.5" | 8.5 lbs. | \$65.50 |
| 4-1968-8-H | 2.5" | 8" | 0.75" | 16.5" | 9.5 lbs. | \$73.65 |
| 4-1969-6 | 3.25" | 6" | 1" | 16.25" | 11 lbs. | \$92.20 |
| 4-1969-8 | 3.25" | 8" | 1" | 18.25" | 13 lbs. | \$108.65 |
| 4-1969-8-H | 3.25" | 8" | 1" | 18.25" | 14 lbs. | \$107.05 |



10" x 14" x 2" DA Air Cylinder



ITEM 4-1953

\$219.95

• New. FABCO AIR Double acting air cylinder. Premium multi-stage air cylinder equipped with stainless rod, aluminum ends, and atmospheric vents on sides of cylinder tube. Cylinder has two pistons to extend for additional force and uses one of the pistons for retract. Front flange mount with four, 26mm bolt holes on 6.5" x 13" bolt centers. Cylinder's external rod is solid and internal rod has air passages for piston stages. Number on cylinder is MPS0015178.

SPECIFICATIONS

- Double Acting
- Bore x Stroke 10" x 14"
- Gland Retainer Tie-rod
- Pressure 100 PSI
- Extend Force 15,708 lbs.
- Rod Dia. 2"
- Ports 1/2" NPT
- Retracted/Overall Length 40.0625"
- Gland Face to Rod Pin Center 4.125"
- Rod End Tapped
- Thread Size-Pitch 1 1/2"-12
- Thread Depth 1.75"
- Base End Flat
- Shpg. 196 lbs.

Truck freight only.

3/4" Bore Air Cylinders

• Used BIMBA stainless steel. Extend port in base, retract port in rod end.

SPECIFICATIONS

- Double acting
- Bore 3/4"
- PSI max. 250
- Rod diam. 1/4"
- Ports 1/8" NPT
- Threaded rod end 1/4"-28 x 1/2" long
- Nose mount threaded 5/8"-18
- Flat base 0.81" O.D.
- Shpg. 1 lb.



ITEM 4-1761-A

\$4.95

• P/N 53E743. Stroke 3/4", retracted lgth. 5" (rod end to base end).



ITEM 4-1761-B

\$4.95

• P/N 53E712. Stroke 1 5/8", retracted lgth. 5 3/8" (rod end to base end).

7/16" x 1" Double Ended



ITEM 4-1705

\$5.95

• New, BIMBA. Nose mount each end. Spring loaded to one end, only moves to one side.

SPECIFICATIONS

- Double acting w/spring return
- Bore/stroke 7/16" x 1"
- 250 PSI
- Ports 10-32
- Rod diam. 3/16" w/10-32 UNF threaded ends
- Mtg. threads 3/8"-24
- Mtg. distance 4 1/4"
- Overall length 8 1/4"
- Shpg. 1/2 lb.

Double Air Cylinder



ITEM 4-1419

\$18.99

• New, BIMBA. Two independent, double-acting cylinders connected in the middle. Four ports, two in the middle, one in each end. Both ends of body threaded 5/8"-18 RH x 3/8" long. Rod ends threaded 5/16"-24 RH x 1/2" long. Retracted length 14 7/8" from rod end to rod end.

SPECIFICATIONS

- Double acting, double cyl.
- Bore 1 1/16"
- Strokes 3" and 4"
- Rods dia. 5/16"
- Pressure 250 PSI max.
- Ports 1/8" NPT
- Mount threaded ends
- Shpg. 2 lbs.

1/4" NPT Mini Air Regulator w/gauge



ITEM 4-9094


\$5.95

• New, Campbell Hausfeld part number RE206901AV. Inline air pressure regulator with gauge.

SPECIFICATIONS

- Inlet Pressure 200 PSI max.
- Outlet Pressure Range 0-135 PSI
- Ports 1/4" NPT
- Gauge Port 1/8" NPT
- Size 3 5/8" x 1 1/2" x 2 3/4"
- Shpg. 1/2 lbs.

24 VAC Solenoid Valve



ITEM 20-1311

\$9.99

• New, ASCO. Operates on 24 VAC, 6 watts. Ports 1/8" NPT. Pressure ratings air 275 PSI, water 200 PSI, oil 150 PSI. Normally open two ways. Brass body. Size 3 1/4" x 2" x 1 1/2". Shpg. 1 1/2 lbs.