

Leeson Three Phase Motors

- Brand new LEESON fractional horsepower three phase motors with steel motor frame and base.

SPECIFICATIONS

- Voltage 208-230/460
- Service factor 1.15
- Shaft 5/8" with keyway
- RPM 1725
- Electrically reversible
- rotation
- Enclosure TEFC
- No overload protection
- Ball bearings
- Continuous duty



**7.5 HP
3500/3450/
2905 RPM
Motor**



\$199.95

ITEM 10-3089

- New, CENTURY model# TCP71006 inverter duty rated motor. 1" I.D. lifting tab included.

SPECIFICATIONS

- Power 7 1/2 HP
- Voltage 230/460 VAC
- Amperage 19/9 Amps
- Speed 3500 RPM
- Rotation Reversible
- Phase 3
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 213JM
- Face Mount Four 1/2"-13 tapped holes on 7/4" B.C., 8 3/8" pilot
- Base Mount Eight 7/16" holes on 8 1/2" x 1 1/2" x 5 1/2" x 7" centers
- Shaft 1 1/4" dia. x 4 1/4" long, Stepped down to 1" dia., Stepped down to 7/8" dia. w/ 3/16" wide keyway
- Size 16 7/8" x 15" x 10 7/8"
- Shpg. 240 lbs.

Truck freight only.

ITEM	Model	HP	Amps	Frame	Shpg	Price
10-2709	101079	1/3	1.3/0.65	56	22 lbs.	\$142.60
10-2715	102922	1/3	1.3/0.65	56C	19 lbs.	\$159.30
10-2710	100913	1/2	1.9-2/1	56	24 lbs.	\$153.20
10-2716	102917	1/2	1.9-2/1	56C	19 lbs.	\$168.40
10-2711	110034	3/4	2.8/1.4	56	22 lbs.	\$167.45
10-2717	110916	3/4	2.8/1.4	56C	22 lbs.	\$183.55
10-3091	116757	1	3.2/1.6	56	32 lbs.	\$239.95
10-3093	116745	1	3.2/1.6	56C	34 lbs.	\$261.60
10-3092	116759	1 1/2	4.8/2.4	56	43 lbs.	\$262.65
10-3094	116746	1 1/2	4.8/2.4	56C	44 lbs.	\$303.70
10-3095	116761	2	5.8/2.9	56	45 lbs.	\$305.75
10-3101	116747	2	5.8/2.9	56C	48 lbs.	\$321.00

1/2 HP Pool Pump Motor

**ITEM 10-3216
\$79.95**



- New, pool pump motor. Ideal replacement motor for pool pumps. Square flange 4 bolt pump mount on 7 1/8" bolt circle. Stainless steel shaft. Thermally protected.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 208-230/460 AC
- Amps 3/1.5
- RPM 3450
- Rotation CCW
- Phase 3
- Service Factor 1.9
- Enclosure TEFC
- Duty continuous
- Frame 56Z
- Shaft 5/8" diameter with 1/2"-20 UNF-2A threaded end
- Size 10 1/2" x 6 1/2" x 8 1/2"
- Shpg 18 lbs.



1.5 HP 3480 RPM Motor

**ITEM 10-2112
\$88.95**

- New General Electric. Open drip-proof motor with rigid base. Heavy duty cast iron body.

SPECIFICATIONS

- 1 1/2 HP
- 3480 RPM
- 230/460 AC Volts
- 3 phase
- 4/2 amps
- 1.15 Service Factor
- Reversible
- 143T Frame
- 7/8" diam x 2 1/4" keyed shaft
- 8 1/4" x 10" x 7 1/2"
- Shpg. 54 lbs.



**3 HP
1175 RPM
Motor**

**ITEM 10-115633
\$69.95**

- New take off, General Electric three phase 200/400 VAC electric motor model# 5KE184ATD303A.

SPECIFICATIONS

- Power 3 HP
- Voltage 200/400 VAC, 60 Hz
- Phase 3
- Frequency 60 Hz
- Amperage 16/8 Amps
- Speed 1175 RPM
- Rotation Reversible
- Service Factor 1.15
- Bearings Ball
- Thermal Overload
- Protection None
- Enclosure ODP
- Duty Continuous
- Frame 184T
- Rigid Base Mount
- Shaft 1 1/8" dia. x 2 3/4" with 1/4" keyway
- Size 10 1/2" x 8 1/4" x 8"
- Shpg. 84 lb.

1/2 HP 3PH Pool Pump Motor

**ITEM 10-3216-A
\$59.95**



- New, A.O. Smith pool pump motor. Square flange 4 bolt pump mount on 7 1/8" bolt circle. Thermally protected.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 208-230/460 AC
- Amps 3/1.5
- RPM 3450
- Rotation CCW
- Phase 3
- Service Factor 1.9
- Enclosure TEFC
- Duty continuous
- Frame 56Z
- Shaft 5/8" diameter with 1/2"-20 UNF-2A threaded end
- Size 10 1/2" x 7" x 9"
- Shpg 24 lbs



2 HP 3500 RPM Motor

**ITEM 10-2899
\$129.95**

- New, TECHTOP Model BL3-AL-TF-2145T-2-B-D-2-F2-TB. Heavy duty connection box on side. Deep fins for cooling. Epact rated.

SPECIFICATIONS

- Power 2 HP
- Enclosure TEFC
- Voltage 230/460 AC
- Duty continuous
- Amperage 5.42/2.71 Amps
- Frame 145T
- Speed 3500 RPM
- Mount rigid welded base
- Rotation reversible
- Shaft 7/8" dia. x 2 1/8"
- Phase 3
- w/3/16" keyway
- Service factor 1.15
- Size 11" x 9" x 7"
- Bearings ball
- Shpg. 33 lbs.



**7.5 HP 3PH
1765 RPM
Motor**

**ITEM 10-3269
\$329.95**

- New, WEG model 7.5HP042P213T NEMA premium efficiency three phase, electric motor. Inverter-rated, speed range 10:1. Cast iron frame. No thermal overload protection. Connection box on right side of motor when viewing shaft end.

SPECIFICATIONS

- Catalog Number GT1016A
- Power 7 1/2 HP
- Voltage 230/460 AC
- Amperage 18.4/9.18 Amps
- Speed 1765 RPM
- Rotation Reversible
- Phase 3
- Service Factor 1.25
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 213T
- Rigid Base Mount Four 0.41" diameter holes on 8 1/2" x 5 1/2" centers
- Shaft 1-3/8" diam. x 3 3/8" w/ 5/16" keyway
- Size 15.15" x 14.25" x 12.73"
- Shpg. 180 lbs.

Truck freight only.

1 HP 1725 RPM Motor


**ITEM 10-3193
\$69.95**



- New, Marathon Electric model# 80T17FH5212.

SPECIFICATIONS

- Power 1 HP
- Voltage 200/230 Volt AC
- Phase 3
- Frequency 50/60 Hz
- Amperage 3.8/3.2 Amps
- Speed 1410/1725 RPM
- Rotation Reversible
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 80
- Face Mount Four M6-1.0 tapped holes in motor face on 125mm B.C.
- Shaft 19mm dia. x 41mm overall length keyed
- Size 9 1/2" x 6 1/2" x 6"
- Shpg. 29 lbs.



3 HP 3510 RPM Motor

**ITEM 10-2901
\$169.95**

- New, TECHTOP Model GR3-CI-TF-182T-2-B-B-3-X1 NEMA premium inverter duty motor. Heavy finned cast iron housing.

SPECIFICATIONS

- Power 3 HP
- Enclosure TEFC
- Voltage 208/230 AC
- Duty continuous
- Amperage 8.4/7.6
- Frame 182T
- Speed 3510 RPM
- Mount rigid welded base
- Rotation reversible
- Shaft 1 1/8" dia. x 2 3/4"
- Phase 3
- w/5/16" keyway
- Service factor 1.25
- Size 12 1/2" x 8 1/2" x 9"
- Bearings ball
- Shpg. 92 lbs.