



184 TC Frame

## Leeson Single Phase Face & Base Mount TEFC Motors

• Brand new, LEESON general purpose electric motor. Face mount allows for direct coupling to pumps and gearboxes. Capacitor start and run. Steel housing. Manual reset thermal overload protection.

### SPECIFICATIONS

- Rotation reversible
- TEFC
- Phase 1



213TC & 215TC Frame

### 1800 RPM

ITEM	Catalog Number	HP	Voltage	Amps	Frame	Shaft Dia.	Service Factor	Overload Prot.	Size	Shpg.	Price
10-2886	131631.00	3	115/208-230	33.6/16.8	184TC	1 1/8"	1.0	Manual	13 15/16" x 11" x 11 1/4"	84 lbs.	\$1061.75
10-2888	131633.00	5	230	23	184TC	1 1/8"	1.0	Manual	13 15/16" x 11" x 11 1/4"	86 lbs.	\$991.40
10-2890	140807.00	7 1/2	230	33.6	215TC	1 3/8"	1.15	None	17 1/8" x 13 1/4" x 11 3/4"	171 lbs.	\$1279.00
10-2892	140678.00	10	230	40	215TC	1 3/8"	1.15	None	17 5/8" x 13 1/4" x 11 3/4"	159 lbs.	\$1290.45

### 3600 RPM



ITEM	Catalog Number	HP	Voltage	Amps	Frame	Shaft Dia.	Service Factor	Overload Prot.	Size	Shpg.	Price
10-2885	121060.00	3	230	13	145TC	7/8"	1.0	Manual	10 7/8" x 8 7/8" x 8 5/8"	51 lbs.	\$596.35
10-2887	131632.00	5	230	19.8	184TC	1 1/8"	1.15	Manual	13 15/16" x 11" x 11 1/4"	103 lbs.	\$951.60
10-2889	140694.00	7 1/2	208-230	36-32	213TC	1 3/8"	1.0	None	15 15/16" x 13 1/8" x 11 1/4"	150 lbs.	\$1116.65
10-2891*	140695.00	10	208-230	44-41.5	215TC	1 3/8"	1.0	None	18 3/4" x 13 1/8" x 11 1/4"	152 lbs.	\$1332.60

### 7.5 HP 3450 RPM 230 Volt AC Electric Motor



ITEM 10-3124  
**\$399.95**

• New, Century general purpose electric motor. Capacitor start and run. Steel housing. No thermal overload protection.

#### SPECIFICATIONS

- Power 7 1/2 HP
- Voltage 230 AC
- Amperage 33.5-3.05 Amps
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 184T
- Rigid Base Mount
- Shaft 1 1/8" diam. x 2 3/4" w/ 1/4" keyway
- Size 13" x 11 1/4" x 11"
- Shpg. 90 lbs.

### 1 1/2 HP, 115/230 VAC Grain Stirring Motor



ITEM 10-2769  
**\$389.75**

• Brand new, LEESON Model P6K17-FB18H grain stirring motor. High torque design. Designed for use in grain bins. Vertical shaft up with drain hole. Capacitor start and run motor. Steel construction. Manual overload protection.

#### SPECIFICATIONS

- Catalog # 111330.00
- Power 1 1/2 HP
- Voltage 115/208-230 AC
- Amperage 17.2/8.8-8.6
- Speed 1800 RPM
- Rotation reversible
- Phase 1
- Service factor 1.0
- Bearings ball
- Enclosure TEFC
- Duty continuous
- Frame 56HZ
- Base mount 6 hole mount on 4 7/8" x 3" to 5" centers
- Shaft 7/8" dia. x 1.31" w/ 3/16" keyway
- Size 11" x 8.89" x 8.56"
- Shpg. 45 lbs.

### 1 3/4 HP 3490 RPM Centrifugal Pump Motor



ITEM 10-2669  
**\$99.99**

• New, WEG model# .7536ES1BJPR56C capacitor-start, induction-run motor. Steel housing, stainless steel shaft. Intended for use with centrifugal pump. Thermal overload protection with automatic reset.

#### SPECIFICATIONS

- Power 3/4 HP (0.55 kW)
- Voltage 115/208-230 VAC, 60 Hz
- Amperage 10.4/5.0-5.2 Amps
- Speed 3490 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15/1.0 @ 208 VAC
- Enclosure TEFC
- Duty Continuous
- Frame B56C
- Mount Four 3/8"-16 threaded holes in motor face on 5 7/8" B.C., 4 1/2" pilot
- Shaft 5/8" dia. x 2 3/16" overall length w/ 3/16" wide x 1 1/16" long keyway
- Size 9 1/4" L x 9 1/2" W x 8 1/4" T
- Shpg. 29 lbs.

### 1 HP 1800 RPM 115/230 Volt AC Washdown Motor



ITEM 10-3117  
**\$299.95**

• New, MARATHON model D56C17W5388 washdown motor. Designed to handle high-pressure washdowns. White epoxy paint coat. Stainless steel fan and junction box covers. No thermal overload protection. Steel construction. Solid state encapsulated starting switch. Made in the USA.

#### SPECIFICATIONS

- Catalog No. N682
- Power 1 HP
- Voltage 115/208-230 AC
- Amperage 12.8/6.4 Amps
- Speed 1800 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56
- Base Mount
- Four 5/16" wide slots on 4 7/8" x 3" centers
- Shaft 5/8" dia. x 1 7/8" w/ 3/16" keyway
- Size 12 3/16" x 9 1/8" x 9"
- Shpg. 36 lbs.

### 2 HP 1740 RPM 115/230 Volt AC Washdown Motor



ITEM 10-3118  
**\$319.95**

• New, MARATHON model 182TCWW7026 epoxy coated washdown electric motor. Capacitor start and run. Steel housing. Made in the USA.

#### SPECIFICATIONS

- Catalog Number N1684
- Power 2 HP
- Voltage 115/208-230 AC
- Amperage 21/11-10.5 Amps
- Speed 1740 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 182T
- Base Mount: Four 3/8"-16 tapped holes on 5 7/8" diameter bolt circle
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 10.5" x 10" x 11"
- Shpg. 70 lbs.

### 1 HP 1730 RPM Farm Duty Motor



ITEM 10-2920  
**\$149.95**

• New, TECHTOP model RD1-RS-TF-56HC-4-B-C-1-CC-RND farm duty motor. Steel construction. Ball bearings. Capacitor start and run. Manual reset thermal overload protection.

#### SPECIFICATIONS

- Power 1 HP
- Voltage 115/208-230 VAC
- Amperage 9.8/5.5-4.9 amps
- Speed 1730 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56HC
- Mount Face 4 tapped 3/8"-16 holes on 5 7/8" dia. B.C.
- Shaft 5/8" dia. x 2 1/8" long w/ 3/16" keyway
- Size 12" x 8 5/8" x 8 1/8"
- Shpg. 43 lbs.