

1/2 HP Electric Motor

ITEM 10-3127
\$49.99

• New, AO Smith Electric model# J218-582A-LS.

SPECIFICATIONS

- Power 1/2 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3450 RPM
- Rotation CCW
- Service Factor 1.3
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 12" x 6 1/2" x 6 1/2"
- Shpg. 17 lbs.



3/4 HP 1725 RPM 115 Volt Electric Motor

ITEM 10-3204
\$129.95

• Brand new, Leeson Electric model# C6S17DB9A.

SPECIFICATIONS

- Power 2 HP
- Voltage 115/230 AC
- Amperage 23.8/11.8
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Mount 4 bolt base 4 7/8" x 3" centers
- Shaft 5/8" diam. x 2" w/ 3/16" keyway
- Size 10" x 6 7/16" x 8 15/16"
- Shpg. 33 lbs.



1 HP 3525 RPM Motor

ITEM 10-3295
\$149.95

• New, WEG electric model# ME01C0C0J0000101334 capacitor-start. Thermal overload protection with automatic reset.

SPECIFICATIONS

- Power 1 HP
- Voltage 115/208-230 AC
- Phase 1
- Frequency 60 Hz
- Amperage 12.2/6.75-6.1 Amps
- Speed 3525 RPM
- Rotation CCW
- Service Factor 1.15
- Thermal Overload Protection Automatic
- Enclosure TEFC
- Duty Continuous
- Frame E56J
- Face Mount
- Four 3/8"-16 holes on 5 7/8" Bolt Circle
- Rigid Base Mount
- Four 0.34" diam. holes on 4 7/8" x 3" centers
- Shaft 5/8" dia. x 1 3/4" w/ 7/16"-20 thread 1 1/16" long
- Size 13 1/4" x 8 1/2" x 8 1/2"
- Shpg. 38 lbs.



1/2 HP 3450 RPM Motor

ITEM 10-3272
\$79.95

• New, MARATHON model 5KC37NN501Y general purpose electric motor. Capacitor start. Steel housing. Manual reset thermal overload protection.

SPECIFICATIONS

- Catalog Number C14774
- Power 1/2 HP
- Voltage 115/208-230 AC
- Amperage 7.4/3.7 Amps
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.00
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Rigid Base Mount 4 7/8" x 3" slotted
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 7.5" x 6" x 7.5"
- Shpg. 19 lbs.



3/4 HP 3600 RPM Motor

ITEM 10-3120
\$59.95

• New, BLUFFTON MOTOR WORKS model B1244 pool pump motor. Smooth portion of shaft measures 1 9/16" from the bearing overall length 2 1/16". Automatic thermal overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 12.8/6.4 Amps
- Speed 3450 RPM
- Rotation CCW
- Phase 1
- Service Factor 1.27
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56Y
- Mount Square flange 4 bolt on 7 1/8" diam. B.C.
- Shaft 5/8" diam. x 2 1/16" w/ 1/2"-20 RH threaded end
- Size 10 7/8" x 6 5/8" x 6 5/8"
- Shpg. 24 lbs.



1 HP 3450 RPM 115/230 Volt Motor

ITEM 10-3270
\$129.95

• New, US MOTORS model C63CXFDW-1276 electric motor for pump applications. Auto reset thermal overload protection. Four hole base mount on 3" x 4 7/8" centers. Four bolt face on 5 7/8" diameter bolt circle.

SPECIFICATIONS

- Power 1 HP
- Voltage 115/208-230 VAC
- Amperage 12.8/6.6-6.4 amps
- Speed 3450 RPM
- Rotation CCW
- Phase 1Ph
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56J
- Mount Face and Base
- Shaft 5/8" diam. x 2 9/16" w/ 7/16"-20 RH threaded end
- Size 10" x 8 1/2" x 8 1/2"
- Shpg. 32 lbs.



3/4 HP 3450 RPM 115/230 VAC Motor

ITEM 10-3271
\$89.95

• New, A.O.SMITH model 7-C65AC17A01-01 general purpose electric motor. Capacitor start. Steel housing. Auto reset thermal overload protection. Heavy duty connection box on side.

SPECIFICATIONS

- Catalog Number B659
- Power 3/4 HP
- Voltage 115/208-230 AC
- Amperage 9.6/4.8 Amps
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.00
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56
- Resilient Cradle Mount 4 7/8" x 3" slotted
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 10" x 8.25" x 8.5"
- Shpg. 31 lbs.



3/4 HP 3450 RPM Jet Motor

ITEM 10-3019
\$89.95

• New, Myers model# F48Y05A03 (25051A008) thermally protected, capacitor start jet pump motor. Automatic thermal overload protection.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 AC
- Amperage 10.0/5.0 Amps
- Speed 3450 RPM
- Rotation Counterclockwise
- Phase 1
- Service Factor 1.30
- Enclosure ODP
- Duty Continuous
- Frame 48Y
- Mount Face Mount w/ Four 3/8" Holes on 7 1/4" Bolt Circle
- Shaft 5/8" dia. x 2 1/8" Overall Length, 1/2"-20 x 1/4" Long RH Threaded End
- Size 12 1/8" x 5 3/4" x 8"
- Shpg. 25 lbs.



1 1/2 HP AC Motor

ITEM 10-2641
\$129.99

• New, MARATHON model 5KC49PN2521Y electric motor. Manual thermal overload protection. Welded base mount.

SPECIFICATIONS

- Power 1 1/2 HP
- Voltage 115-230 AC
- Amperage 21.3-10.6 Amps
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Mount 4 bolt base 4 7/8" x 3" centers
- Shaft 5/8" diam. x 2" w/ 3/16" keyway
- Size 10" x 6 7/16" x 8 15/16"
- Shpg. 31 lbs.



3/4 HP Electric Motor

ITEM 10-3128
\$49.99

• New, AO Smith Electric model# J218-590B.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 11.5/5.75 Amps
- Speed 3600 RPM
- Rotation CCW
- Service Factor 1.25
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 5/8" dia. x 1 1/2" long with 1/2"-20 threaded end
- Size 10 1/2" x 6 1/2" x 6 1/2"
- Shpg. 22 lbs.



3/4 HP Electric Motor

ITEM 10-3126
\$39.95

• New, AO Smith Electric model# J218-1006.

SPECIFICATIONS

- Power 3/4 HP
- Voltage 115/230 VAC
- Phase 1
- Frequency 60 Hz
- Amperage 12.5/3 Amps
- Speed 3600 RPM
- Rotation CCW
- Bearings Ball
- Thermal Overload Protection Automatic
- Enclosure ODP
- Duty Continuous
- Face Mount Four 3/8" threaded holes in motor face on 7 1/8" B.C.
- Shaft 12mm dia. tapered x 3/4" long with M10-1.0 threaded end
- Size 12" x 8" x 8"
- Shpg. 23 lbs.



2 HP Air Compressor Motor

ITEM 10-3192
\$129.00

• Brand new, Marathon Electric model 5KCR48TN2699Y motor. High torque design for compressor duty applications. Overload protection with manual reset. Steel frame and base. Welded base. Capacitor start/capacitor run.

SPECIFICATIONS

- Power 2 HP Special
- Voltage 115/230 VAC
- Amperage 15/7.5 Amps
- Speed 3450 RPM
- Phase 1
- Rotation CCW
- Service Factor 1.0
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 56
- Mount Base
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 10 1/4" x 8" x 6 1/2"
- Shpg. 35 lbs.

