

**18 x 10.50-10 Smooth Tire and Wheel**

**ITEM 1-5511**  
**\$59.95**

• New CARLISLE SMOOTH model 1L0169 tire on yellow 4 bolt steel rim. Not for Highway Service.

**SPECIFICATIONS**

- Size 18X10.50-10
- O.D. 18.4"
- Tread Smooth
- Tread Width 6 1/2"
- Mount: 4 hole on 4" B.C. 2 1/2" dia. pilot
- Backspace 4"
- Tubeless
- Load Rating 1100 lbs. @ 24 PSI
- Ply Rating 4
- Ply Material Nylon
- Actual weight 22 lbs.
- Shpg. 30 lbs.



**13 x 5.00-6 Wheel Assembly**

**ITEM 1-4143**  
**\$16.95**

• New, tube type tire on orange painted steel wheel. Not for Highway Service. Grease zerk for axle.

**SPECIFICATIONS**

- Size 13X5.00-6
- O.D. 13"
- Tread Turf
- Tread width 4"
- Bore 3/4" diam.
- Bore Thru-Length 3"
- Pressure 30 PSI
- Hub Offset 3/4"
- Bushing Steel
- Tube Type
- Ply Rating 2 Ply
- Shpg. 8 lbs.



**4.80-8 Trailer Wheel Assembly**

**ITEM 1-5711**  
**\$19.95**

• New, WANDA JOURNEY pneumatic tire mounted on steel rim. Ideal replacement log splitter and small trailer wheel for high speed trailer use. Small trailer use only DOT R2A3 max. Grease seal and roller bearings in the hub. Dust cover NOT included.

**SPECIFICATIONS**

- Size 4.80-8
- Outside Diameter 15 3/4" dia.
- Cross Section 4 1/2" Wide
- Tread Sawtooth
- Tread Width 3"
- Bore 1"
- Bore Thru-Length 4 3/16"
- Bearing Thru-Length 3 1/2"
- Hub Type Centered
- Bearing Roller Bearing
- Tire Tubeless
- Load Rating 590 lbs. at 60 PSI, load range B
- Ply Rating 4
- Shpg. 14 lbs.



**18 x 6.50-8 Wheel Assembly**

**ITEM 1-5725**  
**\$32.99**

• New, WANDA pneumatic tire mounted on steel rim. NOT for highway service.

**SPECIFICATIONS**

- Size 18x6.50-8
- Outside Diameter 18" dia.
- Cross Section 6 1/2" Wide
- Tread Knobby
- Tread Width 5 1/2"
- Bore 1"
- Bore Thru-Length 3"
- Hub Type Centered
- Tire Tubeless
- Load Rating 330 lbs. @ 10 PSI
- Ply Rating 2
- Shpg. 16 lbs.



**13 x 5.00-6 Wheel Assemblies**

• New, tubeless tires on painted steel wheel. Grease zerk for axle. NHS.

**SPECIFICATIONS**

- Size 13X5.00-6
- O.D. 12"
- Tread Turf
- Tread width 4"
- Bore 3/4" diam.
- Bore thru-length 3"
- Pressure 30 PSI
- Hub offset 3/4"
- Bushing steel
- Tube type tubeless
- Ply rating 2 Ply
- Shpg. 8 lbs.



**4.80-8 Trailer Wheel Assembly**

**ITEM 1-5717**  
**\$32.99**

• New, WANDA pneumatic tire mounted on steel rim. Ideal replacement log splitter and small trailer wheel for high speed trailer use.

**SPECIFICATIONS**

- Size 4.80-12
- Outside Diameter 20" dia.
- Cross Section 3 3/4" Wide
- Tread Turf
- Tread Width 3 3/4"
- Mount : 5 hole on 4 1/2" B.C.
- 2 3/4" dia. pilot
- Hub Type Offset
- Tire Tubeless
- Load Rating 785 lbs. @ 60 PSI max (DOT-R2B5)
- Ply Rating 4
- Shpg. 20 lbs.



**14.5 x 7.00-6 Wheel and Tire Assembly**

**ITEM 1-5565**  
**\$19.95**

• NEW, Kenda wheel assembly. 145/70-6 size on the tire. 3/4" bore with a 3/16" keyway. Not for Highway Use.

**SPECIFICATIONS**

- Size 14.5x7.00-6
- Outside Diameter 14 3/4" dia.
- Cross Section 5 1/2" Wide
- Tread Knobby
- Tread Width 5 1/2"
- Bore 3/4"
- Bore Thru-Length 3"
- Hub Type Centered
- Bearing Plain
- Tire Tubeless
- Pressure 24 PSI max.
- Ply Rating 2
- Shpg. 9 lbs.



**5 Bolt High Speed Wheel Hub**

**ITEM 1-5718**  
**\$19.95**

• New. Use with a 1" diameter spindle to mount high speed wheels on small trailers. Includes grease cap, tapered roller bearings, seal and lug nuts.


**SPECIFICATIONS**

- Load capacity 1250 lbs.
- Mounting Five studs on 4 1/2" bolt circle
- Studs 1/2-20 UNF x 1" long
- Center housing 2 1/2" dia.
- Bearing Thru-Length 3.29"
- Hub width 4.17"
- Shpg. 7 lbs.



**Trailer Bearing Kits**

• Brand new, DURA-ROLL replacement trailer bearing kit. Use with boat, camping, utility and snowmobile trailers. 1 kit per wheel required. Bearings must be packed with grease before installation. Kit contents available at [www.surpluscenter.com](http://www.surpluscenter.com). Fully tested and exceeds VESC regulations. Installation instructions included.



**Hi-Speed Wheel Hubs**



• Brand new. Use with a 1" diameter spindle to mount high speed wheels on small trailers. Includes grease cap, tapered roller bearings and seal. **7 lbs.**

ITEM	Bolt		Type	Price
	Bolts	Circle		
1-1133	4	4"	Lug Bolt	\$26.20
1-1134	5	4 1/2"	Lug Bolt	\$27.85
1-4884	4	4"	Stud	\$26.85
1-4885	5	4 1/2"	Stud	\$28.60

**1" Trailer Spindle**

**ITEM 1-1128**

• Brand new steel trailer spindle with castle nut. 1" diam. x 8 1/2" long. **Shpg. 4 lbs.**



**8" x 5.5" Steel Wheel Rim w/Bearings**

**ITEM 1-5079**  
**\$5.99**

• New take-offs, black steel rim with dual ball bearings for 8" tires.

**SPECIFICATIONS**

- Wheel Rim Size 8" X 5.5"
- O.D. 8 7/8"
- Width 6 5/16"
- Hub 3/4" Bore x 3 1/16" wide
- Hub Type Offset
- Shpg. 8 lbs.



**Typical Axle**

ITEM	Bearing Bore		Rating (lbs.)	Shpg.	Price
	Inner	Outer			
1-3535	1"	1"	2000	1 lb.	\$14.10
1-3536	3/4"	3/4"	2000	1 lb.	\$11.65
1-3537	1 1/4"	1 1/4"	2000	1 1/2 lb.	\$14.25
1-3538	1 3/8"	1 1/16"	3500	1 lb.	\$14.60
1-3539	1 1/16"	1 1/16"	2000	1 lb.	\$14.25