

**Prince RD5000
Joystick Valves****2 Spool, 25 GPM**

w/Float

ITEM 9-4782

\$355.00**Prince**

• Brand new PRINCE RD5000 Series. Two spool joystick valve for operating double acting cylinders. Ideal for use on front end loaders, lift trucks, and other mobile equipment. The two spools can be operated independently or simultaneously depending on handle movement. First spool float. Open center. Spring centering.

SPECIFICATIONS

- 25 GPM, 3000 PSI
- Spool 1 double acting with float position
- Spool 2 Double Acting
- IN/OUT ports 3/4" NPT
- Work ports 1/2" NPT
- 3000 PSI
- Adjustable Relief Valve 1500-3000 PSI (preset at 2000 PSI)
- Overall size 7 1/2" x 3 1/4" x 11" (excluding handle)
- Shpg. 26 lbs.

**3 Spool, 25 GPM**

With Grapple Control

ITEM 9-8217

\$427.95**Prince**

• Brand new PRINCE HC-V-BP22. Three spool joystick valve for operating double acting cylinders with first spool float and third spool single lever to operate a double acting grapple cylinder. Features include monoblock gray cast iron body, hard chrome plated spools, load checks and spring centering spools. The two spools controlled by joystick lever can be operated independently or simultaneously depending on handle movement. Open center can be converted to power beyond or closed center by changing conversion plug. Ideal for use on front end loaders with a grapple or other attachments, lift trucks, and other mobile equipment.

SPECIFICATIONS

- Open Center
- Spools Three
- Flow 25 GPM max.
- Relief Valve factory set at 2000 PSI Adjustable 1500-3000 PSI
- Pressure 3000 PSI max.
- In/Out Ports SAE 12
- Work Ports SAE 10
- Mount 3 holes thru body
- Size 15" x 9 3/4" x 3 1/4"
- Shpg. 39 lbs.

Power Beyond Sleeves

- Provides oil to a downstream valve.
- Shpg. 1 lb.



ITEM 9-4895-B 3/4" NPT

\$27.00

ITEM 9-4895-B-S SAE 12

\$21.90**Closed Center Plug**

ITEM 9-4895-C

\$22.80

• Use to convert RD5000 valves to closed center. NOTE: Conversion does not allow for drain-off of standby spool leakage. This can allow a small amount of oil to enter the work ports when valve is in neutral. Shpg. 1 lb.

**2 Spool, 14 GPM Prince
Joystick Loader
Control Valve****Prince**

ITEM 9-8185

\$386.10

• Brand new PRINCE LVR1GB5AB6. Two spool joystick valve for operating double acting cylinders with float on first spool. Features include monoblock gray cast iron body, hard chrome plated spools, load checks and spring centering spools. The two spools controlled by joystick lever can be operated independently or simultaneously depending on handle movement. Open center that can be converted to power beyond by changing conversion plug. Ideal for use on front end loaders, lift trucks, and other mobile equipment.

SPECIFICATIONS

- Open Center
- Spools Two
- Flow 14 GPM max.
- Relief Valve factory set at 2000 PSI Adjustable 1500-3000 PSI
- Pressure 3000 PSI max.
- In/Out Ports SAE 10
- Work Ports SAE 8
- Mount 6 drilled/tapped holes
- Size 2 1/4" x 6 3/8" x 9 1/2"
- Shpg. 25 lbs.

Power Beyond Sleeve

ITEM 9-8185-B

\$30.10

- Provides oil to a downstream valve. Port SAE 8. Shpg. 1/2 lb.

**2 Spool, 10 GPM
Joystick Loader
Control Valve****BRAND
HYDRAULICS**

ITEM 9-7401

\$321.45

• Brand new. BRAND Model LV22RFSTKAB. Compact two spool joystick valve for operating double acting cylinders. Ideal for use on front end loaders on small to medium sized tractors, lift trucks, and other mobile equipment requiring a compact valve. The two spools can be operated independently or simultaneously depending on handle movement. First spool has regenerative feature for rapid extension of cylinder and second spool has float to allow free movement of cylinder. Open center. Optional conversion sleeve for power beyond or plug for closed center operation sold separately. Spring centering spool action with detented fourth position for float or regenerative spools.

SPECIFICATIONS

- Open Center
- Spools Two
- Flow 10 GPM
- Relief Valve Adjustable from 800-3000 PSI set at 2000
- Pressure 3000 PSI In/Out Ports SAE 8
- Work Ports SAE 8
- Size 5 1/2" x 2 3/8" x 17 7/8"
- Shpg. 14 lbs.

Power Beyond Sleeve

ITEM 9-7401-B

\$20.55

- Provides oil to a downstream valve. Port SAE 8. Shpg. 1/2 lb.

Closed Center Plug

ITEM 9-7401-C

\$20.20

- For closed center systems with variable displacement pumps. Shpg. 1/2 lb.

**Compact
Double Acting
Directional
Control Valve**

• New CHIEF directional control valve for operating double acting cylinders. Ideal for small tractors and other compact applications. Features include monoblock construction, built-in adjustable pressure relief valve, load check, spring centering spool action, open center, side inlet/outlet ports, top work ports and vertical or horizontal handle mounting.

SPECIFICATIONS

- Open Center
- Double Acting
- Spring Centering
- Flow 10 GPM max.
- Pressure 3600 PSI max.
- Relief Valve Set at 2250 PSI, adj. 1500-3600 PSI
- In/Out Ports SAE 10
- Work Ports SAE 8
- Mount 2 hole base

1 Spool

ITEM 9-12460

\$69.95

Size 8 1/4" x 3 5/8" x 2 7/16" Shpg. 8 lbs.

2 Spool

ITEM 9-12461

\$119.95

Size 8 1/4" x 5 5/8" x 2 7/16" Shpg. 12 lbs.

**2 Spool Joystick Loader
Control Valve w/Float**

ITEM 9-12475

\$189.95

• Brand new, CHIEF compact two spool joystick valve with float feature on first spool for operating double acting cylinders. Ideal for use on front end loaders on small to medium sized tractors. Open center. Load checks. Spring centering spools with detented float.

SPECIFICATIONS

- Model 220957
- Open Center
- Spools Two
- Load Checks Yes
- Flow 10 GPM
- Pressure 3600 PSI
- Relief Valve Adjustable from 1500 to 3600 PSI
- In/Out Ports SAE 10
- Work Ports SAE 8
- Size 5 1/4" x 3" x 18 1/2"
- Shpg. 12 lbs.

CHIEF Power Beyond, Closed Center Options

ITEM 9-12475-PB

\$15.75

- Power Beyond Sleeve. SAE 10. Shpg. 1/4 lb.

ITEM 9-12475-C

\$13.95

- Closed Center Plug. Shpg. 1/4 lb.

**2 Spool Joystick Loader
Control Valve w/Float**

ITEM 9-12473

\$271.00

• Brand new. Wolverine by Prince. Compact two spool joystick valve with float feature on first spool for operating double acting cylinders. Ideal for use on front end loaders on small to medium sized tractors. Open center. Includes conversion plug for power beyond or closed center use. Load checks. Spring centering spools with detented float.

SPECIFICATIONS

- Model WLVT21CGB5A1
- Open Center
- Spools Two
- Load Checks Yes
- Flow 12 GPM
- Pressure 3625 PSI
- Relief Valve Adjustable from 2000 to 3500 PSI, preset at 2500 PSI
- In/Out Ports SAE 8
- Work Ports SAE 8
- Size 5 1/2" x 2 3/4" x 18"
- Shpg. 12 lbs.