

## Humphrey Multi-Mount Air Cylinders

• New, HUMPHREY. Multi-mount style air cylinders. Aluminum construction, rated to 100 PSI working pressure. 10-32 ports.

### Bore - Rod Dimensions

1/4" = 0.118"    3/8" = 0.197"    5/8" = 0.236"

Single Acting  
Push Only



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10621	1/4"	1/4"	2.14"	1/2 lb.	\$5.95
4-10622	3/8"	1/4"	2.337"	3/4 lb.	\$5.95
4-10633	3/8"	1/2"	2.587"	3/4 lb.	\$5.95
4-10640	5/8"	1/4"	2.533"	1/2 lb.	\$6.95
4-10647	5/8"	1/2"	2.783"	3/4 lb.	\$6.95

Double Acting

ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10618	1/4"	1/2"	2.193"	1/2 lb.	\$5.95
4-10613	1/4"	3/4"	2.443"	1/2 lb.	\$5.95
4-10624	3/8"	1/2"	2.39"	3/4 lb.	\$5.95
4-10631	3/8"	3/4"	2.64"	1/2 lb.	\$5.95
4-10637	5/8"	3/4"	2.837"	1 lb.	\$7.99

Double Acting  
Double Rod



ITEM	Bore	Stroke	R. Lgth.	Shpg.	Price
4-10627	3/8"	1/2"	3.4375"	1/4 lb.	\$16.95
4-10630	3/8"	3/4"	3.902"	1/2 lb.	\$8.95
4-10649	5/8"	1/2"	3.677"	3/4 lb.	\$9.95
4-10636	5/8"	3/4"	4.177"	3/4 lb.	\$9.95

## 12 Volt DC Mini Air Pump

ITEM 4-1963  
\$6.95



• New, SKOOCOM compact diaphragm vacuum pump/compressor. Model SC5002PM.

### SPECIFICATIONS

- Voltage 12 DC
- Amperage 1.2 Amps maximum
- Air Flow 10 lpm open flow
- Pressure 23 PSI max.
- Vacuum 160 mbar max.
- Ports 3.5mm barb
- Duty Continuous
- Size 4" x 2 1/2" x 3 1/2"
- Shpg. 1 lb.

## 12 mm x 2 3/4" DA Air Cylinder



ITEM 4-1630 \$5.95

• New, FESTO Model DO-12-74-PP-SA air cylinder. Stainless steel tubing with aluminum end-caps. 10-32 ports with adapters to 1/16" hosebarbs. Rod end threaded 4 mm, 0.70" pitch. Base end-cap tapped 4 mm, 0.70" pitch. Cushions at both ends of stroke.

### SPECIFICATIONS

- Double Acting
- Bore 12 mm (0.472")
- Stroke 2 3/4"
- Rod dia. 4 mm (0.156")
- Press. 8 Bar (116 PSI) max
- Ports 1/16" hosebarbs
- Retracted lgth. 6 3/4" end-to-end
- Shpg. 1 lb.

## Double Acting Pneumatic Cylinders

• New, BUYERS double acting pneumatic cylinder. Has a cushion valve on each end. H Models have hinge mount accessory kit. Ideal for remote tailgate latches.

### SPECIFICATIONS


• Double Acting

- Gland Retainer Tie-Rod
- Pressure 200 PSI

- Ports 1/4" NPT
- Rod End Clevis w/ Jam Nut


- Base End Clevis
- Pin Holes 1/2"

ITEM	Rod				Shpg.	Price
	Bore	Stroke	Dia.	R. Lgth.		
4-1968-6	2.5"	6"	0.75"	14.5"	8.5 lbs.	\$65.20
4-1968-8	2.5"	8"	0.75"	16.5"	8.5 lbs.	\$65.50
4-1968-8-H	2.5"	8"	0.75"	16.5"	9.5 lbs.	\$73.65
4-1969-6	3.25"	6"	1"	16.25"	11 lbs.	\$92.20
4-1969-8	3.25"	8"	1"	18.25"	13 lbs.	\$108.65
4-1969-8-H	3.25"	8"	1"	18.25"	14 lbs.	\$107.05



## 7.5 CFM, Single Stage Air Compressor

ITEM 4-1916  
\$149.95



• New, V-twin cylinder single stage air compressor. Cast iron block and cylinder with aluminum head. Oil level sight glass.

### SPECIFICATIONS

- One stage, two cylinders
- Flow: 7.5 CFM open flow 4.28 CFM at 110 PSI
- Pressure 115 PSI max.
- Power reqd. 2 HP max.
- Speed 980 RPM max.
- Rotation CCW
- Flywheel 10 1/2" A belt
- Port 1/2" OD tube
- 1st stage bore/stroke 55mm x 45mm
- Mount 6 7/8" x 3 5/8"
- Size 13" x 10 1/2" x 10 1/2"
- Shpg. 37 lb.

## Air Filter Pair

ITEM 4-1930  
\$4.95



• New, pair of plastic housing air filters for air compressors. Uses paper element.

### SPECIFICATIONS

- 1/2" NPT connection
- 1/2" inlet tube
- 4" dia x 2"
- Shpg 1 lb

## 3/4" Bore Air Cylinders

• Used BIMBA stainless steel. Extend port in base, retract port in rod end.

### SPECIFICATIONS

- Double acting
- Bore 3/4"
- PSI max. 250
- Rod diam. 1/4"
- Ports 1/8" NPT
- Threaded rod end 1/4"-28 x 1/2" long
- Nose mount threaded 5/8"-18
- Flat base 0.81" O.D.
- Shpg. 1 lb.



ITEM 4-1761-A \$4.95

• P/N 53E743. Stroke 3/4", retracted lgth. 5" (rod end to base end).



ITEM 4-1761-B \$4.95

• P/N 53E712. Stroke 1 5/16", retracted lgth. 5 3/8" (rod end to base end).

## 7/16" x 1" Double Ended



ITEM 4-1705 \$5.95

• New, BIMBA. Nose mount each end. Spring loaded to one end, only moves to one side.

### SPECIFICATIONS

- Double Acting w/spring return)
- Bore/stroke 7/16" x 1"
- 250 PSI
- Ports 10-32
- Rod diam. 3/16" w/10-32 UNF threaded ends
- Mtg. threads 3/8"-24
- Mtg. distance 4 1/4"
- Overall length 8 1/4"
- Shpg. 1/2 lb.

## Double Air Cylinder



ITEM 4-1419 \$18.99

• New, BIMBA. Two independent, double-acting cylinders connected in the middle. Four ports, two in the middle, one in each end. Both ends of body threaded 5/8"-18 RH x 3/8" long. Rod ends threaded 3/16"-24 RH x 1/2" long. Retracted length 14 7/8" from rod end to rod end.

### SPECIFICATIONS

- Double Acting
- Bores 1 1/16"
- Strokes 3" and 4"
- Rods dia. 3/16"
- Pressure 250 PSI max.
- Ports 1/8" NPT UNF threaded ends
- Mount threaded ends
- Shpg. 2 lb.

## 1/4" NPT Mini Air Regulator w/gauge




ITEM 4-9094 \$5.95

• New, Campbell Hausfeld part number RE206901AV. Inline air pressure regulator with gauge.

### SPECIFICATIONS

- Inlet Pressure 200 PSI max.
- Outlet Pressure Range 0-135 PSI
- Ports 1/4" NPT
- Gauge Port 1/8" NPT
- Size 3 5/8" x 1 1/2" x 2 3/4"
- Shpg. 1/2 lbs.

## 24 VAC Solenoid Valve



ITEM 20-1311

\$9.99

• New, ASCO. Operates on 24 VAC, 6 watts. Ports 1/8" NPT. Pressure ratings air 275 PSI, water 200 PSI, oil 150 PSI. Normally open two ways. Brass body. Size 3 1/4" x 2" x 1 1/2". Shpg. 1 1/2 lbs.