



Metal Housing Pressure Switches



\$29.00 each

• Brand new, LEFOO automatic pressure switch for compressed air systems. Automatically turns electric motor ON or OFF at set values. Adjustable differential. Unloader port 1/4" OD copper tubing which allows compressor to start without back pressure load. Sturdy metal housing. Single port.

SPECIFICATIONS FOR BOTH

- Contact rating
 - Min. ON (cut-in) 40 PSI
 - Differential 25-60 PSI
 - Size 3 3/4" x 3 1/2" x 4 1/4"
- Port 1/4" NPT
- Shpg. 3 lbs.

ITEM	Factory Setting		Max. OFF (cut-out)
	ON (cut-in)	OFF (cut-out)	
4-1820-H1	145 PSI	175 PSI	250 PSI
4-1820-L1	105 PSI	135 PSI	200 PSI

Heavy Duty Automatic Pressure Switches



• Brand new, SUNNY automatic pressure switch for compressed air systems. Automatically turns electric motor ON or OFF at set values. Adjustable differential. Unloader port 1/4" OD copper tubing which allows compressor to start without back pressure load. Sturdy plastic housing. Manual off switch.

SPECIFICATIONS

- Contact ratings
 - Port(s) 1/4" NPT
 - Size 3 3/4" x 3" x 3 1/8"
- 25 amps at 120/240 VAC
- 25 amps at 32/120/230 VDC
- Shpg. 1 1/2 lbs.

ITEM	Port(s)	Factory Setting		Price
		ON (Cut-In)	OFF (Cut-Out)	
4-1823-L1	1	95 PSI	125 PSI	\$14.50
4-1823-H1	1	140 PSI	175 PSI	\$14.50
4-1823-L4	4	95 PSI	125 PSI	\$14.50
4-1823-H4	4	140 PSI	175 PSI	\$14.50

Air Pressure Switch w/Unloader & Override



ITEM 4-1797
\$8.99

• New HUBBELL ICD Model A12491 air pressure switch. Has unloader connection to allow motor to start without load. Manual lever has automatic and off positions. Bottom mounting manifold has 4 ports for connecting to tank, relief valve, gauge and hose. Open design requires a protective cover for safety (not included).

SPECIFICATIONS

- Manifold block ports four 1/4" NPT
- Unloader connection 1/4" OD tubing
- Size 3 1/2" x 3 3/4" x 3 1/2"
- Amp rating 24 amps at 120 VAC
- Preset (fixed) On 160 PSI, Off 200 PSI
- Contacts 1 pole
- Shpg. 2 lbs.

Automatic Pressure Switches

\$9.95 each

• Brand new, LEFOO automatic pressure switch for compressed air systems. Automatically turns electric motor ON or OFF at set values. Adjustable differential. Unloader port 1/4" OD copper tubing which allows compressor to start without back pressure load. Sturdy plastic housing. Manual OFF switch.

SPECIFICATIONS

- Contact ratings
 - 120 VAC: 1 1/2 HP at 20 amps
 - 240 VAC: 2 HP at 12 amps
 - 240 VAC 3 Ph.: 3 HP at 9.6 amps
 - 32 VDC: 1/4 HP at 8.6 amps
 - 120 VDC: 1/4 HP at 3.1 amps
 - 240 VDC: 1/4 HP at 1.6 amps
- Shpg. 1 1/2 lbs.



ITEM	Factory Setting		Min. On (Cut-In)	Max. OFF (Cut-Out)	Differential	Ports
	ON (Cut-In)	OFF (Cut-Out)				
4-1819-L1	95 PSI	125 PSI	35 PSI	150 PSI	30-40 PSI	1/4" NPT (x1)
4-1819-L4	95 PSI	125 PSI	35 PSI	150 PSI	30-40 PSI	1/4" NPT (x4)
4-1819-H1	140 PSI	175 PSI	50 PSI	175 PSI	35-55 PSI	1/4" NPT (x1)
4-1819-H4	140 PSI	175 PSI	50 PSI	175 PSI	35-55 PSI	1/4" NPT (x4)



ITEM 11-3044-E



ITEM 11-2576

Automatic Pressure Switches

• New automatic pressure switches. For compressed air of water systems. Automatically switch electric motor ON or OFF at pre-set values.

ITEM	HP	Voltage	Pressure (PSI)		Port	Size	Shpg	Price
			ON	OFF				
11-3044-E	1	115/230	20	40	1/4" Hosebarb	4" x 2 3/4" x 3 1/2"	2 lbs.	\$11.95
11-2576	1 1/2	115	20	40	1/4" NPT	3 1/2" x 2 1/4" x 3"	1 1/2 lbs.	\$12.99



SPDT Pressure Switches

• New surplus. WAAREE pressure switches. Use air or water. Easy screw adjustment to pressure and differential settings. Window on body to view settings. With mounting bracket.

ITEM	Model	Voltage	Pressure (PSI)		Port	Size	Shpg	Price
			ON	OFF				
11-3472-A	UT-10	120/240	72.5	87	1/4-19 JIS thread	3 1/8" x 2" x 3 3/4"	1 lbs.	\$9.95
11-3472-B	UT-16	120/240	116	145	1/4-19 JIS thread	3 1/8" x 2" x 3 3/4"	1 lbs.	\$9.95
11-3472-C	UT-30	120/240	217	290	1/4-19 JIS thread	3 1/8" x 2" x 3 3/4"	1 lbs.	\$9.95
11-3472-D	UT-6	120/240	29	45	1/4-19 JIS thread	3 1/8" x 2" x 3 3/4"	1 lbs.	\$9.95

Portable Air Carry Tanks



• Brand New IRON HORSE portable air carry tanks. Ideal for filling tires, blowing off equipment and other inflation needs when a compressor isn't handy. Features include heavy gauge steel construction, shut-off valve, filling valve, pressure gauge, 3 foot hose, tire chuck and built-in carry handle. Pressure 150 PSI max.

5 Gal. Tank
ITEM 4-1890-5
SPECIFICATIONS

- Capacity 5 gallon
- Size 17 1/2" x 9 3/4" x 11 1/2"
- Shpg. 20 lbs.

\$37.45

10 Gal. Tank
ITEM 4-1890-10
SPECIFICATIONS

- Capacity 10 gallon
- Size 22 1/2" x 12" x 14"

\$59.85

• Shpg. 34 lbs.

SPDT Pneumatic Relay

ITEM 4-1897
\$15.99



• New, ROBERTSHAW model R471-1 pneumatic relay. Sensitive to low pressure changes. Easy rotary adjustment to pressure setting.

SPECIFICATIONS

- Contacts SPDT 120/240/480 VAC
- Current 20 amps
- Pressure Range 3-25 PSI
- Differential 2 PSI fixed
- Connection 1/4" plastic tubing nipple
- Size 2 1/2" x 2 3/4" x 3 7/8"
- Shpg. 1 1/2 lbs.

1/8" NPT Bronze Air Muffler

ITEM 4-11261
.99



• New, HUMPHREY model HKM-10 brass air muffler.

SPECIFICATIONS

- Thread 1/8" NPT male
- Hex Size 7/16"
- Size 1/2" dia. x 3/4" long
- Shpg. 1/10 lb.