

### Enclosure Filter Fans

New, Pentair fresh air enclosure filter fan. High airflow and low noise for cooling electrical equipment or general air circulation. Grey plastic grill. Click-fit design installs into enclosure wall. Snap over grill with foam filter. Terminal block electrical connection.

Grill Size	Item	CFM	Voltage	Push/ Push	IP Rating	Cutout Dimensions	Size	Shpg	Price
4"	16-1546-4-B*	28	230 VAC	Pull	54	3.63" x 3.63"	4 1/8" x 4 1/8" x 2 3/8"	3 Lbs.	\$29.95
	16-1546-5-A	66	48 VDC	Pull	54	4.92" x 4.92"	5 7/8" x 5 7/8" x 2 3/4"	3 Lbs.	\$29.95
5"	16-1546-5-B	61	24 VDC	Pull	55	4.92" x 4.92"	5 7/8" x 5 7/8" x 2 3/4"	3 Lbs.	\$29.95
	16-1546-5-C	61	48 VDC	Pull	55	4.92" x 4.92"	5 7/8" x 5 7/8" x 2 3/4"	3 Lbs.	\$29.95
	16-1546-5-E	61	230 VAC	Pull	55	4.92" x 4.92"	5 7/8" x 5 7/8" x 3/4"	3 Lbs.	\$29.95
9"	16-1546-9-C***	70	48 VDC	Pull	55	6.97" x 6.97"	8 1/16" x 8 1/16" x 3 9/16"	4 Lbs.	\$39.95
10"	16-1546-10-A**	100	24VDC	Pull	54	8.78" x 8.78"	9 7/8" x 9 7/8" x 4 1/8"	6 Lbs.	\$59.95
	16-1546-10-M**	253	230 VAC	Pull	55	8.78" x 8.78"	9 7/8" x 9 7/8" x 4 3/4"	7 Lbs.	\$59.95
13"	16-1546-13-K	473	115 VAC	Pull	54	11.5" x 11.5"	12 3/4" x 12 3/4" x 6 3/4"	11 Lbs.	\$79.95
	16-1546-13-V	375	230 VAC	Push	54	11.5" x 11.5"	12 3/4" x 12 3/4" x 6 1/8"	11 Lbs.	\$79.95
	16-1546-13-X	473	230 VAC	Push	54	11.5" x 11.5"	12 3/4" x 12 3/4" x 6 1/2"	13 Lbs.	\$79.95
	16-1546-13-BB***	346	115 VAC	Pull	55	11.5" x 11.5"	12 3/4" x 12 3/4" x 6"	13 Lbs.	\$79.95



16-1546-5-A



16-1546-13-K

\*Wire leads

\*\*Black Grill

\*\*\*Paper Filter

### 230 Volt AC Ametek 3 Stage Vacuum Blower



ITEM 16-1552  
\$49.95

• New AMETEK vacuum motor blower. Intermittent duty. 3 stages Tangential bypass, cast aluminum frame.

**SPECIFICATIONS**

- Voltage 230 Volt AC
- Amps 5
- Inlet 1 1/4" dia bottom

- Discharge 1 7/8" OD, 1 1/16" ID.
- Size 6 1/2" x 6" x 8"
- Shpg 9 lbs.

### 230 Vac Motorized Impellor



ITEM 16-1459-230  
\$9.99

• New, FANS-TECH ELECTRIC model# FH133L0000. Backward curved motorized impellor. Use for cabinet cooling, air filtration systems. Air is discharged in 360° pattern around impellor. Narrow profile and vertical or horizontal mount to save space. Plastic construction. Quiet operation with high airflow. Requires 1 MFD/450 VAC run capacitor (sold separately).

**SPECIFICATIONS**

- Flow 120 CFM (estimated)
- Voltage 230 VAC, 50/60 Hz
- Amperage 0.13/0.14 A
- Power 29/31 Watts
- Speed 2700/3100 RPM
- Mounting Flange Five

- tapped holes on motor Inlet 3 1/16" dia.
- Outlet 360° around perimeter
- Size 5 1/4" dia. x 3 13/16"
- Shpg. 4 lbs.

### 160 CFM 115 VAC Centrifugal Blower



ITEM 16-1548  
\$49.95


120 VAC. FASCO model 70639814 NESCO part number 94-01-0203. Same specs as 16-1547 but motor on left when facing the output flange.

**SPECIFICATIONS**

- Flow 160 CFM
- Voltage 115 AC
- Amperage 1.0 amps
- Speed 1600 RPM
- Duty Continuous

- Mount 4 hole flange 4.13" x 1.46" centers
- Inlet 5.56" Dia.
- Outlet 2.96" x 3.33"
- Size 8.48" x 7" x 9"
- Shpg. 8 lbs.

### 115 Volt AC Draft Inducer Blower



ITEM 16-1562  
\$89.95

New, JAKEL 119278-00 part # J238-15240 draft inducer blower. Shaded pole motor with cooling fan. Metal housing and blower wheel. Attaches to side of furnace. Hose barb for 3/16 ID pressure sense tube.

**SPECIFICATIONS**

- Voltage 115 AC
- Amperage 2.1
- Speed 3000 RPM
- Duty Continuous
- Mount 5 hole flange w/

- spun fiberglass gasket
- Inlet 6 1/2" dia.
- Outlet 1 5/8" x 2 5/8"
- Size 8 1/2" x 6 1/4" x 8"
- Shpg. 6 lbs.

### 160 CFM 115 Volt AC Dual Blower



ITEM 16-1549  
\$18.95

• New, Air-dec model 60992656 centrifugal double blower. Ideal for use on corn or wood stoves and other general purpose air movement. Metal housing and plastic blower wheels. Mounting tabs on bottom and front. Shaded pole motor.

**SPECIFICATIONS**

- Flow 215 CFM max.
- Voltage 115 AC
- Amperage 1.2
- Speed 3000 RPM
- Duty Continuous
- Blower Wheels 3" dia. x 3 3/4"

- Mount 6 hole base
- Inlets 3 1/4" dia.
- Outlets 4 3/4" x 1"
- Mounts Front 13 1/2" c/c, Base 2" x 3 5/8"
- Size 4 1/2" x 14" x 4"
- Shpg. 7 lbs.

### 780 CFM 230 Volt AC Fan



ITEM 16-1546-RM  
\$79.95

• New, Pentair roof mount filter fan model SR1626424. Utilizes backward curve impellor for higher airflow. High airflow and low noise for cooling electrical equipment or general air circulation. White metal housing. Click-fit design installs into enclosure wall. Snap over grill with foam filter. 70db rating. Terminal block electrical connection.

**SPECIFICATIONS**

- Pull Type Fan
- Model Number SR1626424
- Flow 780 CFM max.
- Voltage 230 AC
- Amperage 0.73 Amps
- Power 150 Watts
- Speed 2950 RPM
- Operating Temperature Range Min. -14° F to Max. 140° F

- Mount six M6-1.0 bolts four on 11.02" x 9.84" centers two on 13.58" centers
- Cutout Dimensions 13.58" x 10.43"
- Inlet 6" Dia.
- Size 16.27" x 13.52" x 4.19"
- Shpg. 20 lbs.

### Blower Wheels

New, metal blower wheels with hub. Set-screw for motor shaft.



16-1489-B



16-1489-E

Item	Diameter	Width	Type	Rotation		Shpg	Price
				Inlet side	Bore		
16-1489-B	6 1/4"	3"	Single	CCW	1/2"	2 lbs.	\$2.99
16-1489-E	6 3/8"	5 5/8"	Double	CW	1/2"	2.5 lbs.	\$2.99
16-1489-F	6 3/4"	5 7/8"	Double	CW	1/2"	2 lbs.	\$4.99