

**Magnetic Drain Plugs**



• Brand new. Square head magnetic steel plug. Ideal for use as a drain plug in hydraulic reservoirs. **Shpg. 1/4 lb.**

**1/2" NPT**  
**ITEM 9-8096-8 \$3.50**

**3/4" NPT**  
**ITEM 9-8096-12 \$3.50**

**2" x 8" x 0.875" Single Acting Cylinder**



**ITEM 9-16084 \$39.95**

• New. International Harvester single acting cylinder. Slight corrosion on cylinder exterior from warehouse storage in the factory box.

**SPECIFICATIONS**

- Single acting
- Port 1/2" NPT
- Part Number 407155R92
- Retracted Length 20 1/4"
- Bore x Stroke 2" x 8"
- Clevis Ends
- Pressure 2000 PSI max.
- Pin Holes 1"
- Rod Dia. 7/8"
- **Shpg. 14 lbs.**

**Hydraulic Steering Valves**



• New. DANFOSS open center non reaction steering valves. **Non-load reaction** - Steering cylinder ports are blocked in neutral, locking the axle position when the operator releases the steering wheel.

**9.8 cu in**  
**ITEM 9-12919-B \$229.95**

**SPECIFICATIONS**

- Model: S10160ARAAAAAAAAAS
- Displacement 9.8 cu. in. / rev.
- Rated input flow 4-11 GPM
- Pressure 3045 PSI max.
- Load circuit Open center, non-load reaction
- Ports SAE 8
- Mount Four 3/8"-16 tapped holes on 3 1/4" B.C.
- Shaft 12T spline, 0.612" deep (no column)
- Overall size 5.75" x 3.875" x 3.25"
- **Shpg. 15 lbs.**

**19.2 cu in**  
**ITEM 9-12919-C \$229.95**

**SPECIFICATIONS**

- Model: S10315AARAAAAAAAAAS
- Displacement 19.2 cu. in. / rev.
- Rated input flow 5-16 GPM
- Pressure 3045 PSI max.
- Load circuit Open center, non-load reaction
- Filtration ISO 18-15 (NAS 3)
- Ports SAE 8
- Mount Four 3/8"-16 tapped holes on 3 1/4" B.C.
- Shaft 12T spline, 0.612" deep (no column)
- Overall size 6.5" x 3.875" x 3.25"
- **Shpg. 17 lbs.**

**3/4" NPT Outlet Tank Strainer**



**ITEM 9-12868 \$8.95**

• New, compact size tank strainer. Mount in hydraulic reservoir to keep debris from being drawn into pump. Ideal size for two stage log splitter reservoirs and other applications.

**SPECIFICATIONS**

- Tank Thread 1 1/2" NPT
- Outlet Thread 3/4" NPT
- Flow Rate 16 GPM max
- Overall Length 3 1/2"
- Screen 60 mesh (250 micron)
- Exposed Screen Size: 1 1/2" dia. x 1 9/16"
- **Shpg. 1/2 lb.**

**Square Head Magnetic Plugs**



• Brand new. Square head magnetic steel plug. Ideal for use as a drain plug in hydraulic reservoirs. **Shpg. 1/4 lb.**

**3/8" NPT**  
**ITEM 9-16098-6 \$1.50**

**1/2" NPT**  
**ITEM 9-16098-8 \$2.00**

**3/4" NPT**  
**ITEM 9-16098-12 \$2.50**

**1" NPT**  
**ITEM 9-16098-16 \$4.00**

**Hydraulic Brake**



**ITEM 9-12918-A \$89.95**  
• New. DANFOSS 9225650K3031AAAAAS hydraulic brake. Shaft length measurement is measured from back mounting face to end of shaft.

**SPECIFICATIONS**

- Holding Torque 5750 in. lbs.
- Release Pressure 290 PSI
- Max Pressure 3,000 PSI
- Release Volume 0.55 cu.in.
- Speed 250 RPM max.
- Port SAE 4
- Shaft 1 1/2" tapered dia. x 5.925" long w/ 5/16" keyway and 1 1/8"-18 threaded w/ castle nut
- Mount Four, 0.53" holes on 6.25" B.C. w/ 4" pilot
- Size 7" x 7" x 6.25"
- **Shpg. 26 lbs. lbs.**

**ITEM 9-12918-B \$69.95**  
**SPECIFICATIONS SAME AS ABOVE EXCEPT**

- Shaft 32mm tapered dia. x 5.689" long w/ 5/16" keyway and 1 1/8"-18 threaded w/ castle nut

**Remote Control Joystick Valve**




**ITEM 9-12835 \$79.95**  
• New WALVOIL SVM430 joystick lever style remote control hydraulic valve for pilot operated applications. Spring to neutral valve action that controls four plungers independently or simultaneously. Inlet port blocked in neutral. Handle has a M12-1.75 threaded end for mounting a knob. Ideal replacement valve or use on many applications to operate hydrostatic transmissions.

**SPECIFICATIONS**

- Model Series SVM430
- Model Number SVM430/41-S/01S-01138B-01154M-01138B-01154M-CRVN
- Part Number 181430057
- Closed Center
- Flow 5.28 GPM max.
- Pressure 1450 PSI max.
- In/Out Ports SAE 4
- Work Ports SAE 4
- Auxiliary Port SAE 4
- Mount Four bolt on 4.094" bolt circle
- Size 4 1/4" x 4 1/4" x 6 7/8"
- **Shpg. 9 lbs.**

**0.860 cu in Hydraulic Gear Pump**



**ITEM 9-1898-D-S \$99.95**

- New, Prince.
- .86 cu in displ
- 7.01 GPM at 2000 RPM
- 3000 PSI
- 4000 RPM max
- IN SAE 12 side
- OUT SAE 10 side
- SAE A 2 bolt mount
- CCW rotation
- 5/8" dia x 1 1/4" keyed shaft
- 5" x 4 5/8" x 4 5/8"
- **Shpg 9 lbs**

**0.97 cu in Hydraulic Pump**



**ITEM 9-12233 \$299.95**  
• New, Hydraulic piston pump w/ charge pump relief set at 290 PSI. Variable displacement axial piston pump for closed circuits with manual flow and direction control for hydrostatic systems.

**SPECIFICATIONS**

- Manufacturer SM Oleodinamica
- Model POA16LSVU-MIB1055
- Disp. 0.97 cu. in. / rev.
- Pump Type Piston
- Rotation CCW
- Mount SAE A
- Pressure: 4060 PSI max
- Speed: 3600 RPM max
- Flow: 15 GPM max
- Shaft 5/8" dia. 9 tooth x 1"
- Inlet Port SAE 8
- Outlet Port SAE 8
- Case Drain SAE 4
- Relief Port SAE 8
- **Shpg. 23 lb.**

**Flow Control Valves**



**\$73.60 Each**  
• Brand new WOLVERINE by PRINCE. Pressure compensated flow control to vary the speed of hydraulic motors. Rotate lever to vary flow to controlled flow port. Can be locked in place. Excess flow port may be plugged for use in closed center systems.

**SPECIFICATIONS**

- Pressure 3000 PSI max.
- Size 4.56" x 4.69" x 1.89"
- Mount Two 1/4" holes thru body, 3.87" c/c
- **Shpg. 9 lbs.**

ITEM	Model	Ports	GPM
9-8994-50-8	W-1950-8	1/2" NPT	0-8
9-8994-50-16	W-1950-16	1/2" NPT	0-16
9-8994-8-8	W-1908-8	SAE 8	0-8
9-8994-12-30	W-1912-30	SAE 12	0-30
9-8994-75-30	W-1975-30	3/4" NPT	0-30

**Chrome-Plated Air Breather Caps**



• Brand new, DYNAMIC FLUID COMPONENTS 40 micron screw-on air breather Chrome-plated steel cap, galvanized steel connector.

**ITEM 9-16088-4 \$11.30**

- SPECIFICATIONS**
- Connection 1/4" NPT
  - Flow 40 GPM
  - Size 1.85" dia. x 1.77"
  - **Shpg. 0.2 lbs.**

**ITEM 9-16088-6 \$11.60**

- SPECIFICATIONS**
- Connection 3/8" NPT
  - Flow 79 GPM
  - Size 1.85" dia. x 1.77"
  - **Shpg. 0.2 lbs.**

**ITEM 9-16088-8 \$11.90**

- SPECIFICATIONS**
- Connection 1/2" NPT
  - Flow 119 GPM
  - Size 3.12" dia. x 2.71"
  - **Shpg. 0.3 lbs.**

**ITEM 9-16088-12 \$17.55**

- SPECIFICATIONS**
- Connection 3/4" NPT
  - Flow 198 GPM
  - Size 3.12" dia. x 2.71"
  - **Shpg. 0.5 lbs.**

**ITEM 9-16088-16 \$18.15**

- SPECIFICATIONS**
- Connection 1" NPT
  - Flow 225 GPM
  - Size 3.12" dia. x 2.87"
  - **Shpg. 0.7 lbs.**