




Prince "Royal" Line Cylinders

Brand new, double acting welded cylinders made by PRINCE MFG. 2500 PSI working pressure. Fully chromed piston rod.



	SPECIFICATIONS: Ports %" NPT, 3/4" dia. pins.						
			Rod	Retracted			
21/2"	ITEM	Stroke	Dia.	Lgth.	Shpg.	Price	
~ /2	9-1672-08	8″	1%″	16″	20 lbs.	<i>\$252.45</i>	
	9-1672-12	12″	13⁄8″	20″	23 lbs.	<i>\$255.15</i>	
В	9-1672-16	16″	13⁄8″	24"	27 lbs.	<i>\$266.65</i>	
0	9-1672-20	20″	13⁄8″	28″	30 lbs.	<i>\$272.70</i>	
R	9-1672-24	24"	1¾″	32"	35 lbs.	<i>\$286.20</i>	
	9-1672-30	30″	13⁄8″	38″	40 lbs.	<i>\$312.55</i>	
Ε	9-1672-32	32"	13⁄8″	40"	42 lbs.	<i>\$317.25</i>	
	9-1672-36	36″	13⁄8″	44"	45 lbs.	<i>\$323.35</i>	
	9-1672-42	42"	13⁄8″	50″	52 lbs.	<i>\$344.25</i>	

	SPECIFICATIONS: Ports 1/2" NPT, 1" dia. pins.							
			Rod	Retracted				
	ITEM	Stroke	Dia.	Lgth.	Shpg.	Price		
3″	9-1650-08	8″	1½″	16″	25 lbs.	\$292.30		
	9-1650-12	12″	1½″	20″	30 lbs.	\$305.10		
_	9-1650-16	16″	1½″	24"	33 lbs.	\$310.50		
В	9-1650-20	20"	1½″	28″	37 lbs.	\$319.30		
0	9-1650-24	24"	1½″	32″	41 lbs.	<i>\$331.45</i>		
R	9-1650-30	30″	1½″	38″	47 lbs.	<i>\$355.75</i>		
	9-1650-32	32"	1½″	40"	50 lbs.	<i>\$352.30</i>		
E	9-1650-36	36″	1½″	44"	53 lbs.	<i>\$382.75</i>		
	9-1650-40	40"	1½″	48″	59 lbs.	\$392.50		
	9-1650-42	42"	1½″	50″	61 lbs.	\$402.30		
	9-1650-48	48"	1½″	56″	69 lbs.	\$448.20		



Dimensional Data for Prince "Royal" Cylinders

				Crosstube Width		
Bore	. A	В	С	L1	L2	
21/2"	29/16"	9/16″	3/4"	3″	1%″	
3″	25/16"	11/16"	1″	3½″	11/2″	
31/2"	1 11/ ₁₆ "	11/16"	1″	4"	11/2″	
4″	21/8″	¹⁵ / ₁₆ "	11/8″	4½″	2″	

	SPECIFICATIONS: Ports 1/2" NPT, 1" dia. pins.						
			Rod	Retracted			
	ITEM	Stroke	Dia.	Lgth.	Shpg.	Price	
31/2"	9-062-08	8″	1½″	16″	30 lbs.	<i>\$315.25</i>	
0/2	9-062-12	12″	1½″	20″	34 lbs.	\$330.10	
	9-062-16	16″	1½″	24"	40 lbs.	\$349.00	
В	9-062-20	20″	1½″	28"	43 lbs.	<i>\$364.50</i>	
0	9-062-24	24"	1½″	32"	47 lbs.	\$373.30	
R	9-062-30	30″	1½″	38″	51 lbs.	\$405.00	
	9-062-32	32″	1½″	40"	57 lbs.	\$415.50	
E	9-062-36	36″	1½″	44"	62 lbs.	<i>\$436.05</i>	
	9-062-40	40"	1½″	48"	66 lbs.	\$443.15	
	9-062-42	42"	1½″	50″	69 lbs.	\$464.80	
	9-062-48	48″	1½″	56″	75 lbs.	<i>\$548.80</i>	

	SPECIFICA	ATIONS: F	orts 1	⁄₂″ NPT, 1	1/4" dia. pi	ins.
			Rod	Retracted	1	
	ITEM	Stroke	Dia.	Lgth.	Shpg.	Price
	9-030-08	8″	2″	17″	43 lbs.	\$417.85
4"	9-030-12	12″	2″	21″	49 lbs.	<i>\$434.05</i>
	9-030-16	16″	2″	25"	56 lbs.	<i>\$451.60</i>
В	9-030-20	20″	2″	29″	62 lbs.	\$467.80
	9-030-24	24"	2″	33″	69 lbs.	<i>\$495.45</i>
0	9-030-30	30″	2″	39″	81 lbs.	<i>\$504.90</i>
R	9-030-32	32"	2″	41″	82 lbs.	<i>\$520.45</i>
E	9-030-36	36″	2″	45″	91 lbs.	<i>\$555.55</i>
	9-030-40	40"	2″	49"	95 lbs.	<i>\$574.45</i>
	9-030-42	42"	2″	51″	99 lbs.	<i>\$584.55</i>
	9-030-48	48"	2″	57″	106 lbs.	<i>\$639.25</i>
	9-030-60	60″	2″	69″	127 lbs.	<i>\$715.50</i>

Bore - Inside diameter of cylinder


Stroke - How far a cylinder extends out

R-length - Distance in inches between pin centers when cylinder is retracted

Rod Diameter - Diameter of cylinder rod

Single Acting - Cylinder is powered one way

Cylinder Definitions



Double Acting - Cylinder is powered both ways (two way)

Crosstube End - Round tube welded perpendicular to cylinder

Single Eye End - For mounting between two mounting ears.

Clevis End - Two mounting ears