


2.25" x 9.625" x 1.25"


ITEM 9-8390
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2 1/4" x 9 5/8"
- Pressure 3000 PSI max.
- Rod Dia. 1 1/4"
- Base to crosstube pin lgth. 17 1/8"
- Trunnion to crosstube pin lgth. 7 3/4"
- Rod crosstube 2 5/16" wide

- Pin hole 25 mm (0.984")
- Base end plain
- Trunnion outside pin width 4.96"
- Trunnion inside pin width 3.34"
- Trunnion pin size 30 mm (1.18")
- Trunnion pin lgth. 1.13"
- Shpg. 22 lbs.

\$79.99

 2.5" x .25" x 1"
 Double Acting Cylinder

ITEM 9-9803
SPECIFICATIONS

- New, Double Acting
- Double acting tie rod
- Bore x Stroke 2 1/2" x 1/4"
- Pressure 1500 PSI
- Rod Dia. 1"

- Ports 3/8" NPT
- Retracted lgth. 12 1/8"
- Rod threaded 7/8-14
- Base end blank
- Shpg. 12 lbs.

\$59.99

2.5" x 3.3125" x 1"


ITEM 9-12504
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 3.3125"
- Pressure 2000 PSI
- Rod Dia. 1"
- Extend Port SAE 6

- Retract Port SAE 4
- Retracted Length 8.75"
- Pin Holes 3/4"
- Rod End Swivel Eye Width 1"
- Base End: Thru-Hole Width 2.75"
- Shpg. 10 lbs.

\$49.95

2.5" x 6" x 1.5"


ITEM 9-20312
SPECIFICATIONS

- Unused old inventory
- Double rod
- Double Acting
- Bore x Stroke 2.5" x 6"
- Pressure 3000 PSI
- Rod Dia. 1.5

- Ports SAE 4
- Retracted Length 28"
- Tang Ends
- Rod End Width 0.636"
- Base End Width 0.623"
- Pin Holes 5/8"
- Shpg. 37 lbs.

\$129.95

 2.5" x 7" x 1.125"
 DA Rephasing Cylinder

ITEM 9-7478

- Rephasing cylinder with internal ball checks to ease cylinder start-up at both ends of stroke.

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 7"
- Pressure 2500 PSI
- Rod Dia. 1 1/8"
- Ports SAE 6
- Retracted Length 15"

- Threaded rod end 1"-16 x 1 1/2" threaded 1" across wrench flats
- Tapped base end 2 1/2" O.D.
- Tapped 1 5/8"-12 x 1 3/4" deep
- Shpg. 19 lbs.

\$49.95

2.5" x 8" x 1.25"


ITEM 9-16083
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2 1/2" x 8"
- Pressure 3000 PSI max.
- Rod Dia. 1 1/4"
- Column Load (lbs.) Full PSI

- Ports SAE 8
- Retracted Length 18 1/4"
- Clevis Ends
- Outside Widths 2.5"
- Inside Widths 1.06"
- Pin Holes 1"
- Shpg. 22 lbs.

\$139.95

2.5" x 9" x 1.25"


ITEM 9-8762

- Two common extend ports.

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2 1/2" x 9"
- Pressure 2500 PSI max.
- Rod Dia. 1 1/4"
- Port SAE 6

- Retracted Length 16"
- Crosstube Ends
- Rod End Width 2"
- Base End Width 3 1/4"
- Pin Holes 1"
- Shpg. 20 lbs.

\$89.99

2.5" x 18.5" x 1.125"


ITEM 9-13061
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.5" x 18"
- Pressure 2500 PSI
- Rod Dia. 1.25
- Ports SAE 6
- Retracted Length 27.75"

- Rod End: Clevis Pin Hole 1"
- Base End: Thru-Hole Thru-Hole Width 2.625"
- Pin Hole 1 1/2"
- Shpg. 30 lbs.

\$89.95

2.5" x 19.69" x 1.5"


ITEM 9-7164
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2 1/2" x 19 1/16"
- Pressure 3000 PSI max.
- Rod Dia. 1 1/2"
- Port SAE 6
- Retracted Length 29 1/16"

- Crosstube Ends
- Rod End Crosstube width 2 1/4"
- Base End Crosstube width 3 1/4"
- Pin Holes 1 1/8"
- Shpg. 39 lbs.

\$109.95

2.5" x 20" x 1.375"


ITEM 9-12375
SPECIFICATIONS

- Double Acting
- Bore x Stroke 2" x 20"
- Pressure 3000 PSI
- Rod Dia. 1.375"
- Ports Male JIC 6

- Retracted Length 27.125"
- Cross-Tube Ends
- Rod End Width 2"
- Pin Holes 3/4"
- Base End Width 3.25"
- Shpg. 30 lbs.

\$119.95

2.5" x 24" x 1.5"


ITEM 9-5576
SPECIFICATIONS

- New, Double Acting
- Bore/Stroke 2 1/2" x 24"
- Pressure 2500 PS
- Rod dia. 1 1/2"
- Ports SAE 8

- Retracted Length 50 1/4"
- Rod crosstube 2 3/4" wide pin hole 1 1/2"
- Base tang 1 1/2" wide pin hole 2 3/8"
- Shpg. 62 lbs.

\$109.99

ITEM 9-7696

- Same as above except 3000 PSI.

\$159.99

2.5" x 55.5" x 1.5"


ITEM 9-20481
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 2.5" x 55.5"
- Pressure 3000 PSI
- Rod Dia. 1.5"
- Ports SAE 6

- Retracted Length 64.25"
- Gland Face to Rod Pin Center 2.5"
- Tang Ends
- Widths 1"
- Pin Holes 1 1/8"
- Shpg. 75 lbs.

\$229.95

2.625" x 15" x 1.5"


ITEM 9-7025
SPECIFICATIONS

- New, double acting
- Bore/Stroke 2 5/8" x 15"
- Pressure 2500 PSI
- Rod dia. 1 1/2"

- Ports SAE 6
- Retracted lgth. 24"
- Base extension 1 1/2" diam
- Pin holes 3/4"
- Shpg. 30 lbs.

\$99.99

2.75" x 2.75" x 1.375"


ITEM 9-20484
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 2.75" x 2.75"
- Pressure 3000 PSI
- Rod Dia. 1.375"

- Ports 3/8" NPT
- Retracted Length 14.5"
- Tang Ends
- Rod End: Width 1.78"
- Base End: Width 1.81"
- Pin Holes 1 1/4"
- Shpg. 23 lbs.

\$89.95

2.75" x 6.5" x 1.375"


ITEM 9-5208
SPECIFICATIONS

- New, double acting
- Bore/Stroke 2 3/4" x 6 1/2"
- Pressure 2500 PSI
- Rod dia. 1 3/8"
- Retracted lgth. 17 3/4"

- Ports 1/4" NPT requires swivel or hose w/ flare
- Tang ends 1 3/4" wide
- Pin holes 1 3/8"
- Shpg. 30 lbs.

\$59.95

Bore - Inside diameter of cylinder**Stroke** - How far a cylinder extends out**R-length** - Distance in inches between pin centers when cylinder is retracted**Rod Diameter** - Diameter of cylinder rod**Single Acting** - Cylinder is powered one way**Double Acting** - Cylinder is powered both ways (two way)**Crosstube End** - Round tube welded perpendicular to cylinder**Single Eye End** - For mounting between two mounting ears.**Clevis End** - Two mounting ears