

2.75" x 8.75" x 1.25"



ITEM 9-9734

\$64.95

• Port block at base end of cylinder has one ball check valve.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 2¾" x 8¾"
- Pressure 3000 PSI max.
- Rod Dia. 1¼"
- Ports ¾" NPT
- Retracted Length 22¾"
- Rod End Tang w/ Swivel Eye
- Rod End Max Thickness 1¼"
- Rod End Pin Hole ¾"
- Base End Clevis
- Base End Outside Width 2½"
- Base End Inside Width 1¾"
- Base End Pin Hole 1½"
- Pin Center to Tang End 1¾"
- Base End Pin Hole 1½"
- Shpg. 33 lbs.

2.75" x 11.31" x 1.375"



ITEM 9-12793

\$79.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.75" x 11.31"
- Pressure 3000 PSI
- Rod Dia. 1.375"
- Ports ORFS 6
- Retracted Length 25"
- Rod End Clevis
- Pin Hole 1"
- Base End Swivel Eye
- Swivel Eye Width 1.09"
- Pin Hole 1¼"
- Shpg. 37 lbs.

2.75" x 15.75" x 1.75"



ITEM 9-9227

\$119.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 2¾" x 15¾"
- Pressure 3000 PSI
- Rod dia. 1¾"
- Ports SAE 4
- Retracted lgth. 40¾"
- Rod ends thru-hole, both 27/32" wide
- Pin hole ¾"
- Cylinder body mount 4 bolt 19¾" x 3½" center
- ¾"-16 tapped mtg. holes
- Shpg. 45 lbs.

2.75" x 18.25" x 1.75"



ITEM 9-8920

\$109.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2¾" x 18¼"
- Pressure 3000 PSI max.
- Crosstube Ends
- Rod End Width 3¼"
- Base End Width 3½"
- Rod Dia. 1¾"
- Pin Hole 1"
- Ports SAE 6
- Retracted Length 32½"
- Shpg. 43 lbs.

2.75" x 21.14" x 1.5"



ITEM 9-12682
SPECIFICATIONS

\$129.95

- New, Double Acting
- Bore x Stroke 2.75" x 21.14"
- Pressure 3000 PSI
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 28.75"
- Crosstube Ends
- Rod End: Width 2"
- Base End: Width 3.5"
- Pin Holes 1½"
- Shpg. 40 lbs.

2.75" x 27.75" x 2"



ITEM 9-20510

\$159.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 2.75" x 27.75"
- Pressure 3000 PSI
- Rod Dia. 2"
- Ports SAE 8
- Retracted Length 42.25"
- Crosstube Ends
- Rod End: O.D. 2.5"
- Width 2.25"
- Base End: O.D. 2.75"
- Width 3.5"
- Pin Holes 1½"
- Shpg. 72 lbs.

Double Acting Hydraulic Trunnion Cylinder

• Double acting with trunnion mount on gland end. Two SUN counterbalance valves installed on rod end manifold block.

2.75" x 186" x 2"



ITEM 9-5584

\$599.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2¾" x 186"
- Pressure 2500 PSI
- Rod Dia. 2"
- Ports SAE 8
- Base to pin retracted lgth. (pin next to gland) 211"
- Counterbalance valves set at 1000 and 1200 PS
- Trunnion to crosstube pin retracted lgth. 61½" (pin next to gland)
- Base end plain w/bracket
- Rod end steel manifold block
- Block dimensions 8¾" x 8" x 3½"
- Two pin holes 1¼"
- Pin centers 3"
- Trunnion end rectangle male pins
- Outside pin width 10½"
- Pin size 1⅞" x 2¼"
- Pin length 1¼"
- Overall lgth. 215½"
- Actual Weight 290 lbs.
- Shpg. 400 lbs.
- Truck freight only

2.76" x 16.34" x 1.57"



ITEM 9-16032

\$79.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 2.76"(70mm) x 16.34"(415mm)
- Pressure 3000 PSI
- Rod Dia. 1.57 (40mm)
- Ports M20 x 3
- Retracted Length 28.25"
- Rod End: Threaded
- Thread Size-Pitch M36 x 3
- Thread Length 3"
- Base End: Tang
- Width 1.57"
- Pin Length 1.77"(45mm)
- Shpg. 43 lbs.

3" x 4" x 1.25"



ITEM 9-16076

\$139.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 4"
- Pressure 2500 PSI
- Rod Dia. 1.25"
- Ports SAE 6
- Retracted Length 11.375"
- Gland Face to End 1.75"
- Rod End: Tapped
- Internal Thread Size ¾16UNF
- Thread Depth 1.125"
- Base End Clevis
- Outside Width 2.5"
- Inside Width 1.25"
- Pin Hole ¾"
- Shpg. 16 lbs.

3" x 4.375" x 1.25"



ITEM 9-12512

\$109.95

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 4.375"
- Pressure 3000 PSI
- Rod Dia. 1.25"
- Ports ¼" NPT
- Retracted Length 11.38"
- Rod End: Threaded 1"-14
- Thread Length 1"
- Base End: Cross-Tube
- Width 4"
- Pin Hole 1"
- Shpg. 18 lbs.

ITEM 9-12512-B

\$109.95

Same as above except Black

3" x 6.125" x 1.5



ITEM 9-2191

\$76.50

SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore/stroke 3" x 6½"
- Retracted lgth. 21¾"
- 1¾" self aligning
- Single eye both ends
- 2500 PSI
- Rod end width 2"
- Rod diam. 1½"
- Base end width 2½"
- Ports SAE 8
- Shpg. 45 lbs.

3" x 7.5" x 0.93"



ITEM 9-11656

\$69.95

SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore/Stroke 3"(76mm) x 7.5"(190mm)
- Pressure 2500 PS
- Rod dia. 0.93"
- Ports ¾" NPT
- Retracted Length 14.5"
- Rod End: Threaded
- Thread Size-Pitch 7/8"-14 TPI
- Thread Length 1.5"
- Base End: Clevis
- Outside Width 3.25"
- Pin hole 7/8"
- Shpg. 19 lbs.

3" x 7.75" x 1.5"



ITEM 9-9756

\$144.95

SPECIFICATIONS

- Unused, old inventory
- Double acting
- Bore/Stroke 3" x 7¾"
- Pressure 2500 PSI
- Rod dia. 1½"
- Ports SAE 8
- Retracted lgth. 24¾"
- Rod End Thread-on Tang
- Max Thickness 2"
- Base End Clevis
- Pin Holes 1¼"
- Shpg. 34 lbs.

3" x 10" x 1.5"



ITEM 9-12842

\$139.95

SPECIFICATIONS

- New, Double Acting
- Bore/Stroke 3" x 10"
- Pressure 3000 PSI
- Rod dia. 1.5"
- Ports SAE 8
- Retracted Length 18"
- Crosstube Ends
- Width 5"
- Pin holes 1½"
- Shpg. 30 lbs.

**Ordering Information
& Shipping Rates
on pages 108 - 109
Order Blank on page 110**