

3" x 11.625" x 1.375"

**ITEM 9-9464**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 11 5/8"
- Pressure 3000 PSI max.
- Rod Dia. 1 5/8"
- Ports SAE 6
- Retracted Length 31 3/4"
- Clevis Ends
- Pin Holes 1 1/4"
- Shpg. 43 lbs.

\$159.95

3" x 12" x 1.5"

**ITEM 9-16102**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 12"
- Pressure 3000 PSI
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 20"
- Swivel Eye Ends
- Swivel Eye Widths 1.75"
- Pin Holes 1"
- Shpg. 30 lbs.

\$149.95

3" x 15" x 1.5"

**ITEM 9-7338**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 55"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 33 lbs.

\$109.99

3" x 15" x 1.5"

**ITEM 9-7339**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99

3" x 15" x 1.5"

**ITEM 9-7340**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99

3" x 15" x 1.5"

**ITEM 9-7341**
SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 15"
- Pressure 3200 PSI max.
- Rod Dia. 1.5"
- Port SAE 8
- Retracted Length 61"
- Crosstube Ends
- Rod End Outside Width 2.69"
- Base End Outside Width 5"
- Pin Holes 1.25"
- Shpg. 60 lbs.

\$109.99

3" x 16" x 1.5"

**ITEM 9-12924**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 2500 PSI
- Rod Dia. 1.5"
- Ports SAE 8
- Retracted Length 36"
- Swivel Eye Ends
- Rod End: Width 1.71"
- Base End: Width 1.76"
- Swivel Eye Width 1.375"
- Pin Holes 1 1/2"
- Shpg. 66 lbs.

\$149.95

3" x 16" x 1.75"

**ITEM 9-10314**

• Two independent 3" x 16" x 1.75" welded cylinders joined in the middle. Four SUN model CACA-LHN adjustable, atmospherically-referenced, vented counterbalance valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1 1/8"-12
- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1 1/4"
- Ports SAE 6, See Above
- Overall Length 92 1/2"
- Shpg. 190 lbs.

\$69.95

Truck freight only

3" x 16" x 1.75"

**ITEM 9-10315**

• Two independent 3" x 16" x 1.75" welded cylinders joined in the middle. Four SUN model CACA-LHN adjustable, counterbalance valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Rod Ends Tapped
- Thread size-Pitch 1 1/8"-12
- Thread Depth 3"
- Pressure 2500 PSI max.
- Rod Dia. 1 1/4"
- Ports SAE 6, See Above
- Retracted Length 92 1/2"
- Shpg. 190 lbs.

\$69.95

Truck freight only

3" x 16" x 1.75"

**ITEM 9-10009**

• Tandem welded cylinder. Two independent cylinders joined in the middle. Four counterbalance valves. Each cylinder has two bleeder valves.

SPECIFICATIONS

- Unused, old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 3000 PSI max.
- Rod dia. 1 3/4"
- Ports SAE 6
- Overall lgh. 62"
- Rod tapped 1 1/8"-12 x 3"
- Shpg. 107 lbs.

\$69.95

3" x 16" x 2.5"

**ITEM 9-20502**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 16"
- Pressure 3000 PSI
- Rod Dia. 2.5"
- Ports SAE 10
- Retracted Length 29.5"
- Gland Face to Rod Pin Center 3.5"
- Crosstube Ends
- Rod End Width 3"
- Base End Width 4.25"
- Pin Holes 2 1/2"
- Shpg. 93 lbs.

\$109.95

See pg. 57 for new line of Wolverine by Prince swivel ball end cylinders.



3" x 19.5" x 1.5"

**ITEM 9-4789**
SPECIFICATIONS

- New, double acting
- Bore x Stroke 3" x 19 1/2"
- Pressure 2500 PSI max.
- Rod dia. 1 1/2"
- Ports SAE 12
- Retracted lgh. 34"
- Clevis ends 3 3/4" w.
- Pin holes 1 3/4"
- Shpg. 78 lbs.

\$99.50

3" x 22" x 2.5"

**ITEM 9-20504**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 22"
- Pressure 3000 PSI
- Rod Dia. 2.5"
- Ports SAE 10
- Retracted Length 41.25"
- Rod End: Swivel Eye Width 2.24"
- Swivel Eye Width 2.25"
- Base End: Crosstube Width 4.25"
- Pin Holes 2 1/2"
- Shpg. 126 lbs.

\$159.95

3" x 30.75" x 2"

**ITEM 9-9028**

• Counter-balance valve with 1.5:1 pilot ratio

SPECIFICATIONS

- Unused, old inventory
- Ports SAE 6
- Double acting
- Retracted lgh. 43 1/2"
- Bore x Stroke 3" x 30 3/4"
- Crosstube ends 4 1/8" wide
- Pressure 3000 PSI max.
- Pin holes 1 1/4"
- Rod dia. 2"
- Shpg. 82 lbs.

\$269.95

3" x 33.25" x 2"

**ITEM 9-20517**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 33.25"
- Pressure 3000 PSI
- Rod Dia. 2"
- Ports SAE 6
- Retracted Length 41.25"
- Rod End: Tapped
- Thread SizePitch 3/4"16 TPI
- Thread Depth 1.08"
- Base End: Male Trunnion Pin Outside/Inside Width 7" / 4.875"
- Pin Center To Rod Pin Center 41.25"
- Pin Center To Base End 2.75"
- Pin Dia. 1 1/2"
- Shpg. 86 lbs.

\$179.95

3" x 34" x 2"

**ITEM 9-9276**

• Manifold block has one counterbalance valve.

SPECIFICATIONS

- New, Double Acting
- Bore x Stroke 3" x 34"
- Pressure 3000 PSI max.
- Rod Dia. 2"
- Ports SAE 6
- Retracted Length 49"
- Crosstube Ends
- Rod End Width 2 1/2"
- Base End Width 3 7/8"
- Pin Holes 1 1/2"
- Shpg. 91 lbs.

\$259.95

3" x 46" x 2"

**ITEM 9-20578**
SPECIFICATIONS

- Unused old inventory
- Double Acting
- Bore x Stroke 3" x 46"
- Pressure 3000 PSI
- Rod Dia. 2"
- Ports SAE 6
- Retracted Length 61"
- Crosstube Ends
- Widths 4.5"
- Pin Holes 1 1/2"
- Shpg. 117 lbs.

\$229.95