


Peerless Six Speed Transaxles

ITEM 13-1620
\$285.75



• Brand new. PEERLESS MST-206-545C six speed transaxle. Push brake lever to actuate brake. This "Axle-Rearward" style transaxle is designed to be mounted at the rear end of the machine, behind the engine, with the transaxle axles towards the rear of the machine and the gearbox portion of the transaxle towards the front of the vehicle. Transaxles are shipped pre-filled with oil from the factory.

SPECIFICATIONS

- Brand Peerless
- Model MST-206-545C
- Speeds: Six forward, Reverse, and Neutral
- Gear ratios First 60.25:1, second 47.46:1, third 30.92:1, fourth 20.67:1, fifth 15.24:1, sixth 13.71:1, reverse 47.46:1
- Input Speed 2,000 RPM max
- Input Rotation CW
- Output Torque 225 ft-lbs max
- Load Rating 525 lbs max
- Input Shaft 5/8" dia. x 1 3/16" w/ 3/16" keyway and snap ring groove
- Axles 3/4" dia. x 4 3/4"
- long w/ 3/16" x 2 3/4" long keyway and snap ring groove
- Overall Axle Width 29 5/8"
- Tire Diameter 20" max
- Gear Shift Shaft 3/8" square, tapped 1/4"-28
- Inner Mount Four 1 1/32" bolt holes on 13" x 1 1/4" centers
- Outer Mount Four 1 1/32" bolt holes on 16 1/4" x 2 1/2" centers
- Housing Size 19 3/4" x 12 1/2" x 6 1/2"
- Brake Lever 3/4" x 1 1/2" w/ 5/16" hole for linkage
- Size 29 5/8" x 12 1/2" x 8"
- Shpg 33 lb.

w/Pull Brake Lever

ITEM 13-1621 **\$284.95**

w/Pull Brake Lever/Axle Forward

ITEM 13-1622 **\$259.35**

Hydrostatic Transaxle



ITEM 13-1607

\$339.95

• New Tuff Torq model K57R. Hydrostatic transaxle. Part #7A646084020. Vertical input for belt drive. Internal wet disc brake. Bypass lever allow vehicle to be moved without power.

SPECIFICATIONS

- Husqvarna Part 437814
- Input speed 3600 RPM max
- Max speed 5.5 mph
- Pump/Motor Displacement 7/10 cc
- Gear Ratio 23:1
- Axle Torque 150 ft.lbs.
- Max axle wt. 915 lbs.
- Input Direction CW
- Pulley 4 1/4" dia.
- Axles 3/4" diam. x 4 5/8" w/ keyway and snap ring groove
- Max Tire Size 23" dia.
- Recommended Oil 5W-50 Synthetic
- Three four-bolt mounts Inner mtg. centers: 1 3/4" x 13" Middle mtg. centers: 2 1/2" x 16 1/4" Outer mtg. centers: 2 1/2" x 17 1/4"
- Overall Size 29" x 15" x 10"
- Actual wt. 35 lbs.
- Shpg. 48 lbs.

6 Inch Heavy Duty Rubber Hood Catch

ITEM 1-5214
\$8.25



• Brand new, BUYERS PRODUCTS model WJ205 heavy duty rubber hood catch. Ideal for securing battery boxes, truck boxes and hoods. Brackets and pins included.

SPECIFICATIONS

- 6" Length
- Size 6" x 3.5" x 1.5"
- Shpg. 1/2 lb.

Aluminum High Speed Gearboxes



ITEM 13-1616-A

\$151.35

• Brand new. Peerless 1000-014-D gearbox. Cast aluminum gearbox and ships with oil. Shafts rotate in same direction when viewed from end.

SPECIFICATIONS

FOR ALL

- Ratio 1:1
- Input Power
- 10 HP continuous
- Input Speed 3600 RPM max.
- Output Torque 360 in-lbs.
- Input Shaft: 7/8" dia. x 1 1/2"
- w/ 3/16" woodruff keyway
- Output Shaft: 7/8" dia. x 1 1/4" w/ 3/32" woodruff keyway and 3/8"-24 tapped end
- Mount: Two 1 3/32" bolt holes on 4" centers, 2.92" dia. pilot
- Size 5 1/2" x 4 3/4" x 7"
- Shpg. 8 lbs.

ITEM 13-1616-B

\$157.55

Peerless 1000-015 gearbox. Shafts rotate in opposite directions when viewed from end. Shpg. 8 lbs.

3 Shaft Gearbox

ITEM 13-1616-C

\$145.35

Brand new. Peerless 1000-007 gearbox. Solid output shaft extends from both sides of case. Shpg. 9 lbs.



Hydro-Gear G700

Hydrostatic Transaxle

ITEM 13-1633
\$349.95



• New HYDRO-GEAR model G700. Hydrostatic transaxle. Part #G7-BCBB-1XDC-IFCA. Vertical input for belt drive. External disc brake. Bypass lever allow vehicle to be moved without power. Damper on controls for smooth operation. Recommended engine size 20-26 HP.

SPECIFICATIONS

- Husqvarna Part 420331
- Input speed 3600 RPM max
- Max speed 5.5 mph
- Pump/Motor Displacement 10/16 cc
- Gear Ratio 27.5:1
- Axle Torque 230 lb.ft. Continuous
- Max axle wt. 665 lbs.
- Input Direction CW
- Pulley 4 1/4" dia.
- Axles 1" diam. x 4 1/2" w/ keyway and snap ring groove
- Max Tire Size 23" dia.
- Recommended Oil 5W-50 Synthetic
- Two four-bolt mounts Inner mtg. centers: 2-12" x 13" Outer mtg. centers: 2 1/2" x 16 1/4"
- Overall Size 29 1/4" x 15" x 10"
- Actual wt. 42 lbs.
- Shpg. 48 lbs.

Peerless Differential Sprockets

• Brand new. PEERLESS sprocket for differential

SPECIFICATIONS

- Bolt Holes Four 0.35" dia. for 3/16"-18 stud
- Bolt Hole Pattern 0.941" x 1.81"



ITEM	Pitch	Bore	Teeth	O.D.	Shpg.	Price
13-1623-35-36	35	2 1/8"	36	4.51"	1/2	\$56.75
13-1623-40-45	40	2 1/8"	45	7.45"	2.5	\$56.90
13-1623-41-40	41	2 1/8"	40	6.81"	2	\$41.90
13-1623-41-48	41	2 1/8"	48	7.93"	2	\$56.00
13-1623-41-60	41	2 1/8"	60	9.84"	5	\$56.30

Peerless Differential Axles

ITEM 13-1618 **\$112.90**

3/4" Diameter

• Brand new. PEERLESS differential. Can be used with PEERLESS 700 series transmission, a gas engine, or electric motor (sold separately) for residential or commercial use. Axle is not heat treated. Used with related PEERLESS drive sprockets (sold separately).

SPECIFICATIONS

- Model 100-007B
- Axles 3/4" dia. x 16" smooth shaft
- Tire Diameter 18" max
- Output Torque 150 ft-lb max
- Load Rating 400 lb max
- Size 39 5/8" x 3 5/8" x 3 5/8"
- Shpg 11 lb.

ITEM 13-1619

\$174.70

1" Diameter

SPECIFICATIONS

- Model 100-224
- Axles 1" dia. x 14" w/ 1/4" x 6" keyway and 1/4" x 1" woodruff keyway. Axle end threaded 3/4"-16 UNF x 1 3/8"
- Output Torque 150 ft-lb max
- Tire Diameter 20" max
- Load Rating 600 lb max
- Size 38" x 3 5/8" x 3 5/8"
- Shpg 14.5 lb.

Hydrogear T2 Hydrostatic Transaxle

ITEM 13-1632
\$349.95



• New HYDRO-GEAR model T2. Hydrostatic transaxle. Part #T2-BDBE-1X2B-18X1. Vertical input for belt drive. External disc brake. Bypass lever allows vehicle to be moved without power. Recommended engine size 19 HP.

SPECIFICATIONS

- Husqvarna Part 587392201
- Input speed 3600 RPM max (no load) 1800 RPM min (loaded)
- Max speed 5.5 mph
- Pump/Motor Displacement 8/10 cc
- Gear Ratio 27.5:1
- Axle Torque 230 lb.ft. Continuous
- Max axle wt. 540 lbs. with 18" dia. tires
- Input Direction CW
- Pulley 4" dia.
- Axles 1" diam. x 5" w/ keyway and snap ring groove
- Max Tire Size 23" dia.
- Recommended Oil 5W-50 Synthetic
- Two four-bolt mounts Inner mtg. centers: 1 3/4" x 13 3/4" Outer mtg. centers: 2 1/2" x 16 1/4"
- Overall Size 29 1/4" x 15" x 10"
- Actual wt. 42 lbs.
- Shpg. 60 lbs.

Hydrostatic Transaxle Transmission

ITEM 13-1637
\$389.95



• New TUFFTORQ K46 model 7A646084591 hydrostatic transaxle. Single control for variable speed and directional control. 3 1/2" dia. input pulley with cooling fan. Internal wet disk brake. Shaft for remote lever to disengage final drive from hydrostatic unit for hand push. Outer case and axle shafts may have some corrosion from warehouse storage.

SPECIFICATIONS

- Input speed 3400 RPM max.
- Max axle wt. 675 lbs.
- Input rotation CW
- Input pulley 3 1/2" dia. for 1/2" belt
- Axles 3/4" diam. x 5 5/8" w/ dual flats, tapped 5/16"-24
- Oil Tuff Torq hydrostatic or equivalent 1.9 liter
- Axle Width 30"
- Mounting Three 4 bolt mtg. patterns
- 2 1/2" x 17 5/8"
- 2 1/2" x 16 1/4"
- 1 3/4" x 13"
- Housing Size 20" x 10" x 8 3/4"
- Actual weight 35 lbs.
- Shpg. 52 lbs. (oversize)