


Aluminum Right Angle Gear Reducers

• Brand new, World Wide Electric aluminum worm gear reducer. Aluminum alloy housings. Gearbox flanges are designed to accept NEMA C-Face electric motors. Pre-filled with synthetic oil. Two bearings on the input and output shafts, double lip oil seals, epoxy paint inside and outside for rust prevention, and hollow output bores to accept plug-in output shafts (sold separately).



60:1
\$89.95

ITEM 13-1581-60-56C-75

- SPECIFICATIONS**
- Brand World Wide Electric
 - Model Number CALM63-60/1-56C-1
 - Box Size 63 mm Center Distance
 - Gear Ratio 60:1
 - Output RPM @ 1750 RPM Input 29 RPM
 - Input HP (1.0 S.F.) 0.82 Hp Max
 - Output Torque 1135 in.-lb. Max
 - Over-Hung Load 985 lbs.
- Max**
- Output Shaft Thrust Load 197 lbs. Max
 - Efficiency 68 %
 - Motor Mount 56C
 - Hollow Output Bore 3/4" keyed, 1/4" keyway
 - Top & Bottom Mount 100mm x 85mm
 - Back Mount 130mm x 85mm
 - Overall Size 6.87" x 6.5" x 8.5"
 - Shpg. 13 lbs.



80:1
\$79.95

ITEM 13-1578-80-56C

- SPECIFICATIONS**
- Brand World Wide Electric
 - Model Number CALM30-80/1-56C
 - Box Size 30 mm Center Distance
 - Gear Ratio 80:1
 - Output RPM @ 1750 RPM Input 22 RPM
 - Input Hp (1.0 S.F.) 0.08 Hp Max
 - Output Torque 109 in.-lb. Max
 - Over-Hung Load 314 lbs.
- Max**
- Output Shaft Thrust Load 63 lbs. Max
 - Efficiency 45 %
 - Motor Mount 56C
 - Output Bore 5/8" keyed, 3/16" keyway
 - Top & Bottom Mount 54mm x 44mm
 - Back Mount 71 mm x 44mm
 - Overall Size 4.62" x 6.5" x 6.5"
 - Shpg. 3 lbs.


Hydrostatic Transmission

ITEM 13-1631 **\$229.95**

• New HYDRO-GEAR SST hydrostatic transmission. Part #1320-1008. Independent clutch for each wheel. Built for use with snowblowers having 24-36" blower width. Control lever for forward and reverse. Recommended engine size 5-13 HP.

SPECIFICATIONS

- Husqvarna Part 589288701
- Input speed 1800-2600 RPM max
- Pump/Motor Displacement 6/6 cc
- Gear Ratio 30.43:1
- Axle Torque 62 lb.ft. Continuous
- 130 lb.ft. Intermittent
- Max axle wt. 290 lbs.
- Input Direction CCW
- Pulley 4 1/4" dia.
- Axles 3/4" diam. x 2 3/4" w/ 3/16" keyway
- Max Tire Size 12-16" dia.
- Recommended Oil 5W-50 Synthetic
- Mount External Bracket
- Overall Size 10" x 6 1/2" x 9"
- Shpg. 25 lbs.



Right Angle Gearboxes

• Brand new. Right angle gearboxes. One piece cast iron gear case and bearing caps. Roller bearings. Ships without oil, user must add 1/3 quart of 80-90 W oil prior to use.



SPECIFICATIONS FOR ALL

- Ratio 1:1
- Input power 40 HP intermittent, 32 HP continuous
- Input speed 1800 RPM max.
- Output shaft 1" dia. x 2 1/4" w/ 1/4" keyway
- Mount four 3/8-16 tapped holes, 4 1/4" square
- Size 5 7/8" x 6 1/2" x 4 1/8"
- Shpg. 24 lbs.

ITEM	Input Shaft	Output rotation	Price
13-1423-KC	1" dia. x 2 1/2" w/ 1/4" keyway and 5/16" crosshole	Opposite of input	\$166.65
13-1423-SKC	1" diam. x 2 1/2" w/ 5/16" crosshole and 1/4" keyway	Same as input	\$161.80
13-1423-3K	1" dia. x 2 1/2" w/ 1/4" keyway	Dual shaft	\$199.35
13-1423-3S	1" diam. x 2 1/2" w/ 5/16" crosshole	Same as input	\$166.75



9:1 Shaft Mount Reducers

• New, AURORA shaft mount reducers. 9:1 gear ratio. Cast iron housing, high grade case hardened steel gears and shafts. Tapered roller bearings. Tapered bushing output (bushing not included). Torque arm included. Similar to Dodge or Browning. HP, torque and RPM specifications are for Class III service. May be used with accessories on previous page.

9:1 Size 4 ITEM 13-1497

- SPECIFICATIONS**
- Model DID409
 - Ratio 9:1
 - Input Power 15 HP
 - Output 132-200 RPM
 - Torque 4811-3230 in.-lbs.
 - Min Drive Pulley Diam 4.0"
 - Shpg. 160 lbs.
 - Input Shaft 1 1/16" diam. x 5" w/ 3/8" keyway
 - Output Bore see table below
 - Size 10 1/2" x 8" x 15"
 - Shpg. 160 lbs.
- Truck freight only.*

\$429.95

9:1 Size 6 ITEM 13-1498

- SPECIFICATIONS**
- Model DID609
 - Ratio 9:1
 - Input Power 30 HP
 - Output 99-200 RPM
 - Torque 4811-3230 in.-lbs.
 - Min Drive Pulley Diam 4.0"
 - Shpg. 330 lbs.
 - Input Shaft 2 3/16" diam. x 5 1/2" w/ 1/2" keyway
 - Output Bore see table below
 - Size 16" x 9 1/2" x 21"
 - Shpg. 330 lbs.
- Truck freight only.*

\$849.95


Cast Iron High Speed Gearboxes

ITEM 13-1617-A

• Brand new. Peerless gearbox. Cast iron gearbox housing ships filled with oil. Shafts rotate in opposite direction when viewed from end.

SPECIFICATIONS

- Brand Peerless
- Model 1050-009A
- Ratio 1:1
- Rotation Opposite
- Input Power 10 HP max continuous
- Input Speed 3600 RPM max.
- Output Torque 360 in-lb max
- Input Shaft 3/4" dia. x 1 5/8" w/ 3/16" woodruff keyway
- Output Shaft 3/4" dia. x 1 5/8" w/ 3/32" woodruff keyway
- Mount Two 3/8-16" bolt holes on 4" centers and 2.9" dia. pilot
- Size 7" x 5 3/4" x 4 3/4"
- Shpg. 13 lbs.



\$199.95

ITEM 13-1617-B

- SPECIFICATIONS SAME AS ABOVE EXCEPT**
- Model 1015-012
 - Ratio 1.2:1
 - Rotation Same

\$199.95

96:1 Inline Gear Reducer

ITEM 13-1586 **\$39.95**

• New, THOMSON MICRON inline speed reducer. Aluminum housing.

SPECIFICATIONS

- Nominal Ratio 96:1
- Actual Ratio 95.98:1
- Output RPM @ 1800 RPM Input 18.75 RPM
- Input Shaft 1/4" dia. x 1/2" (no keyway or flat)
- Motor Mount 2" ID housing
- Output Shaft 1/2" dia. x 5/8" long with dual flats
- Base Mount Four 0.35" holes on 5.12" x 4.33" centers
- Size 7 3/16" x 3 3/8" x 4"
- Shpg. 3 lbs.



50:1 Gear Reducer

• New, IPTS, right-angle worm gear reducer. Cast iron housing. Long output shaft. Mounts with thru holes on housing. Auxiliary 3/16" dia. x 1/2" shaft w/flat on rear of output shaft.

SPECIFICATIONS

- Ratio 50:1
- Power 0.44 HP max.
- Input Speed 1725 RPM max.
- Output Speed 35 RPM max.
- Output Torque 504 in-lb. max.
- Overhung Load 570 lbs.
- Centerline Distance 2.06"
- Input Shaft 5/8" dia. x 1 1/16" with 3/16" key
- Output Type Right hand shaft
- Output Shaft 1" dia. x 6" with 1/4" key slot
- Mount 5" x 3 3/4"
- Size 5" x 3 1/2" x 6"
- Shpg. 18 lbs.



\$69.95

1:1.93 Speed Increaser

ITEM 13-1531-A **\$266.10**

• New, OMNI GEAR series RC-51 right angle rotary cutter gearbox. Horizontal input and vertical output downward. Bevel gears. Large deep groove ball bearings to support output. Four 5/16"-18 tapped holes on 3 3/16" dia. B.C. around input shaft. Non-standard hub. Ships without oil, user must add oil prior to use per user's manual.

SPECIFICATIONS

- Model 251026C
- Rotation CCW input gives CW output
- Gear Ratio 1:1.93 Increaser
- Input RPM 540/1000
- Output RPM 1042/1930
- Input HP 24-40
- Max Torque 2800-4667 in.lbs.
- Input Shaft 1 3/8" dia. x 3" long w/ 1/2" dia. pinhole
- Output Shaft 2" dia. 15 tooth tapered spline w/ threaded end. 4 3/8" total length
- Blade Hub 3.94" dia. x 1.75" stepped down to 2.5" dia. x 1.12" then tapers down to 2.175" dia. over 0.25"
- Mount 4 holes on 6.8" dia. B.C.
- Pilot 5/4" dia.
- Size 10 1/4" x 7" x 7"
- Shpg. 59 lbs.

