



Leeson Single Phase Face & Base Mount TEFC Motors

• Brand new, LEESON general purpose electric motor. Face mount allows for direct coupling to pumps and gearboxes. Capacitor start and run. Steel housing. Manual reset thermal overload protection.



SPECIFICATIONS

- Rotation reversible
- TEFC
- Phase 1

1800 RPM * Products drop-shipped from the manufacturer are not returnable.

ITEM	Catalog Number	HP	Voltage	Amps	Frame	Shaft Dia.	Service Factor	Overload Prot.	Size	Shpg.	Price
10-2888*	131633.00	5	230	23	184TC	1 1/8"	1.0	Manual	13 15/16" x 11" x 11 1/4"	86 lbs.	\$1081.30
10-2890	141429	7 1/2	230	33.6	215TC	1 3/8"	1.15	None	17 1/8" x 13 1/4" x 11 3/4"	171 lbs.	\$1779.35
10-2892*	140678.00	10	230	40	215TC	1 3/8"	1.15	None	17 5/8" x 13 1/4" x 11 3/4"	159 lbs.	\$1694.70

3600 RPM **

ITEM	Catalog Number	HP	Voltage	Amps	Frame	Shaft Dia.	Service Factor	Overload Prot.	Size	Shpg.	Price
10-2885**	121060.00	3	230	13	145TC	7/8"	1.0	Manual	10 7/8" x 8 7/8" x 8 5/8"	51 lbs.	\$888.05
10-2887	131632.00	5	230	19.8	184TC	1 1/8"	1.15	Manual	13 15/16" x 11" x 11 1/4"	103 lbs.	\$1249.70
10-2889*	140694.00	7 1/2	208-230	36-32	213TC	1 3/8"	1.0	None	15 15/16" x 13 1/8" x 11 1/4"	150 lbs.	\$1466.45
10-2891*	140695.00	10	208-230	44-41.5	215TC	1 3/8"	1.0	None	18 3/4" x 13 1/8" x 11 1/4"	152 lbs.	\$1750.05

7.5 HP 3450 RPM 230 Volt AC Electric Motor



ITEM 10-3124
\$399.95

• New, Century general purpose electric motor. Capacitor start and run. Steel housing. No thermal overload protection.

SPECIFICATIONS

- Power 7 1/2 HP
- Voltage 230 AC
- Amperage 33.5-3.05 Amps
- Speed 3450 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 184T
- Rigid Base Mount
- Shaft 1 1/8" diam. x 2 3/4" w/ 1/4" keyway
- Size 13" x 11 1/4" x 11"
- Shpg. 90 lbs.

Marathon Washdown Motors



• New, Designed to handle high-pressure washdowns. White epoxy paint coat. Stainless steel fan and junction box covers. No thermal overload protection. Steel construction. Solid state encapsulated starting switch.

1 HP ITEM 10-3117 \$299.95

SPECIFICATIONS

- Model D56C17W5388
- Power 1 HP
- Voltage 115/208-230 AC
- Amperage 12.8/6.4 Amps
- Speed 1800 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56
- Base Mount
- Four 3/16" wide slots on 4 7/8" x 3" centers
- Shaft 5/8" dia. x 1 7/8" w/ 3/16" keyway
- Size 12 3/16" x 9 1/8" x 9"
- Shpg. 36 lbs.

2 HP ITEM 10-3118 \$319.95

SPECIFICATIONS

- Model 182TCWW7026
- Power 2 HP
- Amperage 21/11-10.5 Amps
- Speed 1740 RPM
- Frame 182T
- Base Mount:
- Four 3/8"-16 tapped holes on 5 7/8" diameter bolt circle
- Size 10.5" x 10" x 11"
- Shpg. 70 lbs.

1 1/2 HP, 115/230 VAC Grain Stirring Motor



ITEM 10-2769*
\$559.45

• Brand new, LEESON Model P6K17-FB18H grain stirring motor. High torque design. Designed for use in grain bins. Vertical shaft up with drain hole. Capacitor start and run motor. Steel construction. Manual overload protection.

SPECIFICATIONS

- Power 1 1/2 HP
- Voltage 115/208-230 AC
- Amperage 17.2/8.8-8.6
- Speed 1800 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.0
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56HZ
- Base mount 6 hole mount on 4 7/8" x 3" to 5" centers
- Shaft 7/8" dia. x 1.31" w/ 3/16" keyway
- Size 11" x 8.89" x 8.56"
- Shpg. 45 lbs.

1/2 HP 3500 RPM Motor



ITEM 10-3342
\$69.95

• New, RELIANCE model B81V3509 three phase, electric motor. Explosion proof. No thermal overload protection

SPECIFICATIONS

- Brand Reliance
- Model B81V3509
- Power 1/2 HP
- Frequency 50/60
- Voltage 190/380//230/460 AC
- Amperage 2.2/1.1//1.5/0.75 Amps
- Speed 2850//3500 RPM
- Rotation Reversible
- Phase 3
- Service Factor 1.00
- Bearings Ball
- Enclosure XPFC
- Duty Continuous
- Frame 56CZ
- Face Mount Four 3/8"-16 holes on 5 7/8" Bolt Circle
- Rigid Base Mount Four 0.34" dia. holes on 4 7/8" x 3" centers
- Shaft 5/8" dia. smooth x 1 1/8" stepped to 1/2" dia. x 7/8" w/ 1/8" keyway
- Size 12 1/4" x 8" x 7"
- Shpg. 37 lbs.

TECO - Westinghouse Motors

• New, TECO-WESTINGHOUSE general purpose electric motors. Capacitor start and run. Steel housing. Automatic reset overload protection.

1/4 HP
ITEM 10-3358
\$69.95

SPECIFICATIONS

- Model Number SPT0/22
- Power 1/4 HP
- Voltage 115/208-230 AC
- Amperage 2.56/1.42-1.28
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 48
- Rigid Base Mount:
- Shaft 1/2" diam. x 1 1/2" w/ Flat
- Size 9 1/4" x 7 3/4" x 7 1/4"
- Shpg. 23 lbs.



1/3 HP
ITEM 10-3362
\$79.95

SPECIFICATIONS

- Model Number SPHT0/32
- Power 1/3 HP
- Voltage 115/208-230 AC
- Amperage 3.36/1.86-1.68
- Speed 3500 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure TEFC
- Duty Continuous
- Frame 56
- Rigid Base Mount:
- Shaft 5/8" diam. x 1 7/8" w/ 3/16" keyway
- Size 9 3/8" x 8" x 7 3/4"
- Shpg. 24 lbs.



1/2 HP
ITEM 10-3363
\$89.95

SPECIFICATIONS

- Model Number SPO/52
- Power 1/2 HP
- Voltage 115/208-230 AC
- Amperage 4.94/2.73-2.47
- Speed 3510 RPM
- Rotation Reversible
- Phase 1
- Service Factor 1.15
- Bearings Ball
- Enclosure ODP
- Duty Continuous
- Frame 48
- Rigid Base Mount
- Shaft 1/2" diam. x 1 7/8" w/ Flat
- Size 9 1/2" x 7 3/4" x 7 1/4"
- Shpg. 25 lbs.

