



16-1522



16-1525

## 12 VDC Fans

• New, axial fans. Provide airflow at very low sound levels. Low power consumption. Easy to mount with holes in each corner.



16-1531

ITEM	CFM	Mfg.	Watts	RPM	# Blades	db	Bearing	Size	Shpg.	Price
16-1522	9.5	GDT	1.2	6000	9	27	Sleeve	40mm x 40mm x 10mm	¼ lb.	\$2.99
16-1525	11.9	Protechnic	2.3	5800	9	34.6	Rifle	50mm x 50mm x 10mm	¼ lb.	\$2.99
16-1508	22	Globe	2.04		5	34	Ball	60mm x 60mm x 25mm	¼ lb.	\$2.49
16-1527	50	Delta	10.44		7	55	Ball	60mm x 60mm x 25mm	¼ lb.	\$3.49
16-1528	109	Nidec	20.7	8500	7	60	Ball	80mm x 80mm x 38mm	½ lb.	\$3.99
16-1531	110	SanAce	13.2	5000	7	50	Ball	92mm x 92mm x 38mm	½ lb.	\$3.99
16-1558	285	TKFAN	30		7	72	Ball	120mm x 120mm x 38mm	½ lb.	\$4.95

### 10 CFM 12 VDC Blower

ITEM 16-1545  
**\$6.95**

• New, NICEC Gamma28 model A33475-68 centrifugal blower. Brushless design with lubricated ball bearing. Flat mounting on back side. 2 thru holes for mounting.

#### SPECIFICATIONS

- Flow 10 CFM max.
- Voltage 12 DC
- Amperage 0.29 Amps
- Inlet 1 7/8" dia.
- Outlet 1 5/16" x 1 3/8"
- Size 3" x 3" x 1 1/8"
- Shpg. ¼ lb.



### 7 CFM 12 VDC Fan

ITEM 16-1561-A  
**\$3.99**

• New, Niced model U66R12MS1AB-53K09. Made for automatic ice makers. Rubber isolators for simple push in mounting.

#### SPECIFICATIONS

- Flow 7 CFM max.
- Voltage 12 DC
- Power 1.2 Watt
- Blades 9
- Mount 67mm sq.
- Size 65mm x 65mm x 15mm
- Shpg. ¼ lb.



## Top Quality Microswitches

• For limit switches, burglar alarm systems, etc. Shpg. ¼ lb.

### Standard Size Microswitches

Standard size 1 7/8" x 3/4" x 5/8".

#### Pushbutton



ITEM	CONTACTS	AMP	PRICE
(A) 11-1901	SPNO	15	\$.80
(B) 11-3388	SPNO	15	\$.99

### Miniature Microswitches

Miniature size 1 1/2" x 5/8" x 3/4".



ITEM	CONTACTS	AMP	PRICE
(A) 11-3695	SPDT	1	\$.99

## 24" Tubeaxial Belt Driven Fan

ITEM 16-1543  
**\$449.95**

• New, DAYTON mod 3C411 belt-drive tubeaxial fan. Features include steel housing and aluminum 6 blade fan. Sealed ball bearings. May be mounted either horizontally or vertically. Aerodynamic belt guard. Very minor corrosion from storage. Motor stand will fit 56,142 and 184 frame motors. Motor not included.

#### SPECIFICATIONS

- Air Flow 10,310 CFM
- Requires 3 HP motor and 1910 blade RPM
- Temperature Ratings 200°F inlet 104°F ambient
- Fan 24" dia. 6 blades
- Pulley 4.5" dia. dual A groove
- Shaft 1" dia.
- Mounting 8 holes 25 3/4" bolt circle
- Size 27" dia. x 18"
- Shpg. 34 lbs.



## 12 VDC Heavy Duty Cab Fan

Two Speed  
Metal Blades

ITEM 16-1458-12  
**\$68.25**

• Brand new, SERVICEMATE two speed cab fans. Metal mounting base with swivel ball joint to position air flow. Toggle switch for low/off/high. Aluminum fan blades with chromed steel shroud. Single wire installation (ground thru base).

#### SPECIFICATIONS

- Airflow 285 CFM (high speed)
- Voltage 12 DC
- Amperage 1.6/2.6 Amps
- Blade Dia. 6 1/4"
- Number of Blades 4
- Mount 4 hole pattern 1 3/4" x 1"
- Size 7 1/4" x 5" x 8 3/4"
- Shpg. 5 lbs.


## Stepper Motor Driven Low Flow Blower

ITEM 16-1450  
**\$24.95**

• Unused, blower assembly from a CPAP breathing machine. NOT FOR MEDICAL REPLACEMENT PURPOSES. Heavy aluminum housing with isolation to control sound. Performance and motor specification are unknown. Wiring diagram is NOT available.

#### SPECIFICATIONS

- Motor Stepper (8 leads)
- Duty Continuous
- Inlet 3/4" OD tubing
- Outlet 3/4" OD tubing
- Size 7 1/2" x 8" x 3 1/2"
- Shpg. 5 lbs.



## 12 VDC Cab Fan

ITEM 16-1503  
**\$19.99**

• Brand new, two speed cab fan. Metal mounting base with swivel ball joint to position air flow. Toggle switch for low/off/high. Aluminum fan blades with chromed steel shroud. Two wire installation.

#### SPECIFICATIONS

- Voltage 12 DC
- Amperage 0.6/0.9 Amps
- Blade Dia. 6 1/4"
- Number of Blades 4
- Mount 3 hole pattern 2 3/16" B.C.
- Size 7 1/4" x 4 1/4" x 8 3/4"
- Shpg. 3 lbs.



## 26 CFM, 48 VDC

ITEM 16-1449  
**\$8.95**

• New, ROTRON Biscuit centrifugal blower. Operating voltage range 24-56 DC. Plastic body.

#### SPECIFICATIONS

- Model BD48B3
- Airflow 26 CFM
- Voltage 48 DC
- Pressure 0.87" H2O
- Inlet 2 3/4" dia.
- Outlet 1" x 2 3/16"
- Blower wheel 3 1/4" diam. x 5/8"
- Mount 4 holes thru body
- Size 4.8" x 4.8" x 1.6"
- Shpg. 2 lbs.



## 9 VDC Muffin Fan

ITEM 16-1047  
**\$5.99**

• New ROTRON. Supplied with housing to direct airflow through fan and turn 90° through 1 1/2" x 4 1/2" outlet. Ideal for moving air through cabinets with restricted access. Operates on 9 VDC, 0.6 amps. Approx. 90 CFM airflow. 5 blades, 4 1/4" diam. Size 5" x 3 1/8" x 5". Shpg. 2 lbs.

